

Technical specifications

WDM (Encrypted)

WDM Private Connection

WDM Private Connection characteristics	
Connection options	Single Dual Homed
Ethernet Bandwidth (Gb/s)	10, 100 ¹
SONET/SDH Bandwidth (Gb/s)	10
Latency per kilometer fiber-optic route	5 µsec
Latency per PoP location	5.2 µsec
Standard interfaces	
Ethernet (10Gb/s)	10GBASE-LR (10km) 10GBASE-ER (40km) 10GBASE-ZR (80km)
Ethernet (100Gb/s) ¹	100GBASE-LR4 (10km) 100GBASE-LR4 (80km)
SONET/SDH	OC-192/STM-64 SR-1 (10km) OC-192/STM-64 IR-2 (40km) OC-192/STM-64 LR-2 (80km)
OTN	OTU-2, OTU-2e SR-1 (10km) OTU-2, OTU-2e IR-2 (40km) OTU-4 (10km) ¹

WDM Private Network

WDM Private Network characteristics	
Connection options	Single Dual via geographically separated routes
Ethernet Bandwidth (Gb/s)	1, 10, 40 ² , 100
Fiber Channel Bandwidth (Gb/s)	1, 2, 4, 8, 16
SONET/SDH Bandwidth (Gb/s)	10
OTN framing types	OTU-2, OTU-2e
CPE management	At one of the customer locations
Latency per kilometer fiber-optic route	5 µsec
Latency per node	5,2 µsec
Compatible with Fiber Channel switches of the following providers	HP, Brocade, IBM, Cisco, Netapp
Standard interfaces	
Ethernet (1Gb/s)	1000Base-SX (500m) MMF (OM3 or better) 1000Base-LX (10km) SMF
Ethernet (10Gb/s)	10GBase-SR (300m) MMF (OM3 or better) 10GBase-LR (10km) SMF
Ethernet 40Gb/s	40GBase-LR4 (10km) MPO
Ethernet 100Gb/s	100GBase-LR4 (10km) SMF
Fiber Channel	FC1, FC2, FC4, FC8, FC16 (100m) MMF ³ FC1, FC2, FC4, FC8, FC16 (10km) SMF
SONET/SDH	OC-192/STM-64 SR-1 (10 km) SMF
OTN	OTU-2, OTU-2e SR-1 (10km) SMF OTU-2, OTU-2e IR-2 (40km) SMF

Technical specifications

WDM (Encrypted)

WDM Encrypted Private Connection

WDM Encrypted Private Connection characteristics	
Connection options	Single Dual Homed
Bandwidth Ethernet (Gb/s)	10
Latency per kilometer fiber-optic route	5 µsec
Latency per PoP location	5.2 µsec
Standard interfaces	
Ethernet 10 Gb/s	10GBASE-LR (10km)

WDM Encrypted Private Network

WDM Encrypted Private Network characteristics	
Connection options	Single Dual via geographically separated routes
Bandwidth Ethernet (Gb/s)	10, 40 ⁴ , 100
Bandwidth Fiber Channel (Gb/s)	4, 8
Bandwidth SONET/SDH (Gb/s)	10
Management CPE	On all customer locations
Latency per kilometer fiber-optic route	5 µsec
Latency per node	5.2 µsec
Compatible with Fiber Channel switches from these suppliers	HP, Brocade, IBM, Cisco, Netapp
Standard interfaces	
Ethernet (10Gb/s)	10GBase-SR (300m) MM (OM3 or better) 10GBase-LR (10km) SM
Ethernet 40Gb/s	40GBase-LR4 (10km) SM
Ethernet 100Gb/s	100GBase-LR4 (10km) SM
Fiber Channel	FC4, FC8 (100m) MM ⁵ FC4, FC8 (10km) SM
SONET/SDH	OC-192/STM-64 SR-1 (10km) SM

¹ 100G will be geographically rolled out between 2020 and 2023

² 40 Gb/s on request

³ Eurofiber advises against Multi Mode interfaces for Fiber Channel bandwidths of 4Gb/s and higher

⁴ 40 Gb/s on request

⁵ Eurofiber discommends Multi Mode interfaces for Fiber Channel bandwidths of 4 Gb/s and higher

Eurofiber Nederland

Safariweg 25-31
3605 MA Maarssen
+31 (0)30 242 87 00
info@eurofiber.nl