





MASTER LINK WITH & WITHOUT FLATS

WORKING LOAD LIMIT: 3,360 TO 142,440 LBS.

BENEFITS & FEATURES

- Designed to accept HA800 chain, wire rope and synthetic attachments
- Use with mechanical and welded assemblies
- Sizes up to 1-1/4" available with flats to accommodate Omega link
- 100% proof tested
- 6:1 design factor
- Extra wide body makes these links ideal for wire rope applications and use with Omegaloks. Master link with flat allows for easy installation of these attachments.



Can be used with included angles up to 120°

Trade Size (in.)	Working Load Limit with Wire Rope & Synthetics (lbs.)	Product Code	Nominal Dimensions (in.)			Flat Dimensions (in.)		Weight (lbs.)	Sling Type and Size (in.)	
			Material Diameter A	Inside Length B	Inside Width C	Width	Thickness		Single	Double
7/16	3,360	ML040 ML040NF	0.44	4.13	2.29	0.94 —	0.28 —	0.50	7/32 & 9/32	7/32
1/2	4,600	ML050 ML050NF	0.56	4.84	2.69	0.94 —	0.28 —	1.02	—	7/32
5/8	7,200	ML063 ML063NF	0.63	5.29	2.98	1.22 —	2.81 —	1.34	3/8	9/32
3/4	11,360	ML075 ML075NF	0.75	6.61	3.72	1.41 —	0.40 —	2.36	1/2	3/8
7/8	13,840	ML087 ML087NF	0.88	7.35	4.14	1.56 —	0.44 —	3.60	—	—
1	21,200	ML100 ML100NF	1.00	7.53	4.30	1.56 —	0.53 —	5.20	5/8	1/2
1-1/4	29,920	ML125 ML125NF	1.25	9.26	5.29	1.56 —	0.68 —	9.60	3/4 & 7/8	5/8
1-1/2	42,400	ML150	1.50	11.03	6.30	—	—	16.20	1	3/4
1-3/4	57,720	ML175	1.75	12.86	7.35	—	—	25.10	—	7/8
2	75,360	ML200	2.00	14.70	8.40	—	—	41.00	1-1/4	1
2-1/4	95,360	ML225	2.25	16.54	9.45	—	—	58.00	—	—
2-1/2	117,720	ML250	2.50	18.38	10.50	—	—	74.90	—	1-1/4
2-3/4	142,440	ML275	2.75	20.21	11.55	—	—	99.80	—	—

NOTE: Master link with flats are available through 1-1/4" only. Part numbers with "NF" are for master links WITHOUT flats.

