



EAN:	4013288157744	Size:	70x65x12 mm
Part number:	05057693001	Weight:	70 g
Article number:	Bit-Check 6 TX Impaktor 1	Country of origin:	CZ
		Customs tariff number:	82079030

- Upright positionable, multi-component Bit-Check
- Impaktor technology for above-average service life
- Particularly suitable for use with customary impact drivers
- Diamond coating for a secure fit in the screw, literally bites into the screwhead to prevent cam-out
- Take it easy tool finder: colour coding according to profile and size

6 Wera Impaktor bits tidily arranged in a minimum of space in a practical Bit-Check. The Impaktor technology offers an above-average service life even under extreme circumstances thanks to the best possible utilisation of the material properties and the optimised geometry. The bit tip is coated with tiny diamond particles; this reduces the risk of any slipping out of the screw head thanks to the enhanced frictional resistance.

Web link
<https://www.wera.de/en/05057693001>

Wera - Bit-Check 6 TX Impaktor 1
05057693001 - 4013288157744

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

At the workplace



The Bit-Checks can be positioned upright at the workplace so the tool is always quickly to hand.

Improved productivity



For use with impact screwdrivers. Improve productivity when screwdriving with power tools.

Above-average service life



Maximum utilisation of the material properties, a very special geometry - designed particularly to meet the extreme demands - as well a specific manufacturing process mean that Wera Impaktor tools have an above-average service life.

Impaktor-Bits



For an above-average service life. Maximum utilisation of the material properties, a very special geometry - designed particularly to meet the extreme demands - as well a specific manufacturing process mean that Wera Impaktor tools have an above-average service life. Another product advantage is the coating of the Impaktor bits with minute diamond particles. These diamond particles reduce the cam-out effects - particularly high in power tool applications - which can lead to a slipping out of the screw head. The diamond particles literally bite themselves into the screw recess. This means that less contact pressure is required, something that greatly delays fatigue setting-in in power tool screwdriving jobs.


Web link

<https://www.wera.de/en/05057693001>

Wera - Bit-Check 6 TX Impaktor 1
05057693001 - 4013288157744


Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Torsion zone



Torsion zone specially designed to absorb such forces and thereby protect the bit tip.

Reduced contact pressure




These diamond particles reduce the cam-out effects - particularly high in power tool applications - which can lead to a slipping out of the screw head. The diamond particles literally bite themselves into the screw recess. This means that less contact pressure is required, something that greatly delays fatigue setting-in in power tool screwdriving jobs.

TriTorsion system



The combination of the double torsion zones in the Impaktor holder and the torsion zone in the Impaktor bit results in the so-called TriTorsion system.

Take it easy tool finder system



The Take it easy Bit-Checks have bits with a sleeve which - from its colour (e.g. red = Phillips) and size designation - make it simple to access the right bit quickly.

Web link

<https://www.wera.de/en/05057693001>

Wera - Bit-Check 6 TX Impaktor 1
05057693001 - 4013288157744

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Set contents:

867/4 IMP DC Impaktor TORX® bits, TX 20 x 50 mm



- 2x TX 20 x 50 mm
- 2x TX 25 x 50 mm
- 1x TX 30 x 50 mm
- 1x TX 40 x 50 mm

Web link

<https://www.wera.de/en/05057693001>

Wera - Bit-Check 6 TX Impaktor 1
05057693001 - 4013288157744

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de