

Series 7400 ESD Kraftform adjustable torque screwdrivers (0.1-1.0 Nm), 7436 ESD
x 0.30-1.00 Nm



EAN:	4013288179029	Size:	170x40x40 mm
Part number:	05074788001	Weight:	166 g
Article number:	7400 ESD Halfmoon	Country of origin:	CZ
		Customs tariff number:	82054000

- Adjustable Kraftform ESD torque screwdriver with quick-release chuck
- ESD-safe tool thanks to surface resistance of $\leq 10^{+9}_{-9}$ Ohm
- Multi-component Kraftform Micro handle for fast and ergonomic screwdriving
- Hexagonal anti-roll feature against rolling away
- Suitable for bits with 4 mm halfmoon and 4 mm HIOS drive

Wera torque screwdriver. Dependable protection against electrostatic energy and associated damage. Variable torque setting option with highest precision. Simple adjustment of the required torque value without any special tools. Easy-to-read scale value. Rapidaptor quick-release technology for rapid bit change. Unlimited torque to loosen seized screws. Multi-component Kraftform handle with hard and soft zones for high working speeds, whilst being easy on the hand. Suitable for bits with a 4 mm Halfmoon drive (Wera series 9) and a 4 mm HIOS drive (Wera series 21).



Web link
<https://www.wera.de/en/05074788001>

Wera - 7400 ESD Halfmoon
05074788001 - 4013288179029

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Adjustable Torque Screwdrivers

Wera ESD Tools

For Halfmoon and HIOS Bits


Setting with Speed



Wera's adjustable torque screwdrivers allow variable torque settings with maximum precision and ensure that the user gets the very best results in the familiar Wera design with superior ergonomics.



The requirements for ESD-safe screwdrivers are specified in the European standard DIN EN 61340-5-1. This standard also includes a handle that has to be out of a defined conductive material. The Wera products in the ESD series satisfy these standards and the even more stringent requirements demanded by some technology companies.



Features a combination bit holder for both bits with Halfmoon and bits with HIOS drive.



Simple setting of the required torque by hand.

Attachable magnifying glass



Articles 1430 ESD and 1431 ESD, all come with a magnifying glass. This can be easily attached on to the scale, dramatically improving visibility.

Measurement accuracy



Measurement accuracy is $\pm 6\%$ (article 1430: $\pm 10\%$) in accordance with the standard DIN EN ISO 6789. Distinctly audible and noticeable excess-load signal when the pre-set torque is reached.

Unlimited torque




Unlimited torque for loosening seized screws.

Torque Tools



Wera's torque tools offer torque-controlled screw tightening so as to avoid damage to the screw or workpiece and to ensure the integrity of the screw connection. This makes work-intensive drilling-out of screws and unproductive downtimes a thing of the past. It is also important whenever repeat accuracy is required. They come with an ergonomic Kraftform handle and have a distinctly audible and perceptible click signal whenever the required torque value is reached. No time-consuming blade changes; instead of special blades, conventional bits conforming to C 6,3 and E 6,3 or even $\frac{1}{4}$ " sockets can be used.

Further versions in this product family:

							
	art. no.	Nm	Nm	mm	mm	inch	
	05074786001 ¹⁾	7435 ESD	0.10-0.34	0.015	89	142	5 7/16"
	05074788001 ¹⁾	7436 ESD	0.30-1.00	0.05	89	142	5 7/16"

¹⁾ With attachable magnifying glass, significantly improving readability.

Web link

<https://www.wera.de/en/05074788001>

Wera - 7400 ESD Halfmoon
05074788001 - 4013288179029

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de