



# ISUZU GRR 16-210 AMT

SMOD	M220FM3
Axle layout	4X2
Control	Forward

MASS		
Permissible body + payload	kg	12280
Tare - total (T) - Estimated	kg	3720
Tare - front	kg	2240
Tare - rear	kg	1480
GVM	kg	11000
V	kg	11000
GCM	kg	16000
D/T	kg	16000
Axle - front GA/GAU	kg	3600
Axle - front A/AU	kg	3600
Axle - rear GA/GAU	kg	7700
Axle - rear A/AU	kg	7600
Litres of fuel tank 1 included in tare	ltrs	15
Litres of fuel tank 2 included in tare	ltrs	-
Tools included in tare	Jack, warning triangle, basic tool kit	
Spare wheel included in tare	Yes	
Fifth Wheel Included in tare	-	

PERFORMANCE		
Gradeability at V	%	45
Gradeability at D/T	%	31
Max. geared road speed (Without SLD)	km/h	117
Max allowable speed (SLD for SA)	km/h	80

MAJOR DIMENSIONS		
Overall length	mm	7425
Overall width	mm	2120
Wheelbase	mm	4360
CA - cab to bogie/rear axle	mm	3804
CE - Cab to end of chassis	mm	5699
OH - Overall height	mm	2530
FOH - Front overhang	mm	1170
ROH - Rear overhang	mm	875
Rear axle bogie spacing	mm	N/A
1/2 rear axle bogie spacing	mm	N/A
EH - Chassis height rear	mm	955
HH - Ground clearance	mm	186
Chassis width rear	mm	840
Turning radius (curb to curb)	mm	6600
Turning radius (wall to wall)	mm	7350

ENGINE		
Make	ISUZU	
Model	4HK1-TCS	
Capacity	cm3	5193
Layout	Diesel inline 4	
Type	Turbocharged Intercooled Common Rail	
Power at r/min	kW	154 @ 2600
Torque at r/min	Nm	637 @ 1600 - 2600
Emissions standard	Euro 3	

CLUTCH		
Make	N/A	
Model	N/A	
Type	N/A	
Diameter	mm	N/A
Operation	Automated Hydraulic Controlled Wet Clutch	

TRANSMISSION		
Make	ISUZU	
Model	MZW6P (AMT)	
Type	Synchromesh	
Shift	Automated Manual	
No. of gears forward	6	
Crawler gear ratio	-	
First Gear Ratio : 1 (crawler where applicable)	6.615	
2nd gear ratio	4.095	
3rd gear ratio	2.358	
4th gear ratio	1.531	
5th gear ratio	1	
6th gear ratio	0.722	
7th gear ratio	-	
8th gear ratio	-	
9th gear ratio	-	
Top Gear Ratio : 1	-	
Rev	6.615	
Permanent 4X4	No	
Central Differential lock	No	
Rear Differential lock	No	
PTO (Power Take-Off)	PTO Ready	

DRIVE AXLE		
Make	ISUZU	
Model Drive axle Front	F036	
Model Drive axle rear	R077	
Hypoid	Standard	
Final ratio :1	4.875	

SUSPENSION		
Front	Multi-Leaf Springs	
Rear	Multi-Leaf Springs	
Shock absorbers	Front	
Stabilisers	Front	

STEERING		
Operation	Power	

BRAKES		
System type	Air over hydraulic	
Front	Drums	
Rear	Drums	

BRAKES		
Anti-lock braking system (ABS)	Standard	
Park/emergency system	Spring	
Exhaust brake	Standard	
Engine brake	No	
Retarder	No	
Hill Start Assist (HSA)	Standard	

ELECTRICAL & FUEL		
Fuel tank 1 capacity	ltrs	200
Fuel tank 2 capacity	ltrs	0

TYRES		
Size and ply rating - front & rear (Tubeless - Opt)	-	
Size and ply rating - front	235/75 R 17.5	
Size and ply rating - rear	235/75 R 17.5	

CAB & EXTRAS		
Type	Day	
Roof	Low	
No. of bunks	0	
No. of seats	3	
Airconditioning	Optional	
Radio/USB	Optional	
Radio/CD	-	
Speakers	Standard	
USB charger	Standard	
Daytime Running Lights (DRL)	Standard	
Telematics	Standard	
Driver and far passenger airbags	Standard	
Central locking	Standard	
Electric windows	Standard	
Tachograph	Optional	
On-board computer	Yes	
Tilt cab	Yes	
Jost 5th Wheel - JSK37C185	Yes	
Catwalk	Yes	

**BUILD FOR LIFE**

www.isuzu.co.za      
**ISUZU**  
*With you, for the long run*