



ISUZU NMR 250

SMOD	M220NB6
Axle layout	4X2
Control	Forward

MASS		
Permissible body + payload	kg	3370
Tare - total (T)	kg	2130
Tare - front	kg	1460
Tare - rear	kg	670
GVM	kg	5500
V	kg	5500
GCM	kg	8700
D/T	kg	8700
Axle - front GA/GAU	kg	2900
Axle - front A/AU	kg	2300
Axle - rear GA/GAU	kg	5000
Axle - rear A/AU	kg	4360
Litres of fuel tank 1 included in tare	ltrs	15
Tools included in tare	Jack, warning triangle, basic tool kit	
Spare wheel included in tare	Yes	

PERFORMANCE		
Gradeability at V	%	41.76
Gradeability at D/T	%	26.40
Max. geared road speed (Without SLD)	km/h	122
Max allowable speed (SLD for SA)	km/h	100

MAJOR DIMENSIONS		
OL - Overall length	mm	6020
OW - Overall width	mm	1815
WB - Wheelbase	mm	3345
CA - Cab to bogie/rear axle	mm	2892
CE - Cab to end of chassis	mm	4457
OH - Overall height	mm	2200
FOH - Front overhang	mm	1110
ROH - Rear overhang	mm	1565
EH - Chassis height rear	mm	810
HH - Ground Clearance	mm	210
Chassis width rear	mm	700
Turning radius (curb to curb)	mm	7250
Turning radius (wall to wall)	mm	7950

ENGINE		
Make	ISUZU	
Model	4JJ1-TCC	
Capacity	cm3	2 999
Layout	Diesel inline 4	
Type	Turbocharged Intercooled Common Rail	

ENGINE (CONTINUED)		
Power at r/min	kW	96 @ 3050
Torque at r/min	Nm	330 @ 1400 - 3200
Emissions standard	Euro 2	

CLUTCH		
Make	Exedy	
Model	300	
Type	Single	
Diameter	mm	300
Operation	Hydraulic Assisted	
Auto Slack Adjuster	Standard	

TRANSMISSION		
Make	ISUZU	
Model	MYY5T	
Type	5 Speed synchromesh	
Shift	Manual Gearshift	
No. of gears forward	5	
1st gear ratio	5.315	
2nd gear ratio	3.053	
3rd gear ratio	1.655	
4th gear ratio	1	
5th gear ratio	0.721	
6th gear ratio	-	
REV	5.068	
Transfer case	No	
Manual Locking Hubs (4X4)	No	
Limited Slip Differential	No	
PTO	PTO Ready	

DRIVE AXLE		
Make	ISUZU	
Model drive axle front	F029	
Model drive axle rear	R050	
Hypoid	Standard	
Final ratio :1	5.125	

SUSPENSION		
Front	Semi-elliptic springs	
Rear	Semi-elliptic springs	
Shock absorbers	Front and rear	
Stabilisers	Yes	

STEERING		
Operation	Power	

BRAKES		
System type	Vacuum + Power Assist	
Front	Drums	
Rear	Drums	
Anti-lock braking system (ABS) with EBD	Standard	
Park/emergency system	Drum on Propshaft	
Exhaust brake	Standard	

ELECTRICAL & FUEL		
Fuel tank 1 capacity	ltrs	100
Fuel tank 2 capacity	ltrs	0

TYRES		
Size and ply rating - front & rear (Tubed - Opt)	-	
Size and ply rating - front & rear (Tubeless)	205/75R16C	

CAB & EXTRAS		
Type	Day	
Roof	Low	
No. of bunks	0	
No. of seats (lap rear & centre)	3	
Airconditioning	Optional	
Radio/USB	Optional	
Speakers	Standard	
USB Charger	Standard	
Daytime Running Lights (DRL)	Standard	
Telematics	Standard	
Driver & Far Passenger Airbags	Standard	
Central locking	Standard	
Electric windows	Standard	
Tilt cab	Yes	

Disclaimer: The information contained in this document was accurate at the time of issue in September 2023. Vehicles may differ from images shown. Please contact your ISUZU Dealer to verify information. Ts&Cs apply. E&OE.

BUILD FOR LIFE

www.isuzu.co.za    
ISUZU
With you, for the long run