

10,000 km or 12 Months Service Schedule TF Series (RT) - 2.5L(4JA1) Diesel



PLEASE NOTE:

- 1. Refer to the Service Interval Guideline by Country for the correct Interval by kilometers or months, whichever occurs first.
- 2. This Service Schedule will have preference over the Owner's Manual and Warranty & Service Guide (Refer to updated date).
- 3. Refer to the Warranty and Service Guide for Severe Driving Conditions.
- 4. Consult the Owner/Customer prior to any additional work being carried out as an additional cost will be charged for items not covered under warranty.

NOTE: APPLICABLE FOR 10,000 KM TO 100,000 KM OR 12 MONTHS TO 120 MONTHS SERVICE INTERVALS

Job Card No.: Date :							Model :									
Customer Name:							KM Reading:									
Service Adviso	r :	Authorisation No:					Technicia	n (Print) :								
		I = Inspection. After inspection clean and correct, or repla	ace as nece	essary - R = I	Replace - L	= Lubricat	e - A = Adjı	ıst								
SERVICE INTERV	CE INTERVAL EVERY KMs (x 1000) 10 20 30 40 50 60 70 80 90 100								ОК	NOT						
or months, which	ever o	occurs first) Months	12	24	36	48	60	72	84	96	108	120	UK	OK		
		Labour hrs.	1,2	1,7	1,2	1,7	1,2	1,7	1,2	1,7	1,2	1,7				
	1	Engine Oil and Filter	R	R	R	R	R	R	R	R	R	R				
	2	Fuel Filter	R	R	R	R	R	R	R	R	R	R				
	3	Fuel sedimentor for presence of water	I	I		ı	I	I	I	ı	I	I				
ENGINE	4	Fuel leakage at tank, cap and pipes	I	I	I	ı	I	I	1	ı	I	I				
	5	Air filter element (I & R) and all air cleaner hose fitments for tightness (I)	I	R	I	R	1	R	1	R	I	R				
	6	Valve Clearance	-	Α	-	Α	-	Α	-	Α	-	Α				
	7	All engine drive belts for tension and damage and check pulley condition (replace if needed)		1		I	I	I	I	I	ı	I				
	8	Run engine through operating range & check for excessive smoke		1		I	I	I	I	I	ı	I				
		Coolant system for leaks (press. test radiator & cap) & check coolant concentration (50% gly.)	I	I	I	I	1	I	1	1	I	I				
		Coolant concentration (50 % glycol) - Add 0.3 hrs (Record coolant freezing point on the job card)	I	I	I	- 1	R	- 1	1	- 1	I	R				
		Radiator core (check for foreign objects) and fan operation	I	I	I	I	1	I	1	- 1	I	- 1				
		Exhaust system for leaks and mountings for tightness or damage	I	I	I	- 1	1	- 1	1	- 1	I	- 1				
		All hoses & pipes in engine compartment for tightness or damage	I	I	I	- 1	1	- 1	1	- 1	I	- 1				
		Brake pedal function, travel and free play	I	I	I	1	1	1	1	- 1	I	- 1				
		Brake fluid level	ı	I	ı	ı	I	ı	I	I	ı	ı				
SERVICE		Brake fluid - Add 0.3 hrs		R		R	ı	R	I	R	ı	R				
BRAKE		Front disc brake pads & discs for wear (Record thickness size of pads & discs on the job card)	ļ	I		ı	I	ı	ı	ı	l	- 1				
		Rear brake linings & drums for wear (Record thickness size of shoes & drums on the job card)	I&A	I&A	I&A	I&A	I&A	I&A	I&A	I&A	I&A	I&A				
		Brake pipes & hoses for leaks, loose connections or damage	l	ı	I	ı	ı	ı	ı	ı	ı	ı				
		Clutch pedal function, travel and free play & fluid leaks	<u> </u>	!	<u> </u>	ı	ı	ı	I		ı	ı				
CLUTCH		Clutch fluid level	<u> </u>	1	<u> </u>	ı	ı	I	I	I	ı	I				
	22	Clutch fluid - Add 0.1 hrs		R		R	l	R	l	R	l	R				
TRANS. & TRANSFER CASE	23	Manual transmission fluid-add 0.3 hrs for replacement	R	I	I	I	R	I	I	I	R	Ι				
PROPSHAFT	24	Prop shaft mounting and universal joints & sliding sleeve for looseness and excessive wear	1	L	1	L	1	L	- 1	L	1	L				
FRONT/	25	Rear axle fluid (without limited slip diff) - add 0.3 hrs for replacement	ı	ı	I	I	I	I	I	R	I	I				
REAR AXLE	26	All axle shafts and housing for distortion or damage	1	I	I	1	1_	I	1	1	I	1				

CONTINUED....



10,000 km or 12 Months Service Schedule TF Series (RT) - 2.5L(4JA1) Diesel



PLEASE NOTE:

- 1. Refer to the Service Interval Guideline by Country for the correct Interval by kilometers or months, whichever occurs first.
- 2. This Service Schedule will have preference over the Owner's Manual and Warranty & Service Guide (Refer to updated date).
- 3. Refer to the Warranty and Service Guide for Severe Driving Conditions.
- 4. Consult the Owner/Customer prior to any additional work being carried out as an additional cost will be charged for items not covered under warranty.

Date

NOTE: APPLICABLE FOR 10,000 KM TO 100,000 KM OR 12 MONTHS TO 120 MONTHS SERVICE INTERVALS

I = Inspection. After inspection clean and correct, or replace as necessary - R = Replace - L = Lubricate - A = Adjust

SERVICE INTER	NTERVAL EVERY KMs (x 1000) 10		10	20	30	40	50	60	70	80	90	100	ок	NOT	
(or months, which	ever o	occurs first)	1onths	12	24	36	48	60	72	84	96	108	120	Oit	OK
	27	Steering wheel play and function		-	ı	ı	I		I	I	I		I.		
STEERING	28	Power steering fluid		ı		ı	R		-	I	R				
STEEKING	29	Steering rack and ball joint rubber boots		-	ı	ı	I		I	I	I		_		
	30	Wheel alignment inspection (to be offered to customer)				Reco	mmended e	very service	-cost for cu	stomer's acc	count				
PARKING		Parking brake function - lever travel & ratchet for damage		1	1	I	I	I	I	1	I	I	I		
BRAKE	32	Parking brake cables for looseness or damage		ı	1	I	I	I	I	1	I	I	I		
	33	Suspension front & rear - strut rubbers, bushes, tie-rod ends & link arms		-	ı	ı	I		I	I	I		_		
CHASSIS &	34	Shock absorbers for leaks and looseness		I	ı	ı	I		I	I	I		_		
SUSPENSION	35	Leaf/coil springs for damage		I	ı	ı	I		I	I	I		_		
	36	Cab mountings for looseness and damage			- 1	ı	I		I	I	I				
	37	Tyre Pressure - Check and correct (incl. spare wheel)		ı	- 1	ı	1	I	- 1	1	I	I	I		
	38	Inspect tyres & rims for damage (incl. spare wheel)		- 1	1	I	I	I	I	I	I	I	-		
WHEELS	39	Wheel bearing (front & rear) - Inspect for bearing play		ı	- 1	ı	1	I	- 1	1	I	I	I		
		Rotate tyres & torque wheel nuts as per specification-Refer Bulletin GEN-2015-09		Т	Т	Т	Т	Т	Т	Т	Т	Т	Т		
	41	Front wheel bearing grease and seal - Add 1.1 hrs		- 1	I	ı	- 1	R	- 1	- 1	1	I	R		
	42	Vehicle systems - Check all ECUs for DTCs & reset service interval*		1	1	I	I	I	I	I	I	I	Ι		
	43	Starter and alternator function / output		- 1	1	I	I	I	I	I	I	I	-		
ELECTRICAL	44	Battery electrolyte level and specific gravity*		- 1	1	I	I	I	I	I	I	I	-		
EQUIPMENT	45	Check operation of all lights, hooter, instruments, a/c, radio, wiper blades & washers		1	1	I	I	I	I	1	I	I	_		
	46	Remote key battery*		I	R	ı	R		R	1	R	I	R		
	47	Airbag system and Airbag warning light, visual inspection		I	1	ı	- 1		1	1	1		_		
	48	Seatbelts function and damage		I	ı	ı	I		I	I	I		_		
	49	Inspect chassis and body for corrosion - Complete Inspection Sheet				Attacl	h copy of Sh	eet to Job C	Card at ever	y service int	erval				
BODY	50	Doors, bonnet, tailgate links, locks and door restraints to Check/Adjust/Clean/Lubricate		- 1	L	ı	L		L	- 1	L	I	L		
	51	Pollen filter*		- 1	R	ı	R		R	- 1	R	I	R		
		Air conditioner drain pipe for drainage		1	1	1	1	I	1	- 1	1	I	I		
SAFETY		Check for open RECALLS or SERVICE CAMPAIGNS		Attach copy of IVH to Job Card at every service interval											
TESTING	54	Road Test						Ι							

^	wr	nere	e fit	tec
	VVI	ICIC	, III	ıec

where grease nipples are fitted.

Customer Signature

Attach one copy to Customer's Invoice Attach one copy to Job Card

I was informed of the service cost & additional items that needs attention.

Technician Signature

I hereby confirm that all items have been checked and and rectifed where required.

Updated. Oct 2023 Document No. CKD / ISUZU

2.5 Diesel



10,000 km or 12 Months Service Schedule TF Series (RT) - 2.5L(4JA1) Diesel



PLEASE NOTE:

- 1. Refer to the Service Interval Guideline by Country for the correct Interval by kilometers or months, whichever occurs first.
- 2. This Service Schedule will have preference over the Owner's Manual and Warranty & Service Guide (Refer to updated date).
- 3. Refer to the Warranty and Service Guide for Severe Driving Conditions.
- 4. Consult the Owner/Customer prior to any additional work being carried out as an additional cost will be charged for items not covered under warranty.

NOTE: APPLICABLE FOR 110,000 KM TO 180,000 KM O
132 MONTHS TO 216 MONTHS SERVICE INTERVALS

Service Advisor :	Authorisation No:	Technician (Print) :
Customer Name:	VIN:	KM Reading:
Job Card No.:	Date :	Model:

I = Inspection. After inspection clean and correct, or replace as necessary - R = Replace - L = Lubricate - A = Adjust

OEDVIOE INTES					120	120	110	150	100	170	100			
SERVICE INTERVAL EVERY KMs (x 1000)				110	120	130	140	150	160	170	180	OK	NOT OK	
(or months, which	ever	,		132	144	156	168	180	192		204 216			
		Labour	nrs.	1,2	1,7	1,2	1,7	1,2	1,7	1,2	1,7			
		Engine Oil and Filter		R	R	R	R	R	R	R	R			
		Fuel Filter		R	R	R	R	R	R	R	R			
		Fuel sedimentor for presence of water		ı	I	I	ı	I	I	I	ı			
		Fuel leakage at tank, cap and pipes		ı	I	I	ı	I	I	I	ı			
		Air filter element (I & R) and all air cleaner hose fitments for tightness (I)		I	R	I	R	I	R	I	R			
		Valve Clearance		-	Α	-	Α	-	Α	-	Α			
ENGINE	7	All engine drive belts for tension and damage and check pulley condition (replace if needed)		I	1		ı	I	I	I	I			
	8	Run engine through operating range & check for excessive smoke		I	1		ı	I	I	I	I			
	9	Coolant concentration (50 % glycol) - Add 0.3 hrs (Record coolant freezing point on the job card)		I	1		ı	I	I	I	I			
	10 Coolant concentration (50 % glycol) - Add 0.3 hrs			I	1	I	I	R	I	I	I			
	11	Radiator core (check for foreign objects) and fan operation		I	1	I	I	I	I	I	I			
	 12 Exhaust system for leaks and mountings for tightness or damage 13 All hoses & pipes in engine compartment for tightness or damage 			I	1		1	I	I	I	ı			
				I	1	I	I	I	I	I	I			
	14	Brake pedal function, travel and free play		_	1		ı	1	I	I	I			
	15	Brake fluid level		_	1		I	I	I		I			
SERVICE	16	Brake fluid - Add 0.3 hrs		_	R	I	R	I	R	I	R			
BRAKE	17	Front disc brake pads & discs for wear (Record thickness size of pads & discs on the job card)		_	1	I	I	I	I	I	I			
	18	Rear brake linings & drums for wear (Record thickness size of shoes & drums on the job card)		I&A										
	19	Brake pipes & hoses for leaks, loose connections or damage		_	1	I	I	I	I	I	I			
	20	Clutch pedal function, travel and free play & fluid leaks		I	1		I	- 1	I	I	I			
CLUTCH	21	Clutch fluid level		-	1		ı	- 1	ı		ı			
	22	Clutch fluid - Add 0.1 hrs		_	R		R	I	R	I	R			
TRANS. &														
TRANSFER	RANSFER 23 Manual transmission fluid-add 0.3 hrs for replacement CASE			I	1	R	I	I	I	R	I			
CASE														
PROPSHAFT		Prop shaft mounting and universal joints & sliding sleeve for looseness and excessive wear		I	L	I	L	I	L	I	L			
FRONT/	25	Rear axle fluid (without limited slip) - add 0.3 hrs for replacement		I	I	I	ı	I	R	I	I			
REAR AXLE	26	All axle shafts and housing for distortion or damage		Ī	1			1	I					
		TAULED												

CONTINUED....



10,000 km or 12 Months Service Schedule TF Series (RT) - 2.5L(4JA1) Diesel



PLEASE NOTE:

- 1. Refer to the Service Interval Guideline by Country for the correct Interval by kilometers or months, whichever occurs first.
- 2. This Service Schedule will have preference over the Owner's Manual and Warranty & Service Guide (Refer to updated date).
- 3. Refer to the Warranty and Service Guide for Severe Driving Conditions.
- 4. Consult the Owner/Customer prior to any additional work being carried out as an additional cost will be charged for items not covered under warranty.

Date

NOTE: APPLICABLE FOR 110,000 KM TO 180,000 KM OR 132 MONTHS TO 216 MONTHS SERVICE INTERVALS

	I = Inspection. After inspection clean and correct, or replace as necessary - R = F	Replace - I	_ = Lubricat	e - A = Adjı	ıst							
SERVICE INTER	/AL EVERY KMs (x 1000)	110	120	130	140	150	160	170	180	ок	NOT	
(or months, which	ever occurs first) Months	132	144	156	168	180	192	204	216	OK	OK	
	27 Steering wheel play and function	I	I	I	I	ı	I	ı	I			
STEERING	28 Power steering fluid	I	R	I	I	!	R	1	!			
STEERING	29 Steering rack and ball joint rubber boots	I	I	I	I	!	!	1	!			
	30 Wheel alignment inspection (to be offered to customer)		Reco	mmended e	every service	e-cost for cu	istomer's ac	count				
PARKING	31 Parking brake function - lever travel & ratchet for damage	I	I		_	1	1	- 1	-			
BRAKE	32 Parking brake	I	1		I	1	1	1	I			
	33 Suspension front & rear - strut rubbers,bushes,tie-rod ends & link arms	I	1		I	1	1	1	I			
CHASSIS &	34 Shock absorbers for leaks and looseness	I	1	ı	I	- 1	I	- 1	- 1			
SUSPENSION	35 Leaf/coil springs for damage	I	1	ı	I	- 1	I	- 1	- 1			
	36 Cab mountings for looseness and damage	I	I	ı	1	1	1	- 1	- 1			
	37 Tyre Pressure - Check and correct (incl. spare wheel)	I	I	ı	1	1	1	- 1	- 1			
	38 Inspect tyres & rims for damage (incl. spare wheel)	I	I	ı	1	1	1	- 1	- 1			
WHEELS	39 Wheel bearing (front & rear) - Inspect for bearing play	I	I	I	I	1	I	I	ı			
	40 Rotate tyres & torque wheel nuts as per specification-Refer Bulletin GEN-2015-09	T	Т	Т	T	T	Т	T	T			
	41 Front wheel bearing grease and seal - Add 1.1 hrs	ı	I		ı	R	I	I	ı			
	42 Vehicle systems - Check all ECUs for DTCs & reset service interval*	I	I		I	ı	ı	ı	I			
	43 Starter and alternator function / output	I	I		I	ı	ı	ı	I			
ELECTRICAL	44 Battery electrolyte level and specific gravity*	I	I		I	ı	ı	ı	I			
EQUIPMENT	45 Check operation of all lights, hooter, instruments, a/c, radio, wiper blades & washers	I	I	ı	I	1	ı	ı	1			
	46 Remote key battery*	I	R		R	1	R	I	R			
	47 Airbag system and Airbag warning light, visual inspection	I	I		_	1	1	- 1	-			
	48 Seatbelts function and damage	I	I		-	I	I	I	1			
	49 Inspect chassis and body for corrosion - Complete Inspection Sheet		Attac	h copy of SI	neet to Job	Card at eve	ry service in	iterval				
BODY	50 Doors, bonnet, tailgate links, locks and door restraints to Check/Adjust/Clean/Lubricate	1	L	ı	L	- 1	L	- 1	L			
	51 Pollen filter*	I	R		R	I	R	I	R			
	52 Air conditioner drain pipe	I	I	I	I	l	I	I	!			
SAFETY	53 Check for open RECALLS or SERVICE CAMPAIGNS	Attach copy of IVH to Job Card at every service interval					$oxed{oxed}$					
TESTING	54 Road Test	I	I	_		1	I	1	- 1			

* v	vhere	fitted
-----	-------	--------

where grease nipples are fitted.

I was informed of the service cost & additional items that needs attention.

Attach one copy to Customer's Invoice

Customer Signature

Attach one copy to Job Card

Technician Signature

I hereby confirm that all items have been checked and and rectifed where required.

Updated.
Oct 2023

Document No.
CKD / ISUZU

2.5 Diesel

Corrosion Inspection Sheet TF Series (RT) Single Cab



PLEASE NOTE: Copy to be attached to Job Card

Job Card No.	. Date:		Model:	
Customer Name:	.Km.:		VIN :	
Service Consultant name:	Technician ı	name:		
Bodywork Inspection				
Vehicle OK Comments				
Yes No				
Vehicle Repaired				
Yes No				
		DE	ALER'S STAMP	
Accident / Bodywork damage			4.415	
repaired to factory standard			AND	
			SIGNATURE	
Yes No No	Ĺ			
MARK TEST DE	CIII TO LICI	ING RELEVANT	CVMDOL	
	_			
STONE THROW	O DEN	NT / BUMP	BODYWORK DAM	AGE
			_	
+ SCRATCH	••	NTWORK DAMAGE	SEAL UNDERBOD	PΥ
THE DIAGRAM IS	S REPRESENTA	ATIVE OF ALL MODEL S	SERIES	
	0			