

10,000 km or 12 Months Service Schedule TF Series (RT) - 2.5L(4JK1) & 3.0L(4JJ1) Diesel



PLEASE NOTE:

- 1. Refer to the Service Interval Guideline by Country for the correct Interval by kilometers or months, whichever occurs first.
- 2. This Service Schedule will have preference over the Owner's Manual and Warranty & Service Guide (Refer to updated date).
- 3. Refer to the Warranty and Service Guide for Severe Driving Conditions.
- 4. Consult the Owner/Customer prior to any additional work being carried out as an additional cost will be charged for items not covered under warranty.

| NOTE: APPLICABLE FOR 10,000 KM TO 100,000 KM OF |
|---|
| 12 MONTHS TO 120 MONTHS SERVICE INTERVALS |

| Service Advise Service Service Advise Service Advise Service Advise Service Service Advise S | Job Card No.: . | Date : | | | | | Model: | | | | | | | |
|--|-------------------|--|----------|--------------|--------------|-------------|--------------|---------------|-----|-----|-----|-----|----|----|
| Securic Part Part | Customer Nam | e: VIN : | | | | | KM Readi | ng: | | | | | | |
| SERVICE INTERVAL EVERY | Service Adviso | r : Authorisation No: | | | | | Technicia | n (Print) : . | | | | | | |
| ## Commonts, which ever occurs (ris) Morting 12 | | I = Inspection. After inspection clean and correct, or replace | as neces | sary - R = R | eplace - L = | Lubricate - | A = Adjust - | S = Service | • | | | | | |
| Commonths, whichever countries Months 12 24 36 48 60 72 84 96 60 108 109 1 | SERVICE INTER | VAL EVERY KMs (x 1000) | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | OK | |
| 1 Engine Oil and Filter R R R R R R R R R | (or months, which | ever occurs first) Months | 12 | 24 | 36 | 48 | 60 | 72 | 84 | 96 | 108 | 120 | OK | OK |
| Part Filter Fil | | Labour hrs. | 1,2 | 1,3 | 1,2 | 1,3 | 1,2 | 1,3 | 1,2 | 1,3 | 1,2 | 1,3 | | |
| Service Final Full Fuller (Note: only where fitted)-add 0.1 hours | | 1 Engine Oil and Filter | R | R | R | R | R | R | R | R | R | R | | |
| A Fleel sediment for presence of water | | 2 Fuel Filter | R | R | R | R | R | R | R | R | R | R | | |
| Final Fina | | 3 Pre-Fuel Filter* (Note: only where fitted)-add 0.1 hours | R | R | R | R | R | R | R | R | R | R | | |
| Engine 6 Air filter element (1 & R) and all air cleaner hose fittings (1) 1 R R | | 4 Fuel sedimentor for presence of water | ı | - 1 | - 1 | - 1 | - 1 | I | - 1 | - 1 | l l | I | | |
| Property Property | | • | ı | I | I | I | - 1 | - 1 | - 1 | I | - 1 | l l | | |
| 8 All engine drive belts for tension and damage and check pulley condition (replace if needed) | | i i | ı | R | ı | R | - 1 | R | I | R | I | R | | |
| 9 Run engine through operating range & check for excessive smoke | ENGINE | · · · · · · · · · · · · · · · · · · · | - | - | - | - | Α | - | - | - | - | Α | | |
| 10 Coolant system for leaks (press. test radiator & cap) & check coolant concentration (50% gly.) 1 | | | ı | I | ı | I | I | I | I | ı | I | I | | |
| 11 Coolant concentration (50 % glycol) - Add 0.3 hrs (Record coolant freezing point on the job card) 1 | | 0 0 1 0 0 | ! | I | I | I | - 1 | I | I | I | I | I | | |
| Radiator core (check for foreign objects) and fan operation | | , | ı | I | ı | I | - 1 | I | 1 | I | I | I | | |
| Service Figure | | (0, / (0, 1 / / | ı | I | ı | I | R | I | 1 | I | I | R | | |
| 14 All hoses & pipes in engine compartment for tightness or damage | | | ı | I | ı | I | I | I | I | ı | I | I | | |
| 15 Brake fluid level 1 | | | ı | I | ı | I | I | I | I | ı | I | I | | |
| SERVICE 17 Brake fluid level 1 1 1 1 1 1 1 1 1 | | 11 0 1 0 | ı | I | ı | I | I | I | I | ı | I | I | | |
| 17 Brake fluid - Add 0.3 hrs 18 Front disc brake pads & discs for wear (Record thickness size of pads & discs on the job card) 1 1 1 1 1 1 1 1 1 | | | ı | I | ı | I | I | I | I | ı | I | I | | |
| BRAKE 18 Front disc brake pads & discs for wear (Record thickness size of pads & discs on the job card) 1 | | | ı | I | ı | I | I | I | I | ı | I | I | | |
| 19 Rear brake linings & drums for wear (Record thickness size of shoes & drums on the job card) 18A | 0 | | ı | R | ı | R | I | R | I | R | I | R | | |
| 20 Brake pipes & hoses for leaks, loose connections or damage | BRAKE | , , , | ı | I | ı | I | I | I | ' | ı | I | I | | |
| 21 Clutch pedal function, travel and free play & fluid leaks | | | I&A | I&A | I&A | I&A | I&A | I&A | I&A | I&A | I&A | I&A | | |
| CLUTCH 22 Clutch fluid level | | 11 ' | ı | I | ı | I | I | I | I | ı | I | I | | |
| 23 Clutch fluid - Add 0.1 hrs 24 Manual transmission fluid-add 0.3 hrs for replacement R I I I I I I I I I | | | l | I | ı | I | ı | ı | ı | ı | l | I | | |
| TRANS. & TRANSFER CASE 24 Manual transmission fluid-add 0.3 hrs for replacement R I I I R I I I R I I | CLUTCH | | l | I | ı | I | ı | ı | ı | ı | l | ' | | |
| TRANSFER CASE 25 Automatic transmission fluid-add 0.3 hrs for replacement (4x4 only) R I I I I I I I I I | | | l | R | ı | R | ı | R | ı | R | l | R | | |
| CASE 26 Transfer case fluid-add 0.2 hrs for replacement (4x4 only) | | · | R | I | ı | I | R | ı | ı | ı | R | I | | |
| PROPSHAFT 27 Universal joints & sliding sleeve # 1 L | | ' | l | I | ı | I | ı | ı | ı | ı | l | R | | |
| PROPSHAFT 28 Prop shaft mounting and universal joints & sliding sleeve for looseness and excessive wear 1 | CASE | · | R | I | ı | I | R | ı | ı | ı | R | I | | |
| 28 Prop shaft mounting and universal joints & sliding sleeve for looseness and excessive wear | PROPSHAFT | | <u> </u> | L | | L | I | L | I | L | | L | | |
| FRONT/ REAR AXLE 30 Shift on the fly fluid* - add 0.1 hrs for replacement on 4x4 R I | | | ı | I | | I | ı | I | I | | I | I | | |
| REAR AXLE 31 Rear axle fluid (without limited slip) - add 0.3 hrs for replacement I | | · | | I | | I | I | I | I | | I | I | | |
| 32 Rear axle fluid (with limited slip) - add 0.1 hrs for replacement R I I R I I R I | | · | R | I | | I | I | I | I | | I | I | | |
| | REAR AXLE | 17 | ı | I | I | I | I | I | I | R | I | I | | |
| | | 17 | R | 1 | l | 1 | R | I | I | | R | l | | |

CONTINUED....



10,000 km or 12 Months Service Schedule TF Series (RT) - 2.5L(4JK1) & 3.0L(4JJ1) Diesel



PLEASE NOTE:

- 1. Refer to the Service Interval Guideline by Country for the correct Interval by kilometers or months, whichever occurs first.
- 2. This Service Schedule will have preference over the Owner's Manual and Warranty & Service Guide (Refer to updated date).
- 3. Refer to the Warranty and Service Guide for Severe Driving Conditions.
- 4. Consult the Owner/Customer prior to any additional work being carried out as an additional cost will be charged for items not covered under warranty.

NOTE: APPLICABLE FOR 10,000 KM TO 100,000 KM OR 12 MONTHS TO 120 MONTHS SERVICE INTERVALS

| SERVICE INTER | RVAL | EVERY KMs (x 1000) | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | ОК | NOT |
|---|-------|--|----|-----|------|---------------|---------------|----------------|----------------|-------|-----|-----|----|-----|
| (or months, which | hever | occurs first) Months | 12 | 24 | 36 | 48 | 60 | 72 | 84 | 96 | 108 | 120 | OK | OK |
| FRONT/ | 33 | Shift on the fly | | - 1 | I | ı | I | I | I | I | I | 1 | | 1 |
| REAR AXLE | 34 | All axle shafts and housing for distortion or damage | I | 1 | I | 1 | I | I | | I | I | 1 | | |
| KLAK AALL | 35 | Front drive axle CV joints, condition of rubber dust covers | | - 1 | I | ı | I | I | I | I | I | 1 | | |
| | 36 | Steering wheel play and function | | ! | 1 | 1 | 1 | I | | ı | I | ! | | |
| STEERING | 37 | Power steering fluid | | ! | 1 | R | 1 | I | | R | I | ! | | |
| STEERING | 38 | Steering rack and ball joint rubber boots | | ! | 1 | 1 | 1 | I | | ı | I | ! | | |
| | 39 | Wheel alignment inspection (to be offered to customer) | | • | Red | commended | every servic | e-cost for cus | stomer's acc | ount | • | • | | |
| PARKING | 40 | Parking brake function - lever travel & ratchet for damage | I | 1 | 1 | 1 | 1 | I | I | I | I | 1 | | |
| BRAKE | 41 | Parking brake cables for looseness or damage | I | 1 | ı | 1 | ı | I | | I | I | 1 | | |
| | 42 | Suspension front & rear - strut rubbers, bushes, tie-rod ends & link arms | | ! | 1 | 1 | 1 | I | | I | I | ! | | |
| CHASSIS & | 43 | Shock absorbers for leaks and looseness | | 1 | I | I | I | | | I | I | I | | |
| SUSPENSION | 44 | Fox Shock Absorbers- Remove, Service & Refit - Artic Models only - Add 2.0 hrs | - | - | - | - | - | - | S | - | - | - | | |
| OCCI ENGICIA | | Leaf/coil springs for damage | | I | - 1 | 1 | - 1 | I | I | I | I | I | | |
| | | Cab mountings for looseness and damage | | I | - 1 | 1 | - 1 | I | I | I | I | I | | |
| | | Tyre Pressure - Check and correct (incl. spare wheel) | | I | - 1 | 1 | - 1 | I | I | I | I | I | | |
| | | Inspect tyres & rims for damage (incl. spare wheel) | | I | - 1 | 1 | - 1 | I | I | I | I | I | | |
| WHEELS | 49 | Wheel bearing (front & rear) - Inspect for bearing play | | I | - 1 | 1 | - 1 | I | I | I | I | I | | |
| *************************************** | | Rotate tyres & torque wheel nuts as per specification-Refer Bulletin GEN-2015-09 | T | T | T | T | T | Т | T | T | T | T | | |
| | | Front wheel bearing grease and oil seal - Add 1.1 hrs for replacement (4x2) | I | 1 | - 1 | - 1 | R | I | I | - 1 | I | R | | |
| | | Front wheel and needle bearing grease and oil seal - Add 2.8 hrs for replacement (4x4) | I | 1 | I | 1 | R | I | I | I | I | R | | |
| | 53 | Vehicle systems - Check all ECUs for DTCs & reset service interval* | I | 1 | - 1 | Ţ | - 1 | I | | I | I | I | | |
| | | Extract DRM data & generate VDAS REPORT*- Refer Bulletin 2304261630TRA0 – SB2309 | | | | Attach repor | rt to Job Car | d at every se | rvice interval | | | | | ı |
| ELECTRICAL | 55 | Starter and alternator function / output | | I | - 1 | 1 | - 1 | I | I | I | I | I | | ı |
| EQUIPMENT | 56 | Battery electrolyte level and specific gravity* | ļ | - 1 | - 1 | - 1 | - 1 | I | ļ | I | I | ļ | | 1 |
| EQUII IIIEITI | 57 | Check operation of all lights, hooter, instruments, a/c, radio, wiper blades & washers | I | I | 1 | 1 | 1 | I | | I | I | 1 | | |
| | 58 | Remote key battery* | | R | 1 | R | 1 | R | | R | I | R | | |
| | 59 | Airbag system and Airbag warning light, visual inspection | | ! | 1 | 1 | 1 | I | | ı | I | ! | | 1 |
| | 60 | Seatbelts function and damage | | 1 | I | I | I | | | I | I | I | | |
| | 61 | Inspect chassis and body for corrosion - Complete Inspection Sheet | | | Atta | ach copy of S | Sheet to Job | Card at every | service inte | erval | | | | |
| BODY | _ | Doors, bonnet, tailgate links, locks and door restraints to Check/Adjust/Clean/Lubricate | I | L | - 1 | L | - 1 | L | - 1 | L | I | L | | |
| | _ | Pollen filter* | ı | R | 1 | R | 1 | R | I | R | I | R | | |
| | | Air conditioner drain pipe for drainage | ı | 1 | 1 | - 1 | 1 | 1 | I | I | I | 1 | | |
| SAFETY | _ | Check for open RECALLS or SERVICE CAMPAIGNS | | | At | tach copy of | IVH to Job C | ard at every | service inter | val | | | | |
| TESTING | 66 | Road Test | I | I | - 1 | 1 | - 1 | I | I | I | I | 1 | | 1 |

* where fitted

where grease nipples are fitted.

Customer Signature Date Technician Signature

I hereby confirm that all items have been checked and and rectifed where required.

Updated. Oct 2023 Document No. CKD / ISUZU

2.5 / 3.0 Diesel

Attach one copy to Customer's Invoice

I was informed of the service cost & additional items that needs attention.

Attach one copy to Job Card



10,000 km or 12 Months Service Schedule TF Series (RT) - 2.5L(4JK1) & 3.0L(4JJ1) Diesel



PLEASE NOTE:

- 1. Refer to the Service Interval Guideline by Country for the correct Interval by kilometers or months, whichever occurs first.
- 2. This Service Schedule will have preference over the Owner's Manual and Warranty & Service Guide (Refer to updated date).
- 3. Refer to the Warranty and Service Guide for Severe Driving Conditions.
- 4. Consult the Owner/Customer prior to any additional work being carried out as an additional cost will be charged for items not covered under warranty.

| NOTE: APPLICABLE FOR 110,000 KM TO 180,000 KM OF |
|--|
| 132 MONTHS TO 216 MONTHS SERVICE INTERVALS |

| Job Card No.: | Date : | Model : |
|-------------------|-------------------|----------------------|
| Customer Name: | VIN : | KM Reading: |
| Service Advisor : | Authorisation No: | Technician (Print) : |

I = Inspection, After inspection clean and correct, or replace as necessary - R = Replace - L = Lubricate - A = Adjust - S = Service

| RVAL EVERY | KMs (x 1000) | 110 | 120 | 130 | 140 | 150 | 160 | 170 | 180 | OK | NOT |
|--|---|---|--|--|--------------|-------------------|--------|---------------------------|--------------|--|--|
| chever occurs first) | Months | 132 | 144 | 156 | 168 | 180 | 192 | 204 | 216 | TOK | OK |
| | Labour hrs. | 1,2 | 1,3 | 1,2 | 1,3 | 1,2 | 1,3 | 1,2 | 1,3 | | |
| 1 Engine Oil and Filter | | R | R | R | R | R | R | R | R | | |
| 2 Fuel Filter | | R | R | R | R | R | R | R | R | | |
| 3 Pre-Fuel Filter* (Note: only where fitted)-add 0.1 hours | | R | R | R | R | R | R | R | R | | |
| 4 Fuel sedimentor for presence of water | | I | I | I | I | I | ı | ı | ı | | |
| 5 Fuel leakage at tank, cap and pipes | | I | 1 | I | I | I | ı | ı | - | | |
| 6 Air filter element (I & R) and all air cleaner hose fitments for tightness (I) | | I | R | I | R | I | R | ı | R | | |
| 7 Valve Clearances - add 1.5 for adjustment | | - | - | - | - | Α | - | - | - | | |
| 8 All engine drive belts for tension and damage and check pulley condition (replace if needed) | | I | I | I | 1 | I | I | I | ı | | |
| 9 Run engine through operating range & check for excessive smoke | | I | I | I | I | I | ı | ı | ı | | |
| 10 Coolant concentration (50 % glycol) - Add 0.3 hrs (Record coolant freezing point on the job card) | | I | I | I | I | I | ı | ı | ı | | |
| 11 Coolant concentration (50 % glycol) - Add 0.3 hrs | | I | I | I | I | R | ı | ı | ı | | |
| 12 Radiator core (check for foreign objects) and fan operation | | ı | ! | ı | 1 | ı | ı | ı | ı | | |
| 13 Exhaust system for leaks and mountings for tightness or damage | | ı | ! | ı | 1 | ı | ı | ı | ı | | |
| 14 All hoses & pipes in engine compartment for tightness or damage | | I | I | ı | 1 | I | ı | ı | I | | |
| 15 Brake pedal function, travel and free play | | ı | ! | ı | 1 | ı | ı | ı | ı | | |
| 16 Brake fluid level | | ı | ! | ı | 1 | ı | ı | ı | ı | | |
| 17 Brake fluid - Add 0.3 hrs | | ı | R | ı | R | ı | R | ı | R | | |
| 18 Front disc brake pads & discs for wear (Record thickness size of pads & discs on the job card) | | I | I | I | I | I | ı | ı | ı | | |
| 19 Rear brake linings & drums for wear (Record thickness size of shoes & drums on the job card) | | I&A | I&A | I&A | I&A | I&A | I&A | I&A | I&A | | |
| 20 Brake pipes & hoses for leaks, loose connections or damage | | I | I | I | I | I | ı | ı | ı | | |
| 21 Clutch pedal function, travel and free play & fluid leaks | | I | I | I | I | I | ı | ı | ı | | |
| 22 Clutch fluid level | | I | I | I | I | I | ı | ı | ı | | |
| 23 Clutch fluid - Add 0.1 hrs | | I | R | I | R | I | R | ı | R | | |
| 24 Manual transmission fluid-add 0.3 hrs for replacement | | I | I | R | I | I | ı | R | ı | | |
| 25 Automatic transmission fluid-add 0.3 hrs for replacement | | I | I | ı | 1 | I | I | ı | I | | |
| 26 Transfer case fluid-add 0.2 hrs for replacement for 4x4 | | I | I | R | I | I | ı | R | ı | | |
| 27 Universal joints & sliding sleeve # | | I | L | I | L | I | L | I | L | | |
| 28 Prop shaft mounting and universal joints & sliding sleeve for looseness and excessive wear | | I | I | I | I | I | ı | ı | I | | |
| 29 Front axle fluid *- add 0.1 hrs for replacement on 4x4 | | I | I | I | I | R | ı | ı | ı | | |
| 30 Shift on the fly fluid* - add 0.1 hrs for replacement on 4x4 | | I | I | I | I | R | ı | ı | ı | | |
| 31 Rear axle fluid (without limited slip) - add 0.3 hrs for replacement | | I | I | I | I | R | ı | ı | ı | | |
| 32 Rear axle fluid (with limited slip) - add 0.1 hrs for replacement | | | | R | - | | | D | | 1 | 1 |
| cho | 1 Engine Oil and Filter 2 Fuel Filter 3 Pre-Fuel Filter* (Note: only where fitted)-add 0.1 hours 4 Fuel sedimentor for presence of water 5 Fuel leakage at tank, cap and pipes 6 Air filter element (I & R) and all air cleaner hose fitments for tightness (I) 7 Valve Clearances - add 1.5 for adjustment 8 All engine drive belts for tension and damage and check pulley condition (replace if needed) 9 Run engine through operating range & check for excessive smoke 10 Coolant concentration (50 % glycol) - Add 0.3 hrs (Record coolant freezing point on the job card) 11 Coolant concentration (50 % glycol) - Add 0.3 hrs 12 Radiator core (check for foreign objects) and fan operation 13 Exhaust system for leaks and mountings for tightness or damage 14 All hoses & pipes in engine compartment for tightness or damage 15 Brake pedal function, ravel and free play 16 Brake fluid level 17 Brake fluid - Add 0.3 hrs 18 Front disc brake pads & discs for wear (Record thickness size of pads & discs on the job card) 19 Rear brake linings & drums for wear (Record thickness size of shoes & drums on the job card) 20 Brake pedal function, travel and free play & fluid leaks 21 Clutch pedal function, travel and free play & fluid leaks 22 Clutch fluid - Add 0.1 hrs 24 Manual transmission fluid-add 0.3 hrs for replacement 25 Automatic transmission fluid-add 0.3 hrs for replacement 26 Transfer case fluid-add 0.2 hrs for replacement 27 Automatic transmission fluid-add 0.3 hrs for replacement 28 Prop shaft mounting and universal joints & sliding sleeve for looseness and excessive wear 29 Front axle fluid *- add 0.1 hrs for replacement on 4x4 30 Shift on the fly fluid* - add 0.1 hrs for replacement on 4x4 31 Rear axle fluid (without limited slip) - add 0.3 hrs for replacement | were occurs first) Months Labour hrs. I Engine Oil and Filter Fuel Filter Pre-Fuel Filter (Note: only where fitted)-add 0.1 hours Fuel sedimentor for presence of water All engine drive belts for tension and pipes All engine drive belts for tension and damage and check pulley condition (replace if needed) Run engine through operating range & check for excessive smoke Coolant concentration (50 % glycol) - Add 0.3 hrs (Record coolant freezing point on the job card) Coolant concentration (50 % glycol) - Add 0.3 hrs (Record coolant freezing point on the job card) Exhaust system for leaks and mountings for tightness or damage All hoses & pipes in engine compartment for tightness or damage Brake pidel function, travel and free play Brake fluid level Brake fluid level Clutch fluid - Add 0.3 hrs Front disc brake pads & discs for wear (Record thickness size of pads & discs on the job card) Brake pipes & hoses for leaks, loose connections or damage Clutch fluid - Add 0.3 hrs Clutch fluid - Add 0.1 hrs Manual transmission fluid-add 0.3 hrs for replacement Automatic transmission fluid-add 0.3 hrs for replacement Automatic transmission fluid-add 0.3 hrs for replacement Transfer case fluid-add 0.3 hrs for replacement for 4x4 Universal joints & silding sleeve * Prop shaft mounting and universal joints & silding sleeve for looseness and excessive wear Front disc full dividut uniform, travel and 0.3 hrs for replacement on 4x4 Rear avale fluid (without limited slip) - add 0.3 hrs for replacement Ton the fift fluid - add 0.1 hrs for replacement on 4x4 Rear avale fluid (without limited slip) - add 0.3 hrs for replacement | ever occurs first) Months Labour hrs. R Fuel Filter R R Fuel Filter R R Fuel Filter R R Fuel sedimentor for presence of water I Fuel seadimentor for presence of water I Valve Clearances - add 1.5 for adjustment I Valve Clearances - a | ever occurs first) Months Labour hrs. 132 144 | Months 132 | Labour hrs. 132 | Months | North Labour hrs. 132 | Months 132 | Months 132 144 156 168 180 192 204 216 | Mortest Labour Ins. 1.2 1.44 156 168 180 192 2.04 2.16 |

CONTINUED....



10,000 km or 12 Months Service Schedule TF Series (RT) - 2.5L(4JK1) & 3.0L(4JJ1) Diesel



PLEASE NOTE:

- 1. Refer to the Service Interval Guideline by Country for the correct Interval by kilometers or months, whichever occurs first.
- 2. This Service Schedule will have preference over the Owner's Manual and Warranty & Service Guide (Refer to updated date).
- 3. Refer to the Warranty and Service Guide for Severe Driving Conditions.
- 4. Consult the Owner/Customer prior to any additional work being carried out as an additional cost will be charged for items not covered under warranty.

NOTE: APPLICABLE FOR 110,000 KM TO 180,000 KM OR 132 MONTHS TO 216 MONTHS SERVICE INTERVALS

| | I = Inspection. After inspection clean and correct, or replace as necessary - R = R | eplace - L = | Lubricate - / | A = Adjust - | S = Service |) | | | | | |
|---|---|--------------|---------------|--------------|----------------|---------------|----------------|-------|-----|------|-----|
| SERVICE INTER | VAL EVERY KMs (x 1000) | 110 | 120 | 130 | 140 | 150 | 160 | 170 | 180 | ок | NOT |
| (or months, whichever occurs first) Months | | 132 | 144 | 156 | 168 | 180 | 192 | 204 | 216 | - OK | OK |
| EDONT/ | 33 Shift on the fly | ı | I | | I | I | I | I | I | | |
| FRONT/ REAR AXLE | 34 All axle shafts and housing for distortion or damage | ı | I | | I | I | I | I | I | | |
| REAR AALE | 35 Front drive axle CV joints, condition of rubber dust covers | ı | I | | I | I | I | I | I | | |
| | 36 Steering wheel play and function | I | I | | I | I | ı | I | I | | |
| STEERING | 37 Power steering fluid | I | R | | I | I | R | I | I | | |
| STEERING | 38 Steering rack and ball joint rubber boots | I | I | | I | I | ı | ı | I | | |
| | 39 Wheel alignment inspection (to be offered to customer) | | Rec | ommended | every service | e-cost for cu | stomer's acc | ount | | | |
| PARKING | 40 Parking brake function - lever travel & ratchet for damage | I | I | I | 1 | I | ı | I | I | | |
| BRAKE | 41 Parking brake | I | I | | I | I | ı | ı | I | | |
| | 42 Suspension front & rear - strut rubbers,bushes,tie-rod ends & link arms | I | I | | I | I | ı | ı | I | | |
| CHASSIS & | 43 Shock absorbers for leaks and looseness | I | I | | I | I | ı | ı | I | | |
| SUSPENSION | 44 Fox Shock Absorbers- Remove, Service & Refit - Artic Models only - Add 2.0 hrs | - | - | - | S | - | - | - | - | | |
| SUSFENSION | 45 Leaf/coil springs for damage | I | I | | I | I | ı | ı | I | | |
| | 46 Cab mountings for looseness and damage | I | I | | I | I | ı | ı | I | | |
| | 47 Tyre Pressure - Check and correct (incl. spare wheel) | I | I | I | 1 | I | ı | I | I | | |
| | 48 Inspect tyres & rims for damage (incl. spare wheel) | I | I | I | 1 | I | ı | I | I | | |
| WHEELS | 49 Wheel bearing (front & rear) - Inspect for bearing play | I | I | I | 1 | I | ı | I | I | | |
| WHEELS | 50 Rotate tyres & torque wheel nuts as per specification-Refer Bulletin GEN-2015-09 | Т | Т | T | Т | Т | Т | Т | Т | | |
| | 51 Front wheel bearing grease and oil seal - Add 1.1 hrs for replacement (4x2) | I | I | I | 1 | R | ı | I | I | | |
| | 52 Front wheel and needle bearing grease and oil seal - Add 2.8 hrs for replacement (4x4) | 1 | I | ı | 1 | R | ı | 1 | I | | |
| | 53 Vehicle systems - Check all ECUs for DTCs & reset service interval* | I | I | I | 1 | 1 | I | I | - 1 | | |
| | 54 Extract DRM data & generate VDAS REPORT*- Refer Bulletin 2304261630TRA0 – SB2309 | | | Attach repo | rt to Job Card | d at every se | rvice interva | | | | |
| EL ECTRICAL | 55 Starter and alternator function / output | ! | I | ı | 1 | ! | I | 1 | ı | | |
| ELECTRICAL EQUIPMENT | 56 Battery electrolyte level and specific gravity* | I | I | ı | I | I | ı | I | I | | |
| EQUIPMENT | 57 Check operation of all lights, hooter, instruments, a/c, radio, wiper blades & washers | I | I | I | 1 | I | ı | - 1 | I | | |
| | 58 Remote key battery* | I | R | | R | I | R | ı | R | | |
| | 59 Airbag system and Airbag warning light, visual inspection | ı | I | ı | ı | ı | ı | ı | ı | 1 | |
| | 60 Seatbelts function and damage | ı | I | ı | ı | ı | ı | ı | ı | 1 | |
| | 61 Inspect chassis and body for corrosion - Complete Inspection Sheet | | Atta | ch copy of S | heet to Job | Card at ever | y service inte | erval | | | |
| BODY | 62 Doors, bonnet, tailgate links, locks and door restraints to Check/Adjust/Clean/Lubricate | ı | L | | L | 1 | L | ı | L | | |
| | 63 Pollen filter* | I | R | | R | I | R | ı | R | 1 | |
| | 64 Air conditioner drain pipe | I | ı | I | I | I | ı | I | I | | |
| SAFETY | 65 Check for open RECALLS or SERVICE CAMPAIGNS | | Att | ach copy of | IVH to Job C | ard at every | service inter | rval | • | 1 | |
| TESTING | 66 Road Test | I | I | I | 1 | 1 | I | - 1 | I | 1 | |

| * where | fitted |
|---------|--------|
|---------|--------|

where grease nipples are fitted.

Customer Signature Date

Technician Signature

I hereby confirm that all items have been checked and and rectifed where required.

Updated.
Oct 2023

Document No.
CKD / ISUZU
2.5 / 3.0 Diesel

Corrosion Inspection Sheet TF Series (RT) Single Cab



PLEASE NOTE: Copy to be attached to Job Card

| Job Card No. | . Date: | | Model: | |
|------------------------------|-----------|---|-----------------|--|
| Customer Name: | .Km.: | | VIN : | |
| Service Consultant name: | Technicia | ın name: | | |
| Bodywork Inspection | | | | |
| Vehicle OK Comments | | | | |
| Yes No | | | | |
| Vehicle Repaired | | | | |
| Yes No | | DEALE | R'S STAMP | |
| Accident / Bodywork damage | | | AND | |
| repaired to factory standard | | | | |
| Yes No No | | SIG | NATURE | |
| MARK TEST RE | SULTS U | SING RELEVANT SY | MBOL | |
| STONE THROW | <u> </u> | DENT / BUMP | BODYWORK DAMAGE | |
| + SCRATCH | •• | PAINTWORK DAMAGE ITATIVE OF ALL MODEL SERIE | SEAL UNDERBODY | |
| THE DIAGRAIN IS | REPRESEN | TIATIVE OF ALL MODEL SERIE | | |
| | | | | |
| | 0.5 | | | |
| | | | | |

<u>Corrosion Inspection Sheet</u> <u>TF Series (RT) Extended Cab</u>



PLEASE NOTE: Copy to be attached to Job Card

| | | | |
|------------------------------|----------------------|-----------------|--|
| Job Card No | Date: | Model: | |
| Customer Name: | Km.: | VIN: | |
| Service Consultant name: | Technician name: | | |
| Bodywork Inspection | | | |
| Vehicle OK Comments | | | |
| Yes No | | | |
| Vehicle Repaired | | | |
| Yes No | | DEALER'S STAMP | |
| Accident / Bodywork damage | | AND | |
| repaired to factory standard | | AND | |
| Yes No | | SIGNATURE | |
| | | | |
| MARK TEST RE | SULTS USING REL | EVANT SYMBOL | |
| STONE THROW | O DENT / BUMP | BODYWORK DAMAGE | |
| | | | |
| + SCRATCH | # PAINTWORK DA | · | |
| THE DIAGRAM IS | REPRESENTATIVE OF AL | L MODEL SERIES | |
| | | | |
| | | | |
| | | | |

Corrosion Inspection Sheet TF Series (RT) Double Cab



PLEASE NOTE: Copy to be attached to Job Card

| Job Card No. | Date: | | Model: | |
|------------------------------|---------------|---------------------------------------|------------------|-------|
| Customer Name: | Km.: | | VIN : | |
| Service Consultant name: | Technician na | ame: | ···· <u>····</u> | |
| Bodywork Inspection | | | | |
| Vehicle OK Commo | ents | | | |
| Yes No | | | | |
| Vehicle Repaired | | | | |
| Yes No | | DEALER' | S STAMP |] |
| Accident / Bodywork damage | | 1A | | |
| repaired to factory standard | | A | | |
| Yes No No | | SIGNA | ATURE | |
| MARK TEST | RESULTS USIN | IG RELEVANT SYMI | BOL | |
| ● STONE THROW | O DENT | T/BUMP | BODYWORK DAMAGE | |
| + SCRATCH THE DIAGR | | TWORK DAMAGE IVE OF ALL MODEL SERIES | SEAL UNDERBODY | |
| | | | | |
| | | | | |
| | | | | |