SPEC SHEET
SUMMARY



THE NEW
N-SERIES

www.isuzu.co.za

ISUZU TRUCKS

ISUZU
With you, for the long run

Model		NLR 150	NMR 250	NMR 250 SWB	NMR 250 AMT	NMR 250 AMT SWB	NMR 250 AMT E5	NMR 250 AMT E5 SWB	NMR 250 CREWCAB AMT	NMR 250 CREWCAB AMT E5	NPR 275
SMOD		M260NH5	M260NH6	M260NH7	M260NH8	M260NH9	M260NI0	M260NI1	M260NI2	M260NI3	M260NI4
Axle layout		4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2
Control		Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward
MASS											
Permissible body + payload	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - total (T)	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - front	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - rear	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
GVM	kg	4200	5700	5700	5700	5700	5700	5700	5700	5700	6000
V	kg	4200	5700	5700	5700	5700	5700	5700	5700	5700	6000
GCM	kg	7050	8700	8700	8700	8700	8700	8700	8700	8700	9700
D/T	kg	7050	8700	8700	8700	8700	8700	8700	8700	8700	9700
Axle - front GA/GAU	kg	2900	2900	2900	2900	2900	2900	2900	2900	2900	3100
Axle - front A/AU	kg	1950	2300	2300	2300	2300	2300	2300	2300	2300	2900
Axle - rear GA/GAU	kg	5000	5000	5000	5000	5000	5000	5000	5000	5000	6600
Axle - rear A/AU	kg	3700	4360	4360	4360	4360	4360	4360	4360	4360	5600
Litres of fuel tank 1 included in tare	ltrs	15	15	15	15	15	15	15	15	15	15
Tools included in tare		Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit
Spare wheel included in tare		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
PERFORMANCE											
Gradeability at V	%	44.01	41.76	41.76	46.98	46.98	46.98	46.98	46.98	50.4	38.71
Gradeability at D/T	%	26.40	26.40	26.40	29.70	29.70	29.70	29.70	29.70	31.86	23.94
Max. geared road speed (Without SLD)	km/h	133	122	122	122	122	122	122	118 (113)	118 (113)	103
Max allowable speed (SLD for SA)	km/h	100	100	100	100	100	100	100	100	100	100
MAJOR DIMENSIONS											
OL - Overall length	mm	4730	6022	4906	6022	4906	6022	4906	6022	6022	5985
OW - Overall width	mm	1850	1855	1855	1855	1855	1855	1855	1855	1855	2120
WB – Wheelbase	mm	2480	3350	2475	3350	2475	3350	2475	3350	3350	3365
CA - Cab to bogie/rear axle	mm	2021	2894	2022	2894	2022	2894	2022	2894	2894	2965
CE - Cab to end of chassis	mm	3166	4462	3348	4462	3348	4462	3348	4462	4462	4442
OH - Overall height	mm	2170	2175	2175	2175	2175	2175	2175	2175	2175	2280
FOH - Front overhang	mm	1105	1105	1105	1105	1105	1105	1105	1105	1105	1110
ROH - Rear overhang	mm	1145	1565	1326	1565	1326	1565	1326	1565	1565	1510
EH - chassis height rear	mm	760	810	810	810	810	810	810	810	810	832
HH - ground clearance	mm	200	210	210	210	210	210	210	210	210	200
Chassis width rear	mm	700	700	700	700	700	700	700	700	700	850
Turning radius (curb to curb)	mm	5150	6740	5450	6740	5450	6740	5450	6740	6740	5860
Turning radius (wall to wall)	mm	5670	7430	6120	7430	6120	7430	7430	7430	7430	6540
ENGINE											
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model		4JJ1-TCC	4JJ1-TCC	4JJ1-TCC	4JJ1-TCC	4JJ1-TCC	4JJ1-TCC	4JJ1-TCC	4JJ1-TCC	4JJ1-TCC	4JJ1-TCC
Capacity	cm3	2,999	2,999	2,999	2,999	2,999	2,999	2,999	2,999	2,999	2,999
Layout		Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail	Diesel inline 4 Turbocharged Intercooled Common Rail
Type											
Power at r/min	kW	96 @ 2800	96 @ 2800	96 @ 2800	96 @ 2800	96 @ 2800	91 @ 2,800	91 @ 2,800	96 @ 2800	91 @ 2,800	96 @ 2800
Torque at r/min	Nm	330 @ 1600 - 2600	330 @ 1600 - 2600	330 @ 1600 - 2600	330 @ 1600 - 2600	330 @ 1600 - 2600	354 @ 1,600-2,600	354 @ 1,600-2,600	330 @ 1600 - 2600	354 @ 1,600-2,600	330 @ 1600 - 2600
Emissions standard		Euro 2	Euro 2	Euro 2	Euro 3	Euro 3	Euro 5	Euro 5	Euro 3	Euro 5	Euro 2
CLUTCH											
Make		Exedy	Exedy	Exedy	N/A	N/A	N/A	N/A	N/A	N/A	Exedy
Model		300	300	300	N/A	N/A	N/A	N/A	N/A	N/A	300
Type		Single	Single	Single	N/A	N/A	N/A	N/A	N/A	N/A	Single
Diameter	mm	300	300	300	N/A	N/A	N/A	N/A	N/A	N/A	300
Auto slack adjuster		Standard	Standard	Standard	-	-	-	-	-	-	Standard
TRANSMISSION											
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model		MYY5T	MYY5T	MYY5T	MYY6S (AMT)	MYY6S (AMT)	MYY6-E (AMT)	MYY6-E (AMT)	MYY6S (AMT)	MYY6-E (AMT)	MYY5T
Type		5 Speed synchromesh	5 Speed synchromesh	5 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	5 Speed synchromesh
Shift		Manual Gearshift	Manual Gearshift	Manual Gearshift	Automated Manual	Automated Manual	Automated Manual	Automated Manual	Automated Manual	Automated Manual	Manual Gearshift
No. of gears forward		5	5	5	6	6	6	6	6	6	5
1st gear ratio		5.315	5.315	5.315	5.979	5.979	5.979	5.979	5.979	5.979	5.315
2nd gear ratio		3.053	3.053	3.053	3.434	3.434	3.434	3.434	3.434	3.434	3.053
3rd gear ratio		1.655	1.655	1.655	1.862	1.862	2.040	2.040	1.862	2.040	1.655
4th gear ratio		1	1	1	1.297	1.297	1.397	1.397	1.297	1.397	1
5th gear ratio		0.721	0.721	0.721	1.000	1.000	1.000	1.000	1.000	1.000	0.721
6th gear ratio		-	-	-	0.759	0.759	0.769	0.769	0.759	0.769	-
REV		5.068	5.068	5.068	5.701	5.701	5.071	5.071	5.701	5.071	5.068
Transfer case		No	No	No	No	No	No	No	No	No	No
Manual locking hubs (4X4)		No	No	No	No	No	No	No	No	No	No
Limited slip differential		No	No	No	No	No	No	No	No	No	No
PTO		PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready
DRIVE AXLE											
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model axle front		F029	F029	F029	F029	F029	F029	F029	F029	F029	F031
Model drive axle rear		R050	R050	R050	R050	R050	R050	R050	R050	R050	R066
Hypoid		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Final ratio	: 1	4.100	5.125	5.125	5.125	5.125	5.125	5.125	5.125	5.125	5.571
SUSPENSION											
Front		Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs
Rear		Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs
Shock absorbers		Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear
Stabilisers		Front	Front	Front	Front	Front	Front	Front	Front	Front	Front
BRAKES											
System type		Vacuum Hydraulic	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit
Front		Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums
Rear		Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums
Anti-lock braking system (ABS) with EBD		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Park/emergency system		Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft
Exhaust brake		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
ELECTRICAL & FUEL											
Voltage	v	24	24	24	24	24	24	24	24	24	24
Alternator	A	90	90	90	90	90	90	90	90	90	90
Fuel tank 1 capacity	ltrs	75	100	100	100	100	100	100	100	100	100
Fuel tank 2 capacity	ltrs	0	0	0	0	0	0	0	0	0	0
TYRES											
Size and ply rating - front & Rear (Tubeless)		195/75 R16C	205/75R16C	205/75R16C	205/75R16C	205/75R16C	205/75R16C	205/75R16C	205/75R16C	205/75R16C	215/75R17.5
CAB & EXTRAS											
Type		Day	Day	Day	Day	Day	Day	Day	Crew	Crew	Day
Roof		Low	Low	Low	Low	Low	Low	Low	Low	Low	Low
No. of seats (lap rear & centre)		3	3	3	3	3	3	3	6	6	3
Airconditioning		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Radio / USB		Optional	Optional	Optional	Standard	Standard	Standard	Standard	Standard	Standard	Optional
Speakers		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
USB charger		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Daytime running lights (DRL)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Fog lamps (LED)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Headlamps (LED)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Telematics		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Multi information display		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Driver & far passenger airbags		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Central locking		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Electric windows		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Suspension seat (driver)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	No	No	Standard
Tilt cab		Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No	Yes
Wet wiper system		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Seat belt		Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter
Reverse alarm		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Front bumper		3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin
Emissions Control		-	-	-	-	-	DOC	DOC	-	DOC	-
ECE R29 CAB		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

Model		NPR 400	NPR 400 SWB	NPR 400 AMT	NPR 400 AMT E5	NPR 400 CREW AMT	NPR 400 CREW AMT E5	NPR 400 CNG	NPR 400 CNG AMT	NQR 500	NQR 500 SWB	NQR 500 AMT	NQR 550
SMOD		M260NI8	M260NI9	M260NJ0	M260NJ1	M260NJ2	M260NJ3	M260NN4	M260NN3	M260NJ4	M260NJ5	M260NJ7	M260NJ9
Axle layout		4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2
Control		Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward
MASS													
Permissible body + payload	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - total (T)	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - front	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - rear	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
GVM	kg	7700	7700	7700	7700	7700	7700	7500	7500	8500	8500	8500	8999
V	kg	7700	7700	7700	7500	7700	7500	7500	7500	8500	8500	8500	8999
GCM	kg	11000	11000	11000	11000	11000	11000	11000	11000	12000	12000	12000	12000
D/T	kg	11000	11000	11000	11000	11000	11000	11000	11000	12000	12000	12000	12000
Axle - front GA/GAU	kg	3100	3100	3100	3100	3100	3100	3100	3100	3300	3300	3300	3300
Axle - front A/AU	kg	3100	3100	3100	3100	3100	3100	2900	2900	3300	3300	3300	3300
Axle - rear GA/GAU	kg	6600	6600	6600	6600	6600	6600	6600	6600	6600	6600	6600	6600
Axle - rear A/AU	kg	5600	5600	5600	5600	5600	5600	5600	5600	6600	6600	6600	6600
Litres of fuel tank 1 included in tare	ltrs	15	15	15	15	15	15	30	30	15	15	15	15
Tools included in tare		Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit
Spare wheel included in tare		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
PERFORMANCE													
Gradeability at V	%	32.06	32.06	32.06	34.38	34.38	34.38	34.27	34.27	34.61	34.61	34.61	32.69
Gradeability at D/T	%	22.04	22.04	22.04	23.44	23.44	23.44	23.37	23.37	24.52	24.52	24.52	24.52
Max. geared road speed (without SLD)	km/h	116	116	116	116	116	116	118	118	107	107	107	107
Max allowable speed (SLD for SA)	km/h	100	100	100	100	100	100	100	100	100	100	100	100
MAJOR DIMENSIONS													
OL - Overall length	mm	7355	5985	7355	7355	7355	7355	TBA	TBA	7355	5985	7355	7355
OW - Overall width	mm	2120	2120	2120	2120	2120	2120	TBA	TBA	2120	2120	2120	2120
WB - Wheelbase	mm	4175	3365	4175	4175	4175	4175	TBA	TBA	4175	3365	4175	4175
CA - Cab to bogie/rear axle	mm	3607	2794	3607	3607	2616	2616	TBA	TBA	3607	2794	3607	3607
CE - Cab to end of chassis	mm	5672	4304	5672	5672	4727	4727	TBA	TBA	5672	4304	5672	5672
OH - Overall height	mm	2285	2285	2285	2285	2295	2295	TBA	TBA	2285	2285	2285	2285
FOH - Front overhang	mm	1110	1110	1110	1110	1110	1110	TBA	TBA	1110	1110	1110	1110
ROH - Rear overhang	mm	2070	1510	2070	2070	2070	2070	TBA	TBA	2070	1510	2070	2070
EH - Chassis height rear	mm	840	838	840	840	828	828	TBA	TBA	840	822	840	840
HH - Ground clearance	mm	206	200	206	206	185	185	TBA	TBA	206	195	206	206
Chassis width rear	mm	850	850	850	850	850	850	TBA	TBA	850	850	850	850
Turning radius (curb to curb)	mm	7100	5860	7100	7100	7100	7100	TBA	TBA	7100	5860	7100	7100
Turning radius (wall to wall)	mm	7940	6540	7940	7940	7940	7940	TBA	TBA	7940	6540	7940	7940
ENGINE													
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model		4HK1-TCN	4HK1-TCN	4HK1-TCN	4JJ1-TCC	4HK1-TCN	4JJ1-TCC	4HV1(CNG)	4HV1(CNG)	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN
Capacity	cm3	5,193	5,193	5,193	2,999	5,193	2,999	4,570	4,570	5,193	5,193	5,193	5,193
Layout		Diesel inline 4	Diesel inline 4	Diesel inline 4	Diesel inline 4	Diesel inline 4	Diesel inline 4	CNG	CNG	Diesel inline 4	Diesel inline 4	Diesel inline 4	Diesel inline 4
Type		Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Naturally Aspirated	Naturally Aspirated	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail
Power at r/min	kW	110 @ 2600	110 @ 2600	110 @ 2600	91 @ 2800	110 @ 2600	91 @ 2800	96 @ 3200	96 @ 3200	110 @ 2600	110 @ 2600	110 @ 2600	110 @ 2600
Torque at r/min	Nm	404 @ 1600	404 @ 1600	404 @ 1600	354 @ 1600-2600	404 @ 1600	354 @ 1600-2600	353 @ 1400	353 @ 1400	404 @ 1600	404 @ 1600	404 @ 1600	404 @ 1600
Emissions standard		Euro 2	Euro 2	Euro 3	Euro 5	Euro 3	Euro 5	Euro 5	Euro 5	Euro 2	Euro 2	Euro 3	Euro 2
CLUTCH													
Make		Exedy	Exedy	N/A	N/A	N/A	N/A	Exedy	N/A	Exedy	Exedy	N/A	Exedy
Model		325	325	N/A	N/A	N/A	N/A	325	N/A	325	325	N/A	325
Type		Single	Single	N/A	N/A	N/A	N/A	Single	N/A	Single	Single	N/A	Single
Diameter	mm	325	325	N/A	N/A	N/A	N/A	300	N/A	325	325	N/A	325
Auto slack adjuster		Standard	Standard	-	-	-	-	Standard	-	Standard	Standard	-	Standard
TRANSMISSION													
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model		MYY6S	MYY6S	MYY6S (AMT)	MYY6E (AMT)	MYY6S (AMT)	MYY6E (AMT)	MYY6S	MYY6S (AMT)	MYY6S	MYY6S	MYY6S (AMT)	MYY6S
Type		6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh
Shift		Manual Gearshift	Manual Gearshift	Automated Manual	Automated Manual	Automated Manual	Automated Manual	Manual	Automated Manual	Manual Gearshift	Manual Gearshift	Automated Manual	Manual Gearshift
No. of gears forward		6	6	6	6	6	6	6	6	6	6	6	6
1st gear ratio		5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979
2nd gear ratio		3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434
3rd gear ratio		1.862	1.862	1.862	2.040	1.862	2.040	1.862	1.862	1.862	1.862	1.862	1.862
4th gear ratio		1.297	1.297	1.297	1.379	1.297	1.397	1.297	1.297	1.297	1.297	1.297	1.297
5th gear ratio		1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
6th gear ratio		0.759	0.759	0.759	0.769	0.759	0.769	0.759	0.759	0.759	0.759	0.759	0.759
REV		5.701	5.701	5.701	5.071	5.701	5.071	5.068	5.068	5.701	5.701	5.701	5.701
Transfer case		No	No	No	No	No	No	No	No	No	No	No	No
Manual locking hubs (4X4)		No	No	No	No	No	No	No	No	No	No	No	No
Limited slip differential		No	No	No	No	No	No	No	No	No	No	No	No
PTO		PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready
DRIVE AXLE													
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model axle front		F033	F033	F033	F033	F033	F033	F033	F033	F033	F033	F033	F033
Model Drive axle rear		R066	R066	R066	R066	R066	R066	R066	R066	R066	R066	R066	R066
Hypoid		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Final ratio	: 1	4.300	4.300	4.300	5.125	4.300	5.125	5.125	5.125	5.125	5.125	5.125	5.125
SUSPENSION													
Front		Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs
Rear		Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs
Shock absorbers		Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear
Stabilisers		Front	Front	Front	Front	Front	Front	Front	Front	Front	Front	Front	Front
BRAKES													
System type		Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	FULL AIR
Front		Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums
Rear		Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums
Anti-lock braking system (ABS) with EBD		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Park/emergency system		Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft
Exhaust brake		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
ELECTRICAL & FUEL													
Voltage	v	24	24	24	24	24	24	24	24	24	24	24	24
Alternator	A	90	90	90	90	90	90	80	80	90	90	90	80
Fuel tank 1 capacity	ltrs	100	100	100	100	100	100	150	150	200	200	200	200
Fuel tank 2 capacity	ltrs	0	0	0	0	0	0	150	150	0	0	0	0
TYRES													
Size and ply rating - front & rear (tubeless)		215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5
CAB & EXTRAS													
Type		Day	Day	Day	Day	Crew	Crew	Day	Day	Day	Day	Day	Day
Roof		Low	Low	Low	Low	Low	Low	Low	Low	Low	Low	Low	Low
No. of seats (lap rear & centre)		3	3	3	3	7	7	3	3	3	3	3	3
Airconditioning		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Radio / USB		Optional	Optional	Standard	Standard	Standard	Standard	Optional	Standard	Optional	Optional	Standard	Optional
Speakers		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
USB charger		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Daytime running lights (DRL)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Fog lamps (LED)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Headlamps (LED)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Telematics		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Multi information display		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Driver & far passenger airbags		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Central locking		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Electric windows		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Suspension seat (driver)		Standard	Standard	Standard	Standard	No	No	Standard	Standard	Standard	Standard	Standard	Standard
Tilt cab		Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes	Yes
Wet wiper system		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Seat belt		Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter
Reverse alarm		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Front bumper		3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin
Emissions control		-	-	-	DOC	-	DOC	-	-	-	-	-	-
ECE R29 CAB		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

Model		NPR 400	NPR 400 SWB	NPR 400 AMT	NPR 400 AMT E5	NPR 400 CREW AMT	NPR 400 CREW AMT E5	NPR 400 CNG	NPR 400 CNG AMT	NQR 500	NQR 500 SWB	NQR 500 AMT	NQR 550
SMOD		M260NI8	M260NI9	M260NJ0	M260NJ1	M260NJ2	M260NJ3	M260NN4	M260NN3	M260NJ4	M260NJ5	M260NJ7	M260NJ9
Axle layout		4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2	4X2
Control		Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward	Forward
MASS													
Permissible body + payload	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - total (T)	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - front	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Tare - rear	kg	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
GVM	kg	7700	7700	7700	7700	7700	7700	7500	7500	8500	8500	8500	8999
V	kg	7700	7700	7700	7500	7700	7500	7500	7500	8500	8500	8500	8999
GCM	kg	11000	11000	11000	11000	11000	11000	11000	11000	12000	12000	12000	12000
D/T	kg	11000	11000	11000	11000	11000	11000	11000	11000	12000	12000	12000	12000
Axle - front GA/GAU	kg	3100	3100	3100	3100	3100	3100	3100	3100	3300	3300	3300	3300
Axle - front A/AU	kg	3100	3100	3100	3100	3100	3100	2900	2900	3300	3300	3300	3300
Axle - rear GA/GAU	kg	6600	6600	6600	6600	6600	6600	6600	6600	6600	6600	6600	6600
Axle - rear A/AU	kg	5600	5600	5600	5600	5600	5600	5600	5600	6600	6600	6600	6600
Litres of fuel tank 1 included in tare	ltrs	15	15	15	15	15	15	30	30	15	15	15	15
Tools included in tare		Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit	Jack, warning triangle, basic tool kit
Spare wheel included in tare		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
PERFORMANCE													
Gradeability at V	%	32.06	32.06	32.06	34.38	34.38	34.38	34.27	34.27	34.61	34.61	34.61	32.69
Gradeability at D/T	%	22.04	22.04	22.04	23.44	23.44	23.44	23.37	23.37	24.52	24.52	24.52	24.52
Max. geared road speed (without SLD)	km/h	116	116	116	116	116	116	118	118	107	107	107	107
Max allowable speed (SLD for SA)	km/h	100	100	100	100	100	100	100	100	100	100	100	100
MAJOR DIMENSIONS													
OL - Overall length	mm	7355	5985	7355	7355	7355	7355	TBA	TBA	7355	5985	7355	7355
OW - Overall width	mm	2120	2120	2120	2120	2120	2120	TBA	TBA	2120	2120	2120	2120
WB - Wheelbase	mm	4175	3365	4175	4175	4175	4175	TBA	TBA	4175	3365	4175	4175
CA - Cab to bogie/rear axle	mm	3607	2794	3607	3607	2616	2616	TBA	TBA	3607	2794	3607	3607
CE - Cab to end of chassis	mm	5672	4304	5672	5672	4727	4727	TBA	TBA	5672	4304	5672	5672
OH - Overall height	mm	2285	2285	2285	2285	2295	2295	TBA	TBA	2285	2285	2285	2285
FOH - Front overhang	mm	1110	1110	1110	1110	1110	1110	TBA	TBA	1110	1110	1110	1110
ROH - Rear overhang	mm	2070	1510	2070	2070	2070	2070	TBA	TBA	2070	1510	2070	2070
EH - Chassis height rear	mm	840	838	840	840	828	828	TBA	TBA	840	822	840	840
HH - Ground clearance	mm	206	200	206	206	185	185	TBA	TBA	206	195	206	206
Chassis width rear	mm	850	850	850	850	850	850	TBA	TBA	850	850	850	850
Turning radius (curb to curb)	mm	7100	5860	7100	7100	7100	7100	TBA	TBA	7100	5860	7100	7100
Turning radius (wall to wall)	mm	7940	6540	7940	7940	7940	7940	TBA	TBA	7940	6540	7940	7940
ENGINE													
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model		4HK1-TCN	4HK1-TCN	4HK1-TCN	4JJ1-TCC	4HK1-TCN	4JJ1-TCC	4HV1(CNG)	4HV1(CNG)	4HK1-TCN	4HK1-TCN	4HK1-TCN	4HK1-TCN
Capacity	cm3	5,193	5,193	5,193	2,999	5,193	2,999	4,570	4,570	5,193	5,193	5,193	5,193
Layout		Diesel inline 4	Diesel inline 4	Diesel inline 4	Diesel inline 4	Diesel inline 4	Diesel inline 4	CNG	CNG	Diesel inline 4	Diesel inline 4	Diesel inline 4	Diesel inline 4
Type		Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Naturally Aspirated	Naturally Aspirated	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail	Turbocharged Intercooled Common Rail
Power at r/min	kW	110 @ 2600	110 @ 2600	110 @ 2600	91 @ 2800	110 @ 2600	91 @ 2800	96 @ 3200	96 @ 3200	110 @ 2600	110 @ 2600	110 @ 2600	110 @ 2600
Torque at r/min	Nm	404 @ 1600	404 @ 1600	404 @ 1600	354 @ 1600-2600	404 @ 1600	354 @ 1600-2600	353 @ 1400	353 @ 1400	404 @ 1600	404 @ 1600	404 @ 1600	404 @ 1600
Emissions standard		Euro 2	Euro 2	Euro 3	Euro 5	Euro 3	Euro 5	Euro 5	Euro 5	Euro 2	Euro 2	Euro 3	Euro 2
CLUTCH													
Make		Exedy	Exedy	N/A	N/A	N/A	N/A	Exedy	N/A	Exedy	Exedy	N/A	Exedy
Model		325	325	N/A	N/A	N/A	N/A	325	N/A	325	325	N/A	325
Type		Single	Single	N/A	N/A	N/A	N/A	Single	N/A	Single	Single	N/A	Single
Diameter	mm	325	325	N/A	N/A	N/A	N/A	300	N/A	325	325	N/A	325
Auto slack adjuster		Standard	Standard	-	-	-	-	Standard	-	Standard	Standard	-	Standard
TRANSMISSION													
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model		MYY6S	MYY6S	MYY6S (AMT)	MYY6E (AMT)	MYY6S (AMT)	MYY6E (AMT)	MYY6S	MYY6S (AMT)	MYY6S	MYY6S	MYY6S (AMT)	MYY6S
Type		6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh	6 Speed synchromesh
Shift		Manual Gearshift	Manual Gearshift	Automated Manual	Automated Manual	Automated Manual	Automated Manual	Manual	Automated Manual	Manual Gearshift	Manual Gearshift	Automated Manual	Manual Gearshift
No. of gears forward		6	6	6	6	6	6	6	6	6	6	6	6
1st gear ratio		5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979	5.979
2nd gear ratio		3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434	3.434
3rd gear ratio		1.862	1.862	1.862	2.040	1.862	2.040	1.862	1.862	1.862	1.862	1.862	1.862
4th gear ratio		1.297	1.297	1.297	1.379	1.297	1.397	1.297	1.297	1.297	1.297	1.297	1.297
5th gear ratio		1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
6th gear ratio		0.759	0.759	0.759	0.769	0.759	0.769	0.759	0.759	0.759	0.759	0.759	0.759
REV		5.701	5.701	5.701	5.071	5.701	5.071	5.068	5.068	5.701	5.701	5.701	5.701
Transfer case		No	No	No	No	No	No	No	No	No	No	No	No
Manual locking hubs (4X4)		No	No	No	No	No	No	No	No	No	No	No	No
Limited slip differential		No	No	No	No	No	No	No	No	No	No	No	No
PTO		PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready	PTO Ready
DRIVE AXLE													
Make		ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU	ISUZU
Model axle front		F033	F033	F033	F033	F033	F033	F033	F033	F033	F033	F033	F033
Model Drive axle rear		R066	R066	R066	R066	R066	R066	R066	R066	R066	R066	R066	R066
Hypoid		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Final ratio	: 1	4.300	4.300	4.300	5.125	4.300	5.125	5.125	5.125	5.125	5.125	5.125	5.125
SUSPENSION													
Front		Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs
Rear		Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs	Semi elliptic springs
Shock absorbers		Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear	Front and rear
Stabilisers		Front	Front	Front	Front	Front	Front	Front	Front	Front	Front	Front	Front
BRAKES													
System type		Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	Power Assit	FULL AIR
Front		Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums
Rear		Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums	Drums
Anti-lock braking system (ABS) with EBD		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Park/emergency system		Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft	Drum on Propshaft
Exhaust brake		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
ELECTRICAL & FUEL													
Voltage	v	24	24	24	24	24	24	24	24	24	24	24	24
Alternator	A	90	90	90	90	90	90	80	80	90	90	90	80
Fuel tank 1 capacity	ltrs	100	100	100	100	100	100	150	150	200	200	200	200
Fuel tank 2 capacity	ltrs	0	0	0	0	0	0	150	150	0	0	0	0
TYRES													
Size and ply rating - front & rear (tubeless)		215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5	215/75R17.5
CAB & EXTRAS													
Type		Day	Day	Day	Day	Crew	Crew	Day	Day	Day	Day	Day	Day
Roof		Low	Low	Low	Low	Low	Low	Low	Low	Low	Low	Low	Low
No. of seats (lap rear & centre)		3	3	3	3	7	7	3	3	3	3	3	3
Airconditioning		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Radio / USB		Optional	Optional	Standard	Standard	Standard	Standard	Optional	Standard	Optional	Optional	Standard	Optional
Speakers		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
USB charger		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Daytime running lights (DRL)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Fog lamps (LED)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Headlamps (LED)		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Telematics		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Multi information display		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Driver & far passenger airbags		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Central locking		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Electric windows		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Suspension seat (driver)		Standard	Standard	Standard	Standard	No	No	Standard	Standard	Standard	Standard	Standard	Standard
Tilt cab		Yes	Yes	Yes	Yes	No	No	Yes	Yes	Yes	Yes	Yes	Yes
Wet wiper system		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Seat belt		Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter	Pre-tensioner load limiter
Reverse alarm		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Front bumper		3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin	3 - piece resin
Emissions control		-	-	-	DOC	-	DOC	-	-	-	-	-	-
ECE R29 CAB		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard


OFF
AM 1:54
2026
9/27
(SUN)
×1000r/min
km/h
ISUZU
SRS AIRBAG

60+ YEARS ISUZU TRUCKS IN SOUTH AFRICA

1 13 YEARS BECAUSE OF YOU

ISUZU | TRUCKS



ENGINEERED FOR *AFRICA*,
BY *SOUTH AFRICANS*.


NMR
AMT
ISUZU
N-SERIES

www.isuzu.co.za

ISUZU

With you, for the long run

For more information
Contact your nearest authorized ISUZU dealer
Or visit www.isuzu.co.za

Information is correct at the time of print.
November 2026. Ts & Cs apply.

*TBC
permissible payload and tare to be confirmed after the official ship to commerce.