



ISUZU FXZ 26-360 TIPPER

| | | |
|-------------|--|---------|
| SMOD | | M180FC9 |
| Axle layout | | 6X4 |
| Control | | Forward |

"Body for illustration purposes only"

| MASS | | |
|--|--|-------|
| Permissible body + payload | kg | 17970 |
| Tare - total (T) | kg | 7530 |
| Tare - front | kg | 3950 |
| Tare - rear | kg | 3580 |
| GVM | kg | 25500 |
| V | kg | 25500 |
| GCM | kg | 43500 |
| D/T | kg | 43500 |
| Axle - front GA/GAU | kg | 7500 |
| Axle - front A/AU | kg | 7500 |
| Axle - rear GA/GAU | kg | 21000 |
| Axle - rear A/AU | kg | 18000 |
| Litres of fuel tank 1 included in tare | ltrs | 15 |
| Litres of fuel tank 2 included in tare | ltrs | - |
| Tools included in tare | Jack, warning triangle, basic tool kit | |
| Spare wheel included in tare | | Yes |
| Fifth Wheel Included in tare | | No |

| PERFORMANCE | | |
|---|------|-------|
| Gradeability at V (%) | % | 45.19 |
| Gradeability at D/T (%) | % | 25.61 |
| Max. geared road speed - Without SLD (km/h) | km/h | 107 |
| Max allowable speed (SLD for SA) | km/h | 80 |

| MAJOR DIMENSIONS | | |
|-------------------------------|----|-------|
| OL - Overall Length | mm | 7790 |
| OW - Overall Width | mm | 2515 |
| WB - Wheelbase | mm | 4330 |
| CA - Cab to Bogie / Rear Axle | mm | 3660 |
| CE - Cab to End of Chassis | mm | 5640 |
| OH - Overall Height | mm | 2980 |
| FOH - Front Overhang | mm | 1480 |
| ROH - Rear Overhang | mm | 2815 |
| Rear Axle Bogie Spacing | mm | 1370 |
| 1/2 Rear Axle Bogie Spacing | mm | 685 |
| EH - Chassis Rear End Height | mm | 1150 |
| HH - Ground Clearance | mm | 260 |
| Chassis Width - Rear | mm | 850 |
| Turning Radius - Curb to Curb | mm | 10400 |
| Turning Radius - Wall to Wall | mm | 12300 |

| ENGINE | | |
|--------------------|----|--------------------------------------|
| Make | | ISUZU |
| Model | | 6UZ1-TCC |
| Capacity (cm3) | | 9839 |
| Layout | | Diesel Inline 6 |
| Type | | Turbocharged Intercooled Common Rail |
| Power at r/min | kW | 265 @ 2000 |
| Torque at r/min | Nm | 1422 @ 1400 |
| Emissions standard | | Euro 3 |

| CLUTCH | | |
|-----------|----|------------------------|
| Make | | Exedy |
| Model | | 430 |
| Type | | Single |
| Diameter | mm | 430 |
| Operation | | Hydraulic Air-Assisted |

| TRANSMISSION | | |
|----------------------|--|-------------------|
| Make | | ZF |
| Model | | ZF9S1310 |
| Type | | Synchromesh |
| Shift | | Manual Gear-shift |
| No. of gears forward | | 9 |
| Crawler Gear ratio | | 9.480 |
| 1st gear ratio | | 0.750 |
| PTO (Power Take-Off) | | PTO Ready |

| DRIVE AXLE | | |
|------------------------|----|----------|
| Make | | ISUZU |
| Model Drive axle front | | F075 |
| Model Drive axle rear | | RT210 |
| Hypoid | | Standard |
| Final ratio | :1 | 5.125 |

| SUSPENSION | | |
|-----------------|--|--------------------|
| Front | | Multi-Leaf Springs |
| Rear | | Multi-Leaf Springs |
| Shock Absorbers | | Front & Rear |
| Stabilisers | | Front |

| STEERING | | |
|-----------|--|-------|
| Operation | | Power |

| BRAKES | | |
|--------------------------------|--|----------|
| System Type | | Full Air |
| Front | | Drums |
| Rear | | Drums |
| Anti-Lock Braking System (ABS) | | Standard |
| Park / Emergency System | | Spring |
| Exhaust Brake | | Standard |
| Engine brake | | No |
| Retarder | | Optional |

| ELECTRICAL & FUEL | | |
|----------------------|------|-----|
| Fuel tank 1 capacity | ltrs | 200 |
| Fuel tank 2 capacity | ltrs | - |

| TYRES | | |
|-----------------------------|--|-------------|
| Size and ply rating - front | | 315/80R22.5 |
| Size and ply rating - rear | | 315/80R22.5 |

| CAB & EXTRAS | | |
|------------------|--|---|
| Type | | Medium |
| Roof | | Low |
| No. of Bunks | | 1 |
| No. of Seats | | 3 |
| Air Conditioning | | Standard |
| Driver Airbag | | Standard |
| Radio / CD | | Standard |
| Tachograph | | Optional |
| Telematics | | Standard |
| Tilt Cab | | Yes, Hydraulic / Electric with Mechanical Hand Pump |

BUILD FOR LIFE

www.isuzu.co.za f X @ in
ISUZU
With you, for the long run