



# UL LISTED MAGLOCKS

MAGLOCKS WITH ADJUSTABLE RELOCK TIME DELAY & LOCK STATUS SENSOR



## PRODUCT



[Go to the product page](#)

## CERTIFICATIONS



## DESCRIPTION

BEA's **UL LISTED MAGLOCKS** provide a standards compliant locking solution for retail, healthcare, banking and other high security facilities that require UL Listed security products. maglocks can be used on hollow metal, wood, aluminum, glass and composite door materials.

The **UL LISTED MAGLOCKS** are available in surface mount single or double door configurations, with holding force of 600 or 1,200 lbs. These locks include adjustable zero to 90 second relock time delay and a lock status sensor with visible LED.



### Customizable

Adjustable zero to 90 second relock time delay

### Enhanced Reliability

Lock status sensor with visible LED offers either normally open (NO) or normally closed (NC) output configurations

### UL Listed

Input voltage of 12 / 24 VDC, must be used with UL Listed power supply

### Mounting Accessories

Variety of mounting hardware available

### Convenient Packages Available

Available in access control packages with request-to-exit sensor, logic module, actuator, power supply and maglock

## TECHNICAL SPECIFICATIONS

### 10MAGLOCK3UL

<b>Door Configuration</b>	Single, surface mount
<b>Holding Force</b>	600 lb
<b>Input Voltage</b>	12 / 24 VDC (UL Listed power supply required)
<b>Power Consumption</b>	505 mA @ 12 VDC 260 mA @ 24 VDC
<b>Dimensions</b>	9.84" (W) x 1.65" (H) x 1.02" (D)
<b>Material</b>	Anodized Aluminum housing
<b>Relock Time Delay</b>	0 – 90 s
<b>Sensor</b>	Lock Status Sensor (NO or NC outputs)
<b>Output Relay</b>	Up to 1 A @ 24 VDC

### 10MAGLOCK6UL

<b>Door Configuration</b>	Double, surface mount
<b>Holding Force</b>	600 lb
<b>Input Voltage</b>	12 / 24 VDC (UL Listed power supply required)
<b>Power Consumption</b>	505*2 mA @ 12 VDC 260*2 mA @ 24 VDC
<b>Dimensions</b>	19.76" (W) x 1.65" (H) x 1.02" (D)
<b>Material</b>	Anodized Aluminum housing
<b>Relock Time Delay</b>	0 - 90 s
<b>Sensor</b>	Lock Status Sensor (NO or NC outputs)
<b>Output Relay</b>	Up to 1 A @ 24 VDC

### 10MAGLOCK1UL

<b>Door Configuration</b>	Single, surface mount
<b>Holding Force</b>	1200 lb
<b>Input Voltage</b>	12 / 24 VDC (UL Listed power supply required)
<b>Power Consumption</b>	505 mA @ 12 VDC 260 mA @ 24 VDC
<b>Dimensions</b>	10.47" (W) x 2.87" (H) x 1.58" (D)
<b>Material</b>	Anodized Aluminum housing
<b>Relock Time Delay</b>	0 - 90 s
<b>Sensor</b>	Lock Status Sensor (NO or NC outputs)
<b>Output Relay</b>	Up to 1 A @ 24 VDC

### 10MAGLOCK5UL

<b>Door Configuration</b>	Double, surface mount
<b>Holding Force</b>	1200 lb
<b>Input Voltage</b>	12 / 24 VDC (UL Listed power supply required)
<b>Power Consumption</b>	505*2 mA @ 12 VDC 260*2 mA @ 24 VDC
<b>Dimensions</b>	20.94" (W) x 2.87" (H) x 1.58" (D)
<b>Material</b>	Anodized Aluminum housing
<b>Relock Time Delay</b>	0 – 90 s
<b>Sensor</b>	Lock Status Sensor (NO or NC outputs)
<b>Output Relay</b>	Up to 1 A @ 24 VDC

\*This product must be powered from a UL Listed, regulated, power-limited, power supply

## PRODUCT SERIES



**10MAGLOCK3UL**  
600 lb / Single



**10MAGLOCK6UL**  
600 lb / Double



**10MAGLOCK1UL**  
1,200 lb / Single



**10MAGLOCK5UL**  
1200 lb / Double



**10LZBRMAG3UL**  
L & Z Bracket for  
600 lb / Single



**10LZBRMAG1UL**  
L & Z Bracket for  
1,200 lb / Single



**10MAG6LZUL**  
(2) L & Z Bracket for  
600 lb / Double



**10MAG5LZUL**  
(2) L & Z Bracket for  
1,200 lb / Double



**10UBRACKETUL**  
Glass door  
mounting kit



**10FILLER14UL**  
1/4" x 3/4" Filler Plate



**10FILLER12UL**  
1/2" x 3/4" Filler Plate



**10FILLER34UL**  
3/4" x 3/4" Filler Plate



**10FILLER58UL**  
1/16" x 3/4" Filler Plate



**10RIMHOUSING3UL**  
Armature plate housing  
for single 600 lb



**10RIMHOUSING1UL**  
Armature plate housing  
for single 1,200 lb



**10SPACER3UL**  
Vertical spacer bracket  
for single 600 lb



**10SPACER1UL**  
Vertical spacer bracket  
for single 1,200 lb



**10PS12-24**  
UL / ULCL Listed power  
supply



**10PS12-24D**  
UL / ULCL Listed power supply,  
backup circuit  
(battery not included)

**DISCLAIMER** Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

WWW.BEASENSORS.COM



BEA AMERICAS / RIDC Park West / 100 Enterprise Drive / Pittsburgh, PA  
T 1-800-523-2462 / F 1-888-523-2462 / E info-us@BEAsensors.com

A Halma company