



RC multi-technology reader controller

Overview

The Schlage® RC is an IP reader controller that combines patented Pure IP™ access control technology together with Schlage's intelligent hardware, delivering a cost-effective all-in-one edge device that easily integrates into open PACS solutions. The Schlage RC connects to existing IT networks via a single PoE cable; reducing installation time and eliminating the need to run separate power to the door. The Schlage RC provides real-time connectivity with local mode feature, and can be managed in the same system as Schlage NDE and LE wireless locks.

Three models are available to allow for common mounting options; creating a simple install process at each door.

- **RC11:** Mullion mount, multi-technology IP reader controller
- **RC15:** Single gang mount, multi-technology IP reader controller
- **RCK15:** Single gang mount, multi-technology IP reader controller with keypad

Schlage RC reader controllers provide both a modern look and an advanced feature set. Designed with technology to support Bluetooth, NFC (Near Field Communication), smart credentials (13.56 MHz) and standard proximity credentials (125 kHz); end users can define their migration path to secure credentials.



Features and benefits

- Host and local modes supported
 - Host mode allows for real time connectivity where the host makes real time decisions for access, LED and buzzer sequencing, etc. Should the connection drop, the device will switch to local mode.
 - Local mode allows the Schlage RC to function without a connection to the network. This results in faster user response times, less network traffic, and reduced host system loading.
- Reader controllers support 125 kHz proximity, 13.56 MHz smart technology, 2.4 GHz Bluetooth and Near Field Communication (NFC)
- Tamper detection via accelerometer senses any type of altering and prevents a security breach with the reader.
- Communication is secured using industry standard TLS 1.2 encryption
- Supports network communication speeds of 10 or 100 mbps half or full duplex
- Commission via ENGAGE™ mobile app for easy configuration
- Three configurable inputs; Door Position (DPS), Request to Exit (REX), and Auxiliary (AUX)
- Mullion, wall mount and wall mount with keypad form factors
- Credential parity with Schlage readers and wireless locks; ISONAS credential parity is a factory orderable option
- Accommodates interior, exterior, metal and non-metal installation environments

CYBERSECURITY

Learn about Allegion's commitment



Model	RC11	RC15	RCK15
Reader technology	Mobile (NFC and Bluetooth), smart, proximity	Mobile (NFC and Bluetooth), smart, proximity	RC15 + keypad
Mounting style	Mullion	Single gang	Single gang
Modes and capacity	Host mode: real time connectivity; unlimited credential, events, time schedules, and holidays capacity* Local mode: decisions made at device when connection is offline or configured to local; 64,000 credentials - 5,000 events - 32 time schedules - 32 holidays <small>* Host capacity is based on your host programming; contact your support team</small>		
Network communications	10/100 Ethernet - half or full duplex - Cat5e, Cat6, or better cable WebSockets - Network host or client modes - DHCP addressing TLS1.2		
Visual and audible communications	LED (red, amber, green) Audible indicator (on/off)		
System Interfaces	2 TTL Lines / Clock & Data (for use with Advanced Security Module (ASM))		
Inputs	Request to Exit (REX) / Auxiliary Input (AUX) / Door Position Switch (DPS)		
Tamper	Yes		
Power input	PoE or PoE+ (IEEE 802.3af, Class 0) DC power: 10-13 VDC Please note: 24 VDC is not approved for this device		
Power output	600 mA maximum output current @ 12 VDC		
PoE / PoE+ Pigtail	26 AWG, Cat5E, 8" length		
Physical dimensions	5.94" x 1.77" x 1.0" (15.1cm x 4.5cm x 2.5cm)	5.13" x 3.25" x 1.0" (13.0cm x 8.3cm x 2.5cm)	5.13" x 3.25" x 1.0" (13.0cm x 8.3cm x 2.5cm)
Weight	5.8 oz (164.4 g)	8.1 oz (229.6 g)	8.2 oz (232.5 g)
Software compatibility	Works with open PACS systems including ISONAS Pure Access™ Cloud. See us.allegion.com/alliances for details.		
FIPS201 compliant ¹	No		
Certifications	FCC, IC, UL294 V7 / cUL Listed RED Directive, CE Mark, IP65, REACH, Bluetooth SIG, RoHS3		
Frequency	2.4 GHz Bluetooth, 13.56 MHz Smart, 125 kHz Proximity		
Standards	ISO 14443A, ISO 15693		
Operating temperatures	-31° to 151°F (-40° to 66°C)		

Color option



Black
(standard)

- DESFire® CSN, HID iCLASS® CSN, Inside Contactless PicoTag® CSN, ST Microelectronics® CSN, Texas Instruments Tag-It® CSN, Phillips I-Code® CSN
- Schlage® Proximity, ISONAS Prox, HID® Proximity up to 37 bit lengths, GE/CASI® Proximity, AWID® Proximity, LenelProx®
- Schlage smart cards using MIFARE Classic® EV1, Schlage smart cards using MIFARE Plus®, Schlage smart cards using MIFARE® DESFire® EV1, Schlage smart cards using MIFARE® DESFire® EV2 . ISONAS credential parity available; specify CE-5901-0402 with your RC order
- Compatible with Bluetooth and NFC-enabled devices

Allegion, the Allegion logo, Schlage and the Schlage logo are trademarks of Allegion plc, its subsidiaries and/or affiliates in the United States and other countries. All other trademarks are the property of their respective owners

About Allegion

Allegion (NYSE: ALLE) is a global pioneer in seamless access, with leading brands like CISA®, Interflex®, LCN®, Schlage®, SimonsVoss® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion secures people and assets with a range of solutions for homes, businesses, schools and institutions.

For more, visit www.allegion.com

KRYPTONITE ■ LCN ■  ■ STEELCRAFT ■ VON DUPRIN



© 2023 Allegion
013614, Rev. 03/23
www.allegion.com/us