

TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
MATIERE	CANVAS	FT N° 62 V1

This is a through-coloured PVC wallcovering, printed using water-based inks, on a high-tear non-woven backing. Extra washable and impact resistant, this wallcovering is suitable for intensive use in public buildings. In line with regulations, it has M1 and B s2 d0 fire resistance rating. Quick and easy to hang. Simply paste the wall and align the edges of each strip.

Description

Item code	CVS 9130...
Name	CANVAS
Range	MATIERE
Type	PVC wallcovering
Plain	Yes - 20 colours
Patterned	No

Composition

Type	PVC
Backing	High-tear non-woven backing
Weight	350 g/m ²
Thickness	0.55 mm
Ink	Water-based printing inks

Regulations - Environment

Fire rating	B s2 d0 / ASTM 84 - Class A	Euroclass / ASTM
Acoustics	Alpha w = 0,10 or 0,15 according to the substrate	/ acoustic report: PEUTZ - N°A3151
Light fastness	> 6	Standard EN 259
VOCs	A+	ISO 16000
CE marking	DOP-CPR-VSTI-20 / www.texdecor.fr	Standard EN 15 102
Care	Extra washable	Standard EN 259
Use	Intensive	Standard EN 259

Packing - Packaging

Size of widths	1 m, +/- 3%
Length of roll	30 lm
Partial sale to order	Yes
Box size	1030 X 350 X350 cm = 30 lm
Weight of a roll	11 Kg (+/- 10%)

Hanging

Adhesive	Ovalit TM - Quelyd Murale	MSDS available
Adhesive instructions	Apply to the wall, using a roller	
Quantity of adhesive	+/- 200gr/m ²	
Match	Free match	
Hanging direction	Invert strips	
Seam	Edge to edge	
Removal	Pelable	