

TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
 ACOUSTIC	<b>POLYFORM Vinacoustic</b>	FT N° 53 V1

This is a PVC foam wallcovering that is dyed in the mass, micro-perforated, printed with water-based ink, on an Alpha 0.25 acoustic non-woven backing. Highly washable and brushable, resistant to impacts and scratches, this wall covering is particularly well-suited for intensive use in commercial and public establishments. In accordance with regulations, it has a M1 and Cs3d0 fire rating. Quick and easy to hang by simply pasting on the wall and hanging the strips edge to edge.

### Description

Item code	PFY 9101... / 9102... / 9103...
Name	Polyform Vinacoustic
Range	Acoustic 0.3
Type	PVC wallcovering
Plain	20 coordinated plains in the Vinacoustic Dune collection
Patterned	3 designs - 10 colors

### Composition

Type	PVC
Backing	Acoustic non-woven polyester
Weight	890 g/m <sup>2</sup>
Thickness	3,5 mm
Ink	Water-based printing inks
Treatment	Bio-Pruf treatment on request > 500ml

### Regulations - Environment

Fire rating	C s3 d0 / M1	Standard EN 13 501 -1
Acoustics	Alpha w = 0,25	Standard EN 20 354
Light fastness	6	Standard EN 259
L.R.V rate	Light reflectance value (87 max)	LRV Scale
Thermal resistance	R = 0,08 m <sup>2</sup> .K/W	Standard EN 12 667
VOCs	A+	ISO 16000
CE marking	Yes	Standard EN 15 102
Care	Washable scrubbable	Standard EN 259
Use	Intensive	Standard EN 259
Breaking strength	daN : L>35 / T >30	ISO 1421
Color fastness to rubbing	dry 5/4 - wet 5/4	NF ISO 105
Certification	Yes	Oeko-tex standard 100
Manufactured by	a certified factory	ISO 9002

### Packing - Packaging

Size of widths	+/- 1,25m	
Length of roll	25ml - 15ml - 10ml - 5ml	
Partial sale to order	No	
Dispenser box	Yes	FSC Certified Cardboard
Suspended core packaging	Yes	
Box size	1450 X 350 X3 50 cm = 25ml ,15ml / 1450 X 215 X 230 cm = 10ml	
Weight of a roll	31,22 Kg = 25ml, 19,65 Kg = 15ml, 13,87 Kg = 10ml. (+/- 10%)	

### Hanging operation

Adhesive	Ovalit TM - Ovalit S (Metylan - Henkel)
Adhesive instructions	Apply to the wall, using a roller
Quantity of adhesive	250-450 gr/m <sup>2</sup>
Match	Yes
Seams	Edge to edge seams
Removal	Dampen before stripping
For partitions	Yes - 130cm width
Demo video	Yes