

TECHNICAL DATA SHEET - DESCRIPTION		
RANGE	COLLECTION	NUMBER
 ACOUSTIC	POLYFORM Eos 2	FT N° 76/V2

This acoustic wallcovering combines the technical qualities of a high performance acoustic backing and the nobility of a warm faux-suede, made up of foam and micro-perforated fabric to improve acoustic transparency, Alpha W 0.3. Fast and easy hanging, it is delivered with a transparent film that protects the fabric from building site storage conditions. According to the regulation, this wallcovering gets an efficient fire classification.

Description

Item code	PFYV 9152...
Name	POLYFORM Eos 2
Range	Acoustic 0.3
Type	Acoustic textile wallcovering
Patterned	7 colors - Strippe Vertigo

Composition

Type	Micro-perforeted polyester faux-suede
Backing	Polyurethane acoustic foam
Weight	500 g/m ²
Thickness	5 / 6 mm
Treatment	Waterproof surface

Regulations - Environment

Fire rating	B s2 d0 / Class A	Standard EN 13 501 -1 / ASTM - E 84
Acoustics	Alpha w = 0,30 / NRC = 0,25	Standard EN 20 354
Light fastness	> 4 to 7	Standard EN 259
Thermal resistance	R = 0,12 m ² .K/W	Standard EN 12 667
VOCs	A+	ISO 16000
CE marking	DOP-CPR-EOSMD-59	Standard EN 15 102
Care	Wipeable	Standard EN 259
Use	Normal	Standard EN 259

Packing - Packaging

Size of widths	140 cm (+/- 3%)	
Length of roll	25ml, 15ml, 10ml, 5 ml	
Partial sale to order	No	
Dispenser box	Yes	FSC Certified Cardboard
Suspended core packaging	Yes	
Box size	1530 X 480 X 490 mm for 25 lm and 12,50 lm	
Weight of a roll	20,00 Kg for 25 lm, 11,25Kg for 12,50 lm (+/- 10%)	

Hanging operation

Adhesive	Ovalit TM - Ovalit F (Metylan - Henkel)
Adhesive instructions	Apply to the wall, using a roller
Quantity of adhesive	250 - 450 gr/m ²
Match	Free match
Hanging direction	Straight strips
Seams	Edge to edge / butt seam
Removal	Dampen before stripping
For partitions	Yes - 140cm width