

DESIGN SOLUTIONS 5

Pattern Number	Weight	Backing	Installation	Roll Size
DES-501 ~ DES-504	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-505 ~ DES-506	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-507 ~ DES-508	15 oz/ly (340 gr/m²)	Scrim	Straight Hang/Cross Match	52" - 54" * 30 Yards
DES-509 ~ DES-512	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-513 ~ DES-519	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-520 ~ DES-523	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-524 ~ DES-527	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-528 ~ DES-531	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-532 ~ DES-533	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-534 ~ DES-535	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Cross Match	52" - 54" * 30 Yards
DES-536 ~ DES-537	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-538 ~ DES-539	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-540 ~ DES-541	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-542 ~ DES-546	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards
DES-547	15 oz/ly (340 gr/m²)	Scrim	Reverse Hang/Random Match	52" - 54" * 30 Yards

SPECIFICATIONS

- 52-54" (132/137 cm) width.
- Meets/Exceeds CCC-W-408D & W101 Specifications
- High tear and tensile strength
- Highly cleanable & stain resistant
- Fire Certification - Class A - ASTME84
- Fire Certification-GB8624-2012-B1(B-s2,d0, t0)
- Color fast water-based inks
- Low VOC CA01350 (Indoor Air Quality)
- No formaldehyde or heavy metals
- Meets/Exceeds GB18185-2001 Standard for harmful substances
- Meets BS476 Part 6/7-British Class O Standard
- Non-ortho phthalate plasticizers
- Visit versawallcovering.com for technical information.

WARRANTY

Versa products are guaranteed to be free of defects in workmanship and materials for five years.