



PVC-FREE WALL PROTECTION

Vantage II meets or exceeds all Type II requirements of CCC-W-408A/D and W-101

#### Specifications

Content  
Weight (Avg)  
Thickness  
Width  
Backing  
Packaging

#### Performance

Olefin composite  
20 oz/ly (452 gr/m<sup>2</sup>)  
.025" average  
52/54" (132/137 cm)  
Osnaburg  
30 yd bolts

#### Fire Safety

- Class A ASTM-E 84(GRC)
- NFPA 101 Life Safety Code
- CAN/ULC S102
- EN 13501 B-S1,d0

#### Features and Benefits

- Bleach cleanable & disinfectant safe
- Chemical & stain resistant

#### Environmental and Health

- evo® PVC-free
- 20% Recycled Content
- Phthalate Free
- Health Product Declaration (HPD)
- Prop 65 Compliant
- Free of Antimicrobials
- Free of Halogenated flame retardants
- Meets State of Washington Bldg. Specification for Indoor Air Quality
- Meets California Section 01350 Indoor Air Quality Standard
- Aggressive manufacturing materials recovery and reuse program
- Highly cleanable water-based inks

#### USGBC LEED Support

- Supports USGBC LEED v4.1 Criteria
- Material and Resources; Building Product Disclosure and Optimization (includes Recycled Content, Construction Waste Management; HPD's)
- Indoor Environmental Quality: Low emitting materials

Visit [versawallprotection.com](http://versawallprotection.com) for complete specifications, installation instructions, cleaning directions and warranty.

**VERSA**<sup>®</sup>  
DESIGNED SURFACES

