

TECHNICAL DATA SHEET

QUESTEX®

C O N T R A C T

Horizon Stripe

52"- 54" Type II 20oz. Contract Wallcovering

PHYSICAL PROPERTIES

TOTAL WEIGHT:

U.S. UNITS

20.0 oz per linear yard

13.3 oz per square yard

METRIC UNITS

619 grams / linear meter

451 grams / square meter

BACKING: Nonwoven

WIDTH: 52"- 54" (1.32m - 1.37m)

DESIGN: Random / Random

5 YEAR WARRANTY AGAINST MANUFACTURING DEFECTS

*Use only adhesives and primers as recommended by the manufacturer.

All patterns stocked are in 30 linear yard bolts.

Copyright © 2025 Questex, All Rights Reserved.
215-516-7072 | contract@wallquest.com
465 Devon Park Drive, Wayne, PA 19087 USA
www.wallquest.com/questex - MADE IN U.S.A.

TECHNICAL SPECIFICATIONS

FIRE HAZARD CLASSIFICATION RESULTS:

TESTED IN ACCORDANCE WITH ASTM E-84 TUNNEL TEST

CLASS "A" FIRE RATED

FLAME SPREAD 25

SMOKE DEVELOPED 20

EN13501 (B-s1,d0)

This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

FEDERAL SPECIFICATIONS:

Questex exceeds G.S.A Federal Specification CCC-W-408D for Type II materials using test procedures detailed in Federal Specifications CCC-T-191-B. This wallcovering passes The National Fire Protection Association NFPA286 Corner Burn Test.

ANTI-MICROBIAL FEATURES:

Vinyl wallcoverings contain bactericides and mildew inhibitors to discourage the growth of mold and mildew under normal conditions.