

# PRODUCT SAFETY DATA SHEET



HEALTH • HYGIENE • HOME

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

DETTOL All in One Disinfectant Spray Lemon Breeze

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Surface disinfectant

### 1.3. Details of the Supplier of the Safety Data Sheet

#### The United Kingdom:

RB UK Commercial Ltd  
Wellcroft House  
Wellcroft Road  
Slough, Berkshire SL1 4AQ

#### The Republic Of Ireland:

Reckitt Benckiser Ireland Ltd  
7 Riverwalk  
Citywest Business Campus  
Dublin 24 Ireland

### 1.4 Emergency telephone number

**RB UK Contact Telephone:** 0333 2005 345

**RB ROI Contact Telephone:** 01 630 5429

**Only available during the following office hours:** 09:00 - 17:00 weekdays

**RB email:** [consumer.relations-ukroi@rb.com](mailto:consumer.relations-ukroi@rb.com) ⓘ

**Poisons Information Centre of Ireland** 01 809 2166 8am-10pm 7 days a week

<b>Revision Date:</b>	<b>Revision:</b>	<b>Replacing:</b>	<b>RB Ref No:</b>
5 November 2019	1	2514871402 01 Sept 2019	2584571401

**Revisions:** Name change

### Additional useful information

**Product Format:** Aerosol Disinfectant

**Storage Conditions:** Store below 50°C

**Proper Shipping Name:** Aerosols, flammable

**UN Transport Code:** UN: 1950 **Class & Packing Group:** 2.1

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 2, H223, H229

Eye Irrit. 2, H319


The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

**Hazard statements** : Flammable aerosol.  
Pressurised container: May burst if heated.  
Causes serious eye irritation.

#### Precautionary statements

**General** : Keep out of reach of children. If medical advice is needed, have product container or label at hand.

**Prevention** : Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear eye protection. Keep away from sources of ignition - No smoking. Do not spray near an electrical fire, heat sources or electrical equipment in use.  
Do not pierce or burn even after use.

**Response** : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Storage** : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Disposal** : Not applicable.

**Hazardous ingredients** : Not applicable.

**Supplemental label elements** : Use only as directed.

#### Ingredient Declaration:

Per 100 g product contains 60.0g ethanol and 0.10g C12-C18-Alkyldimethylbenzyl ammonium saccharinate

Disinfectant

Perfume contains Limonene and Hexyl cinnamic aldehyde

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : None

#### Special packaging requirements

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

## SECTION 2: Hazards identification

**Other hazards which do not result in classification** : None known.

**Additional information** : Intentional misuse by deliberately concentrating & inhaling can be harmful or fatal. Extremes of temperature can occur in motor cars, near ovens, and fireplaces. Do not spray on a naked flame or any incandescent material.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
ethanol	REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≥50 - ≤75	Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1] [2]
Butane	REACH #: 01-2119474691-32 EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	≤10	Flam. Gas 1, H220 Press. Gas Comp. Gas, H280	[2]
propane	REACH #: 01-2119486944-21 EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5	≤3	Flam. Gas 1, H220 Press. Gas Comp. Gas, H280  <b>See Section 16 for the full text of the H statements declared above.</b>	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

## SECTION 4: First aid measures

- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

## SECTION 5: Firefighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

## SECTION 7: Handling and storage

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

#### Seveso Directive - Reporting thresholds (in tonnes)

##### Named substances

Name	Notification and MAPP threshold	Safety report threshold
Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	50	200
Liquefied extremely flammable gases (including LPG) and natural gas	50	200

##### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P3a: Flammable aerosols containing flammable gases or flammable liquids	150	500

**Do not store above the following temperature:** : 50 °C

### 7.3 Specific end use(s)

**Recommendations** : Germ Protection  
Consumer uses

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
ethanol	<b>EU OEL (Europe, 12/2011).</b> TWA: 1000 ppm 8 hours. TWA: 1920 mg/m <sup>3</sup> 8 hours.
Butane	<b>EU OEL (Europe, 7/2012). Notes: Ministry of Labour (Brochure INRS Ed 984, July 2012). Indicative exposure limits</b> TWA: 800 ppm 8 hours. TWA: 1900 mg/m <sup>3</sup> 8 hours.
propane	<b>EU OEL (Europe, 5/2010). Oxygen Depletion [Asphyxiant].</b> OELV-8hr: 1000 ppm 8 hours.

## SECTION 8: Exposure controls/personal protection

**Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
ethanol	DNEL	Long term Inhalation	950 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Inhalation	1900 mg/m <sup>3</sup>	Workers	Local
	DNEL	Dermal	343 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	114 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Inhalation	950 mg/m <sup>3</sup>	Consumers	Local
	DNEL	Dermal	206 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Oral	87 ng/kg bw/day	Consumers	Systemic

### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
ethanol	Fresh water	0.96 mg/l	Assessment Factors
	Marine water	0.79 mg/l	Assessment Factors
	Sewage Treatment Plant	580 mg/l	Assessment Factors
	Fresh water sediment	3.6 mg/kg dwt	Equilibrium Partitioning
	Marine water sediment	2.9 mg/kg dwt	Equilibrium Partitioning

## 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

## SECTION 8: Exposure controls/personal protection

**Hand protection** : Use chemical resistant gloves classified under Standard EN374 - Protective gloves against chemicals and micro-organisms.

Examples of preferred glove barrier materials include: Nitrile/butadiene rubber ("nitrile" or "NBR"); Chlorinated polyethylene; Butyl rubber; Polyethylene.

Examples of acceptable glove barrier materials include: Natural rubber ("latex"); Neoprene; Viton; Ethyl vinyl alcohol laminate ("EVAL").

A glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended.

Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier. Considering the parameters specified by the glove manufacturer, checks during use should be carried out to ensure the gloves are still retaining their protective properties.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Physical state** : Liquid. [Aerosol]

**Colour** : Clear to pale yellow

**Odour** : Fragrant.

**Odour threshold** : Not available.

**pH** : 10.8 to 11.8 [Conc. (% w/w): 100%]

**Melting point/freezing point** : Not available.

**Initial boiling point and boiling range** : Not available.

## SECTION 9: Physical and chemical properties

<b>Flash point</b>	: Not available.
<b>Evaporation rate</b>	: Not available.
<b>Flammability (solid, gas)</b>	: Not available.
<b>Burning time</b>	: Not applicable.
<b>Burning rate</b>	: Not applicable.
<b>Upper/lower flammability or explosive limits</b>	: Not available.
<b>Vapour pressure</b>	: Not available.
<b>Vapour density</b>	: Not available.
<b>Density</b>	: 0.87 to 0.89 g/cm <sup>3</sup>
<b>Solubility(ies)</b>	: Easily soluble in the following materials: cold water and hot water.
<b>Partition coefficient: n-octanol/ water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not available.
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Not available.
<b>Explosive properties</b>	: Not available.
<b>Oxidising properties</b>	: Not available.
<b>Corrosivity Remarks</b>	: Not available.

### 9.2 Other information

<b>Solubility in water</b>	: Easily soluble in the following materials: cold water and hot water.
<b>Type of aerosol</b>	: Spray
<b>Heat of combustion</b>	: 18.18 kJ/g

No additional information.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame).
<b>10.5 Incompatible materials</b>	: No specific data.
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
<b>Instability Conditions</b>	: Not available.
<b>Instability temperature</b>	: Not available.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dettol Disinfectant Spray_FF8326283_D8335558 (EU)	LC50 Inhalation Vapour	Rat - Male, Female	>2.75 mg/l	4 hours
ethanol	LD50 Dermal	Rat - Male	>5050 mg/kg	-
	LD50 Oral	Rat - Female	>5050 mg/kg	-
butane	LC50 Inhalation Vapour	Rat	124700 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	7 g/kg	-
	LC50 Inhalation Vapour	Rat	658000 mg/m <sup>3</sup>	4 hours

**Conclusion/Summary** : Not classified Information is based on toxicity test result of the concentrate of a similar product.

#### Acute toxicity estimates

Route	ATE value
Oral	>5000 mg/kg

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Dettol Disinfectant Spray_FF8326283_D8335558 (EU)	Eyes - Cornea opacity	Rabbit	>0.2	minutes	21 days
ethanol	Skin - Oedema	Rabbit	0.1	-	21 days
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-

**Skin** : Non-irritant to skin. Information is based on toxicity test result of the concentrate of a similar product.

**Eyes** : Causes serious eye irritation. Information is based on toxicity test result of the concentrate of a similar product.

**Respiratory** : Based on available data, the classification criteria are not met.

#### Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Dettol Disinfectant Spray_FF8326283_D8335558 (EU)	skin	Guinea pig	Not sensitizing

**Skin** : Non-sensitiser. Information is based on toxicity test result of the concentrate of a similar product.

**Respiratory** : Based on available data, the classification criteria are not met.

#### Mutagenicity

No known effect according to our database.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

## **SECTION 11: Toxicological information**

### **Carcinogenicity**

No known effect according to our database.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### **Reproductive toxicity**

No known effect according to our database.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### **Teratogenicity**

No known effect according to our database.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### **Specific target organ toxicity (single exposure)**

No known effect according to our database.

### **Specific target organ toxicity (repeated exposure)**

No known effect according to our database.

### **Aspiration hazard**

No known effect according to our database.

### **Potential acute health effects**

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

### **Symptoms related to the physical, chemical and toxicological characteristics**

- Eye contact** : Adverse symptoms may include the following:
  - pain or irritation
  - watering
  - redness
- Inhalation** : Adverse symptoms may include the following:
  - respiratory tract irritation
  - coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

#### **Short term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

#### **Long term exposure**

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

### **Potential chronic health effects**

Not available.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

## SECTION 11: Toxicological information

**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 µl/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

No known effect according to our database.

**Conclusion/Summary** : The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
ethanol	-0.35	-	low
butane	2.89	-	low
propane	1.09	-	low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## SECTION 14: Transport information

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	UN1950	UN1950	UN1950	UN1950
<b>14.2 UN proper shipping name</b>	AEROSOLS	AEROSOLS	AEROSOLS	Aerosols, flammable
<b>14.3 Transport hazard class(es)</b>	2 	2 	2.1 	2.1 
<b>14.4 Packing group</b>	-	-	-	-
<b>14.5 Environmental hazards</b>	No.	No.	No.	No.
<b>Additional information</b>	<u>Limited quantity</u> 1 L  <u>Special provisions</u> 190, 327, 625, 344  <u>Tunnel code</u> (D)	<u>Special provisions</u> 190, 327, 625, 344	<u>Emergency schedules (EmS)</u> F-D, S-U  <u>Special provisions</u> 63, 190, 277, 327, 344, 959	<u>Passenger and Cargo Aircraft</u> Quantity limitation: 75 kg Packaging instructions: 203 <u>Cargo Aircraft Only</u> Quantity limitation: 150 kg Packaging instructions: 203 <u>Limited Quantities - Passenger Aircraft</u> Quantity limitation: 30 kg Packaging instructions: Y203

## SECTION 14: Transport information

**Special provisions**  
A145, A167, A802

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions** : None  
**on the manufacture,  
placing on the market  
and use of certain  
dangerous substances,  
mixtures and articles**

**Other EU regulations**

**Europe inventory** : All components are listed or exempted.

**Ozone depleting substances (1005/2009/EU)**

Not listed.

**Prior Informed Consent (PIC) (649/2012/EU)**

Not listed.

**Aerosol dispensers** :

3



Flammable

**Seveso Directive**

This product is controlled under the Seveso Directive.

**Named substances**

**Name**

Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas  
Liquefied extremely flammable gases (including LPG) and natural gas

**Danger criteria**

**Category**

P3a: Flammable aerosols containing flammable gases or flammable liquids

**Hazard class for water** : 2 Appendix No. 4

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

### Abbreviations and acronyms

: ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aerosol 2, H223, H229 Eye Irrit. 2, H319	Calculation method On basis of test data

### Full text of abbreviated H statements

H220 H223, H229 H225 H280 H319	Extremely flammable gas. Flammable aerosol. Pressurised container: May burst if heated. Highly flammable liquid and vapour. Contains gas under pressure; may explode if heated. Causes serious eye irritation.
--	--

### Full text of classifications [CLP/GHS]

Aerosol 2, H223, H229 Eye Irrit. 2, H319 Flam. Gas 1, H220 Flam. Liq. 2, H225 Press. Gas Comp. Gas, H280	AEROSOLS - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE GASES - Category 1 FLAMMABLE LIQUIDS - Category 2 GASES UNDER PRESSURE - Compressed gas
--	--

This document complements the technical usage instructions but does not replace them. The information contained herein is based on our best current knowledge of the product concerned, and is given in good faith. The attention of recipients is drawn to (amongst other things) the element of risk consequent to use of the product other than that for which it was intended.

In no way does this document remove the need of the recipient of the product to fully understand and apply statutory requirements. It is the recipient's sole responsibility to take due precautions relative to the use made of the product. All information contained herein is only to assist the recipient in fulfilling their statutory duty connected with the use of hazardous materials.

This Document may be entitled Product Safety Data Sheet as required by REACH (Registration, Evaluation, Authorisation and restriction of Chemicals) Annex II OR Product Data Information Sheet where a product is not required to be supported by a full REACH compliant SDS (e.g. not classified as hazardous or out of scope, such as cosmetics).

Changes from the previous version are given in Section 1.

This list of information must not be considered as exhaustive, and does not exonerate the recipient from taking other precautions described in documents other than those mentioned, concerning the storage and use of the product, for which they remain the sole person responsible.