




Office & Work at Home Solution



1080p 30 fps



Plug & Play



Undistorted Field of View

1080p HD Webcam

VISION Mini

The JPL Vision Mini is our smallest 1080p USB webcam with full HD glass lens. The webcam has a tri-fold hinged bracket with a gripper foot so it can be placed securely above your computer or laptop to allow long distance face to face meetings from your conference room or home office. Compatible with all major softphones. Plug & play solution - No additional software or downloads needed.

Overview

| | |
|----------------|--|
| Features | 1080p HD 30fps CMOS Camera |
| | Student work at home solution, schools or university |
| | Full HD 1080p glass lens - No optical distortion |
| | Two microphones - Built in dual stereo |
| | Built in camera in-use LED indicator |
| | Privacy lens cover included |
| | USB 2.0 Type-A connectivity |
| | Desk mount, monitor mount or tripod option |
| | Full 360° camera rotation including 90° tilt for over desk viewing |
| | Automatic low-light correction |
| | AEC – Automatic Echo Cancellation |
| | ANS – Automatic Noise Suppression |
| Certifications | FCC, CE, RoHS, REACH |
| Dimensions | 72 x 33 x 31.7mm |
| Warranty | 24 Month repair or replacement warranty |
| MOQ | Master Shipping Carton: 20 |
| SKU: | 575-354-001 |
| EAN: | 5060126958376 |

Technical Data

| | |
|-------------------------------|---|
| Camera parameters: | |
| Total Pixels | 2 million pixels |
| Lens size | 1/2.7 inch |
| Aperture | 2.5±5% |
| Image area | 5.85mm x 3.27mm |
| Maximum effective pixel | 1920 (H) x 1080 (V) 2.0 million pixels |
| Output image format | MJPEG and YUY2 |
| Field of view | 67°(W) |
| AIC | Automatic Exposure (AE) Auto White Balance (AWB) Dynamic Black Level Calibration (ABLC) |
| Resolution @ 30fps | 1920 x 1080, 1280 x 720, 640 x 480 |
| Microphone parameters: | |
| SNR | ≥60dB |
| Sensitivity | -42±3dB(0dB=1V/pa,1KHz) |
| Far-field distance | 0-2 meters |
| Horizontal voice pickup | Horizontal 180° |
| Communication mode | Full Duplex |
| AIC | Automatic gain control Automatic noise reduction control Automatic echo noise reduction control |
| Other parameters: | |
| Interface type | USB 2.0 Type-A |
| Voltage | 5V/500mAh |
| OS Support | Win 2000/XP/Vista/Win 7/Win 8/Win 10 Linux with UVC (above Linux - 2.6.26) Mac - OS X 10.4.8 or later Win CE with UVC Android 4.0 or above with UVC |
| Size (camera / gift box) | 72 x 33 x 31.7mm / 105 x 70 x 70mm |
| Weight (camera / gift box) | 106g / 150g |

