



SAFETY DATA SHEET
2WORK THICK BLEACH

Page: 1

Compilation date: 01/08/2008

Revision date: 24/04/2019

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 2WORK THICK BLEACH

Product code: 2W03977

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: VOW EUROPE LTD

MAGNA PARK
HARRIER PARKWAY
LUTTERWORTH
LE17 4XT

Tel: 0844 980 8000

Email: WWW.VOWEUROPE.COM

1.4. Emergency telephone number

Emergency tel: NHS 111

NHS Direct Wales 08454647

ROI 01 809 2166

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: * Skin Corr. 1B: H314; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Met. Corr. 1: H290;
Eye Dam. 1: H318; -: EUH206

Most important adverse effects: Causes severe skin burns and eye damage. Very toxic to aquatic life. Toxic to aquatic life with long lasting effects. May be corrosive to metals. Warning! Do not use together with other products. May release dangerous gases (chlorine).

2.2. Label elements

Label elements:

Hazard statements: * H314: Causes severe skin burns and eye damage.

[cont...]

SAFETY DATA SHEET

2WORK THICK BLEACH

Page: 2

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H290: May be corrosive to metals.

EUH206: Warning! Do not use together with other products. May release dangerous gases (chlorine).

Hazard pictograms: GHS05: Corrosion

GHS09: Environmental



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P280: Wear eye protection, protective gloves.

P264: Wash hands thoroughly after handling.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P314: Get medical advice/attention if you feel unwell.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

P332+P313: If skin irritation occurs: Get medical advice/attention.

P304+P341: IF INHALED: if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P362: Take off contaminated clothing.

2.3. Other hazards

Other hazards: Contact with acids liberates toxic gas.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM HYPOCHLORITE SOLUTION CL ACTIVE - REACH registered number(s): 01-2119488154-34-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-668-3	7681-52-9	-	Skin Corr. 1B: H314; Aquatic Acute 1: H400; -: EUH031	1-10%

[cont...]

SAFETY DATA SHEET

2WORK THICK BLEACH

Page: 3

AMINES, C12-14(EVEN NUMBERED) ALKYL DIMETHYL, N-OXIDES - REACH registered number(s): 01-2119490061-47-XXXX

931-292-6	308062-28-4	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Acute 1: H400; Aquatic Chronic 2: H411	1-10%
-----------	-------------	---	---	-------

ALCOHOLS C12-C14, ETHOXYLATED, SULPHATED, SODIUM SALTS - REACH registered number(s): 01-2119488639-16-xxxx

-	68891-38-3	-	Eye Dam. 1: H318; Skin Irrit. 2: H315; Aquatic Chronic 3: H412	1-10%
---	------------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water.

[cont...]

SAFETY DATA SHEET

2WORK THICK BLEACH

Page: 4

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Polyethylene.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

2WORK THICK BLEACH

Page: 5

SODIUM HYPOCHLORITE SOLUTION...100% CL ACTIVE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1.5mg/m ³	-	-	-

DNEL/PNEC Values

Hazardous ingredients:

AMINES, C12-14(EVEN NUMBERED) ALKYL DIMETHYL, N-OXIDES

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	6.2,g/m ³	Workers	Systemic
DNEL	Dermal	11mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	1.53 mg/m ³	General Population	Systemic
DNEL	Dermal (repeated dose)	5.5 mg/kg bw/day	General Population	Systemic
DNEL	Oral (repeated dose)	0.44 mg/kg bw/day	General Population	Systemic
DNEL	Fresh water	0.0335 mg/l	-	-
PNEC	Microorganisms in sewage treatment	24 mg/L	-	-
PNEC	Marine water	0.00335mg/L	-	-
PNEC	Fresh water sediments	5.24mg/kg	-	-
PNEC	Marine sediments	0.524mg/kg	-	-
PNEC	Soil (agricultural)	1.02mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Hand protection: Impermeable gloves. Rubber gloves. Gloves (alkali-resistant).

Eye protection: Ensure eye bath is to hand. Safety glasses with side-shields.

Skin protection: Alkali resistant protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale yellow

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Viscous

Boiling point/range°C: 100

Melting point/range°C: 0

Flammability limits %: lower: Not applicable.

upper: Not applicable.

Flash point°C: Not applicable.

Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable.

[cont...]

SAFETY DATA SHEET

2WORK THICK BLEACH

Page: 6

Relative density: 1.05 - 1.15

VOC g/l: 0

Vapour pressure: Not applicable.

pH: 12.5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYPOCHLORITE SOLUTION...100% CL ACTIVE

ORL	RAT	LD50	750	mg/kg
-----	-----	------	-----	-------

AMINES, C12-14(EVEN NUMBERED) ALKYL DIMETHYL, N-OXIDES

DERMAL	RAT	LD50	>2000	ppmV
ORAL	RAT	LD50	1680 (est.)	mg/kg

ALCOHOLS C12-C14, ETHOXYLATED, SULPHATED, SODIUM SALTS

ORL	RAT	LD50	>2000	mg/kg
-----	-----	------	-------	-------

[cont...]

SAFETY DATA SHEET

2WORK THICK BLEACH

Page: 7

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM HYPOCHLORITE SOLUTION...100% CL ACTIVE

-	LC100	1	mg/l
---	-------	---	------

AMINES, C12-14(EVEN NUMBERED) ALKYL DIMETHYL, N-OXIDES

ALGAE	72H ErC50	0.146	mg/l
ALGAE	NOEC 28 days	0.067	mg/l
DAPHNIA	48H EC50	3.1	mg/l
DAPHNIA	NOEC 21 days	0.7	mg/l
FISH	96H LC50	2.67	mg/l
FISH	NOEC 302 days	0.42	mg/l

12.2. Persistence and degradability

Persistence and degradability: The surfactants contained in this preparation comply with the biodegradability criteria as laid down in regulation (EC) No.648/2004 on detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET

2WORK THICK BLEACH

Page: 8

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.
(SODIUM HYPOCHLORITE SOLUTION...5 % CL ACTIVE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations:

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

[cont...]

SAFETY DATA SHEET

2WORK THICK BLEACH

Page: 9

* indicates text in the SDS which has changed since the last revision.

5 LTR ; LIMITED QUANTITY FOR ADR

Phrases used in s.2 and s.3: EUH031: Contact with acids liberates toxic gas.

EUH206: Warning! Do not use together with other products. May release dangerous gases (chlorine).

H290: May be corrosive to metals.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.