



P/N	L/(M)	T/(MM)
26-0020MM	2	30
26-0030MM	3	45
26-0050MM	5	75
26-0100MM	10	150

PIN OUT

P1		P2	P1	P2
1	Red coax conductor	1	9	9
2	Green coax conductor	2	10	10
3	Blue coax conductor	3	11	11
4		4	12	12
5		5	13	13
6	Red coax drain	6	14	14
7	Green coax drain	7	15	15
8	Blue coax drain	8	shell	Drain shell

NOTES:

- 1:100% short,open and miss wire test.
- 2:Cable marking:CONNEKT GEAR AWM STYLE 2919 80°C 30V
LOW VOLTAGE Computer Cable RoHS & REACH Compliant

⑤	OUTER MOULDED	BLACK 45P PVC	0.048	KG
④	INNER MOULDED	LDPE	0.021	KG
③	SCREW	#4-40UNC 2.3*45.5MM,BLACK PVC	4	PCS
②	CONNECTOR	HDB 15PIN/MALE,BLUE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN,	2	PCS
①	CABLE	(1C*7/0.1BC+FPE+D+PVC)*3C+9C*7/0.10BC+AL+D+B,JACKET:BLACK PVC, OD:8.0±0.2MM	L	M
NO.	MATERIAL	DESCRIPTION	QTY.	UNIT

Ltemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference		
Designed by	Checked by	Approved by - date JUL 27.2015	File name	Date JUL 27.2015	Scale FREE
ANGLE:			VGA(3+9),HDB15M-HDB15M,30AWG,BLACK		
UNIT:MM			26-0020MM,26-0030MM 26-0050MM,26-0100MM	Edition 1	Sheet 1/1