

TECHNICAL SPECIFICATIONS

PIXMA PRO-200

Print Head / Ink Type	Permanent	Photo Paper Plus Glossy II (PP-201)	L/KG(4"x6")/Hagaki/Square(127 mm) = 20 LTR/A3/A4/2L/8"x10" = 10 A3+ = 1
Number of Nozzles	Total 6,144 nozzles (Y/M/C/PC/PM/Gy/Bk/LGY each 768 nozzles x 8)	Photo Paper Glossy (GP-501)	L/KG(4"x6") = 20 LTR/A3/A4/2L = 10 A3+ = 1
Ink Tank	8-color = Y/M/C/PC/PM/Gy/LGy/BK	Photo Paper Pro Luster (LU-101)	LTR/A4/A3 = 10 A3+ = 1
Maximum Printing Resolution	4800 (horizontal) ¹ x 2400 (vertical) dpi	Photo Paper Plus Semi-gloss (SG-201)	L/KG(4"x6") = 20 LTR/A4/A3/5x7/2L/8"x10" = 10 10"x12"/A3+ = 1
Print Speed		Matte Photo Paper (MP-101)	L/KG(4"x6") = 20 LTR/A4/A3 = 10 A3+ = 1
Photo (11"x14" image on A3+ with Border)²		High Resolution Paper (HR-101N)	LTR/A4/B5 = 80 B4 = 50 A3 = 20 A3+ = 1
Color/PT-101	approx.1 m 30s	T-Shirt Transfer	A4 = 1
Black/PT-101	approx.2 m 55s	Photo Stickers (PS-101)	PS-101/PS-201/PSHRS = 1
Maximum Printable Paper Size		Hagaki	20
Top Tray (width)	Top Tray: 322.2 mm (12.7 inch), Borderless Printing : 329 mm (A3+)(13 inch)	Lightweight Photo Paper	LTR/A4/A3/A3+/LDR/210x 594 mm = 1
Manual Feed (width)	Manual Feed: 322.2mm (12.7 inch), Borderless Printing: 329 mm (13 inch)	Japanese Paper Washi Canvas	LTR/A4/A3/A3+/LDR/210x 594 mm = 1
Custom (length) Printable Area	990.60mm (bordered)	Red Label Superior 80 g/m2(WOP111)	LTR/A4/A3/A3+/LDR/210x 594 mm = 1
Borderless Printing	Top/Bottom/Right/Left margin: each 0 mm	Canon Oce Office Colour Paper 80 g/m2(SAT213)	A4 = 80
Bordered Printing	Top margin: 3 mm, Bottom margin: 5 mm / Left/Right margin: each 3.4 mm (LTR/LGL: Left: 6.4 mm, Right: 6.3 mm) Recommended Top/Bottom/Right/Left margin for Fine Art Paper: each 25 mm	Heavyweight Fine Art Paper	LTR/A4/A3/A3+/LDR/210x594 mm = 1
Support Media		Light Fabric Iron Transfers (LF-101)	LTR/A4/12x12 = 1
Top Tray	Plain Paper/ Photo Paper Pro Platinum (PT-101)/Photo Paper Plus Glossy II (PP-201) / Photo Paper Pro Luster (LU-101)/ Photo Paper Plus Semi-gloss (SG-201)/ Matte Photo Paper (MP-101)/ Photo Stickers (PS-101) / Hagaki/ Lightweight Photo Paper (BOX)/Japanese Paper Washi (BOX)/ Canvas (BOX)/ Red Label Superior 80 g/m2(WOP111)/ Canon Oce Office Colour Paper 80 g/m2(SAT213)/ Heavyweight Fine Art Paper(BOX)/ Inkjet Greeting Card/Cardstock/Photo Paper Plus Glossy II (PP-208) ,High Resolution Paper (HR-101N),Photo Paper Glossy (GP-501), Envelope,T-Shirt Transfer,Light Fabric Iron Transfers(LF-101),Dark Fabric Iron Transfers (DF 101)	Dark Fabric Iron Transfers (DF 101)	LTR/A4/12x12 = 1
Manual Feed	Photo Paper Pro Platinum (PT-101)/Photo Paper Plus Glossy II (PP-201) /Photo Paper Pro Luster (LU-101)/ Photo Paper Plus Semi-gloss (SG-201)/ Matte Photo Paper (MP-101)/ Lightweight Photo Paper (BOX)/ Heavyweight Photo Paper (BOX)/ Japanese Paper Washi (BOX)/ Canvas (BOX)/ Photo Paper Pro Premium Matte (PM-101) / Heavyweight Fine Art Paper (BOX)/ Extra Heavyweight Fine Art Paper (BOX)/Premium Fine Art Rough/Inkjet Greeting Card/Cardstock/Photo Paper Plus Glossy II (PP-208), Photo Paper Glossy (GP-501), Light Fabric Iron Transfers(LF-101), Dark Fabric Iron Transfers (DF 101) Printable Nail Sticker (NL-101) / Printable Disk	Envelopes(DL, COM10)	10
Multi-purpose Tray Paper Size		Inkjet Greeting Card Cardstock	LTR/A4/7"x10" = 1 LTR/A4/12"x12" = 1
Top Tray	A3+/A3/A4/A5/B4/B5/LTR/LGL/Ledger/Hagaki/7"x10"/12x12 L(3.5"x5")/KG(4"x6") /2L(5"x7")/8"x10"/10"x12"/ Square(127 mm) /210 x594 mm Custom size(width 89 mm - 329 mm, length 127 mm - 990.6 mm) Envelopes(DL, COM10)	Paper Handling (Manual Feed) (Maximum Number)	
Manual Feed	A3+/A3/A4/A5/B4/LTR/LGL/Ledger/12x12 8"x10"/10"x12"/210x594 mm Custom size (width 203.2 mm - 330.2 mm, length 254 mm - 990.6 mm) 120x120 mm	Photo Paper Pro Platinum (PT-101)	A3/A4/LTR/8"x10"/10"x12"/A3+ = 1
Multi-purpose Tray Paper Size (Borderless)	A3+/A3/A4/A5/LTR/Ledger/Hagaki/7x10/12x12/5x7/L(3.5"x5")/KG(4"x6")/2L(5"x7")/8"x10"/10"x12"/Square(127 mm)/210 x594 mm	Photo Paper Plus Glossy II (PP-201)	LTR/A4/A3/A3+ = 1
Paper Handling (Top Tray) (Maximum Number)		Photo Paper Pro Luster (LU-101)	LTR/A4/A3/A3+ = 1
Plain Paper	LTR/A4/A5/B5 = 100 B4/A3/LGL/LDR = 50	Photo Paper Glossy (GP-501)	LTR/A4/A3/A3+ = 1
Photo Paper Pro Platinum (PT-101)	L/KG(4"x6") = 20 LTR/A3/A4/2L/8"x10" = 10 10"x12"/A3+ = 1	Photo Paper Plus Semi-gloss (SG-201)	LTR/A4/A3/8"x10"/10"x12"/A3+ = 1
		Matte Photo Paper (MP-101)	LTR/A4/A3/A3+ = 1
		Lightweight Photo Paper	LTR/A4/A3/A3+/LDR/210x 594 mm = 1
		Heavyweight Photo Paper	LTR/A4/A3/A3+/LDR/210x 594 mm = 1
		Japanese Paper Washi Canvas	LTR/A4/A3/A3+/LDR/210x5 94mm = 1
		Photo Paper Pro Premium Matte (PM-101)	LTR/A4/A3/A3+ = 1
		Heavyweight Fine Art Paper	LTR/A4/A3/A3+/LDR/210x 594 mm = 1
		Extra Heavyweight Fine Art Paper	LTR/A4/A3/A3+/LDR/210x 594 mm = 1
		Premium Fine Art Rough (FA-RG1)	LTR/A4/A3/A3+ = 1
		Light Fabric Iron Transfers (LF-101)	LTR/A4/12x12 = 1
		Dark Fabric Iron Transfers (DF 101)	LTR/A4/12x12 = 1
		Inkjet Greeting Card Cardstock	LTR/A4/7"x10" = 1 LTR/A4/12"x12" = 1
		Paper Handling (Multi-purpose Tray) (Maximum Number)	1 (Multi-purpose Tray)
		Paper Weight	
		Top Tray	Plain Paper: 64-105 g/m ² Canon Genuine paper (maximum): approx. 380 g/m
		Manual Feed	Canon Genuine paper (maximum): approx. 380 g/m, or Paper Thickness 0.1 ~0.6 mm or less
		Ink End Sensor	Dot count
		Print Head Alignment	Auto/Manual



TECHNICAL SPECIFICATIONS

PIXMA PRO-200

N/W			
Protocol		SNMP/HTTP/TCP/IP(IPv4/IPv6)	
Wired LAN			
Network Type		IEEE 802.3 10base-T IEEE 802.3u 100base-TX	
Data Rate		10Mbps/100Mbps(Auto switching)	
Security		IEEE 802.1x(EAP-TLS/EAP-TTLS/PEAP)	
Wireless LAN			
Network Type		IEEE802.11n/IEEE802.11g/IEEE802.11b IEEE802.11a	
Frequency Band		2.4GHz / 5GHz	
Channel⁵		2.4GHz: 1-13 (US*: 1-11) 5GHz: W52/W53/W56/W58 *Infrastructure mode and direct mode cannot be used simultaneously in the 5 GHz band. *Direct mode cannot use the 5 GHz band.	
Range		Indoor 50 m ※depends on the transmission speed and conditions	
Security		WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)	
Direct connection (Wireless LAN)		Available	
PRINTING SOLUTIONS			
Canon PRINT Inkjet/SELPHY (for iOS/Android)		Available	
Layout			
1-up(bordered/borderless⁴)		A4,Letter,A3,A3+,11"x17",Ledger,L,KG(4"x6"),2L(5"x7"),Square (127"x127"),7"x10",8"x10",Hagaki	
1-up(bordered only)		B5,A5,Legal,B4	
AirPrint		Available	
Layout			
1-up(bordered/borderless⁴)		A4,Letter,A3,A3+,11"x17",Ledger,L,KG(4"x6"),2L(5"x7"),Square (127"x127"),7"x10",8"x10",10"x12",12"x12",210x594,Hagaki	
1-up(bordered only)		B5,A5,Legal,B4,Envelopes(DL,COM10),Disk,Custom paper size	
Print Quality⁵		Draft/Standard/High	
Mopria⁶		Available	
Layout			
1-up(bordered/borderless⁴)		A4,Letter,A3,A3+,11"x17",Ledger,L,KG(4"x6"),2L(5"x7"),Square (127"x127"),7"x10",8"x10",10"x12",10x12),12x12,210x594,Hagaki	
1-up(bordered only)		B5,A5,Legal,B4,Envelopes(DL,COM10),Disk,Custom paper size	
Print Quality⁵		Draft/Standard/High	
Canon Print Service (for Android)		Available	
Windows 10 Mobile		Available	
PIXMA Cloud Link			
From smartphone or tablet		Available	
Camera Direct Spec.			
Media size		LTR/A4/L/2L(5"x7")/KG (4"x6"/8"x10"/10"x12"/A3/A3+/Square (127"x127"))/Hagaki	
Compatible Digital Camera		"PictBridge" compliant digital cameras, camcorders and camera phones	
Connecting type		WLAN	
File Format		JPEG (Exif ver.2.2/2.21/2.3 compliant) ⁷ ,PNG	
Layout⁸			
1-up(borderless⁴)		Available	
1-up(bordered⁴)		Available	
Photo Index		Available	
Print with shooting information		Available	
20-up print with shooting information		Available	
35-up contact print		Available	
Disc Label		Available ¹⁰	
File number & date print		Available ¹¹	
			GENERAL SPECIFICATIONS
			Operation Panel
			Display
			3.0 inch/7.5cm LCD(Display Panel, Color)
			Language
			33 Languages Selectable: Japanese/English(mm & inch)/German/French/Italian/Spanish/Dutch/Portuguese/Norwegian/Swedish/Danish/Finnish/Russian/Czech/Hungarian/Polish/Slovene/Turkish/Greek/Simplified Chinese/Traditional Chinese/Korean/Indonesian/Slovakian/Estonian/Latvian/Lithuanian/Ukrainian/Romanian/Bulgarian/Thai/Croatian/Vietnamese
			Interface
			USB B Port
			Hi-Speed USB
			PictBridge
			Available
			Wireless LAN
			Temperature: 5~35 °C Humidity: 10~90 %RH (no dew condensation)
			Operating Environment¹²
			Temperature: 15~30 °C Humidity: 10~80 %RH (no dew condensation)
			Recommended Environment¹³
			Temperature: 0~40 °C Humidity: 5~95 %RH (no dew condensation)
			Storage Environment
			Available
			Quiet Mode
			Acoustic Noise (PC Print)
			Plain Paper(A4, Color)¹⁴
			Approx. 42.5db
			Photo Paper Pro Platinum (PT-101) (L,Color,borderless)
			Approx. 42.5db
			Photo Paper Pro Platinum (PT-101) (4x6,Color,borderless)
			Approx. 42.2db
			Power
			AC 100-240 V 50/60 Hz
			Power Consumption
			Standby (scanning lamp is off)
			Approx 1.0W
			USB connection to PC OFF
			Approx. 0.2W
			Printing USB connection to PC
			approx 1.6W
			Standby (all ports connected, scanning lamp is off)
			approx. 2.5W
			<EU only - for ErP Lot 26 regulation>
			Time to enter Standby mode <EU only - for ErP Lot 26 regulation>
			approx. 3 min
			Environment Regulation
			RoHS (EU, China)*, WEEE (EU)* *To be fixed
			Eco-Label
			Energy Star* *To be fixed (except for EUR)
			Dimension(WxDxH)
			Factory configuration
			mm
			approx. 639 x 379 x 200 mm
			inch
			approx. 25.2 x 15 x 7.9 inch
			Output/ADF trays extended
			mm
			approx. 639 x 837 x 416 mm
			inch
			approx. 25.2 x 33 x 16.4 inch
			Weight
			kg
			approx. 14.1kg
			lb
			approx. 32lb



TECHNICAL SPECIFICATIONS

PIXMA PRO-200

Footnotes: -

- ^[1] Ink droplets can be placed with a pitch of 1/4800 inch at minimum.
- ^[2] Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- ^[3] 1-1-1 in US, CND, LTN, BRA, TW and HK.
- ^[4] The amount of image extension beyond the paper cannot be adjusted.
- ^[5] Resolution may be changed between Direct print and printing from PC.
- ^[6] They are list of papers which the printer is capable of. The paper type printable from Mopria depends on the Mopria's capability.
- ^[7] Image data taken by DCF (Ver. 1.0/2.0) -compliant digital cameras, camcorders or camera phones and recorded in JPEG (Exif-compliant) format.
- ^[8] Function depends on the connected digital cameras, camcorders or camera phones.
- ^[9] Plain paper is printed bordered automatically, regardless of the camera settings.
- ^[10] Not supported for 'Printable Printable Printable Nail Stickers'.
- ^[11] Non-support for 2/4/9/16-up in sticker printing as well as date/file number printing in disc label printing.
- ^[12] The performance of the printer may be reduced under certain temperature and humidity conditions.
- ^[13] For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.
- ^[14] Acoustic Noise is measured based on ISO7779 standard with default setting.



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2020