

# PRED CEDAR

## RPET15A



### Key information:

- Highly Dexterous 15g Grey/White Recycled Polyester Liner
- Contact Heat Level 1
- Breathable Back
- Elasticated, coloured cuff for size indication
- Black Nitrile Foam Palm Coating
- Fibre Composition, 64% rPET, 34% Nitrile, 2% Polyester

EN388:2016  
+ A1:2018



3131X

EN407:  
2020



X1XXXX

UK  
CA  
CE



|            |                                         |
|------------|-----------------------------------------|
| Code:      | RPET15A                                 |
| Liner:     | 15g Grey/White Recycled Polyester Liner |
| Size:      | 6 to 11                                 |
| Pack size: | 10 pairs                                |

|         |           |
|---------|-----------|
| Carton: | 120 pairs |
| EN388:  | 3131X     |
| EN407:  | X1XXXX    |



### Applications include:

General Handling, Warehousing, Packaging, Landscaping, Construction, Logistics

### Limitations of Use

|                    |                                                                                                                                                                    |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Maintenance</b> | Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.           |
| <b>Storage</b>     | Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.                                                                      |
| <b>Disposal</b>    | Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.                                                            |
| <b>Cleaning</b>    | Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.                             |
| <b>Durability</b>  | The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves. |
| <b>Note</b>        | Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.                                 |



## Hands Protected; Work Perfected

just1source.com | sales@just1source.com | 01653 617718

## PRODUCT INFORMATION SHEET

These items were imported by: -  
Just 1 Source & Supply Limited, Barton Hill, Whitwell, York. YO60 7JX  
Telephone: 01653 617718 - [www.just1source.com](http://www.just1source.com)

These items comply with the requirements of the EU Regulation 2016/425 & Regulation 2016/425 on personal protective equipment, as amended to apply in GB, in line with the harmonised and designated standard(s) referenced below.

**NOTE: -** Declarations of Conformity can be found at [www.just1source.com](http://www.just1source.com)

**Limitations of use:**

EN 388:2016 + A1:2018; EN407:2020; EN ISO 21420:2020 - The overall classification of gloves with two or more layers does not necessarily reflect the performance of the outermost layer. Gloves should not be worn when there is a risk of entanglement by moving parts or machinery.

Protection is limited to the hand area only.

The EN 388 test results shown below are taken from the palm area of the glove.

EN 388:2016 + A1:2018



**3131X**

EN407:2020



X1XXXX

EN ISO 21420:2020



| Test                         | Performance Level    | Test                | Performance Level    |
|------------------------------|----------------------|---------------------|----------------------|
| <b>EN 388:2016 + A1:2018</b> |                      | <b>EN407:2020</b>   |                      |
| Abrasion                     | <b>3 (Scale 1-4)</b> | Burning Behaviour   | <b>X (Scale 0-4)</b> |
| Blade Cut (Coup Test)        | <b>1 (Scale 1-5)</b> | Contact Heat        | <b>1 (Scale 0-4)</b> |
| Tear                         | <b>3 (Scale 1-4)</b> | Convective Heat     | <b>X (Scale 0-4)</b> |
| Puncture                     | <b>1 (Scale 1-4)</b> | Radiant Heat        | <b>X (Scale 0-4)</b> |
| ISO 13997 Cut (TDM)          | <b>X (Scale A-F)</b> | Small Molten Splash | <b>X (Scale 0-4)</b> |
| Impact Protection            | <b>(P if passed)</b> | Large Molten Splash | <b>X (Scale 0-4)</b> |

| ISO Cut Level | A  | B  | C   | D   | E   | F   |
|---------------|----|----|-----|-----|-----|-----|
| Newtons       | ≥2 | ≥5 | ≥10 | ≥15 | ≥22 | ≥30 |

Performance levels are measured where the highest number indicates the best protection. "X" indicates that the product has not been tested against this risk.

**Warning:** No flame protection is claimed

|                        |                                                                                             |                     |
|------------------------|---------------------------------------------------------------------------------------------|---------------------|
| Product Code: -        | <b>RPET15A</b>                                                                              | Size: <b>6 - 11</b> |
| Product Name: -        | <b>PRED Cedar</b>                                                                           |                     |
| Product Description: - | 15g Grey/White Recycled Polyester Liner (Recycler Post-Consumer); Nitrile Foam Palm Coating |                     |

Gloves providing protection against mechanical risks.

**Maintenance:** examine gloves for damage, splits and holes before each use. Always replace damaged gloves.

**Disposal** – Dispose of used gloves as instructed by your local authority.

**Warning** – This product is contact heat level 1 and not fit to remove items from the oven.

**STORAGE:** Store in dry ambient conditions

**AFTERCARE:** No Cleaning Treatment



EU Type Certification issued by **CTC**, 4 Rue  
Hermann Frenkel, 69367 LYON, Cedex 07,  
FRANCE – **Notified Body 0075**



UK Type Certification issued by **ITS Testing Services (UK) Ltd**, Centre Court, Meridian Business Park, Leicester. LE19 1WD – **Approved Body AB 0362**