



## APC Back-UPS BE850G2-UK - 8x BS 1363 outlets, 850VA, 2 USB chargers, 1 USB data port

Brand : APC

Product code: BE850G2-UK

Product name : APC Back-UPS BE850G2-UK - 8x BS 1363 outlets, 850VA, 2 USB chargers, 1 USB data port


APC Back-UPS BE850G2-UK - 8x BS 1363 outlets, 850VA, 2 USB chargers, 1 USB data port  
APC Back-UPS BE850G2-UK - 8x BS 1363 outlets, 850VA, 2 USB chargers, 1 USB data port. UPS topology: Standby (Offline), Output power capacity: 0.85 kVA, Output power: 520 W. USB port type: USB Type-C. Battery life (max): 5 year(s), Battery recharge time: 16 h. Form factor: Compact, Product colour: Black, Cable length: 1.83 m. Compliance certificates: RoHS, Certification: CE, EAC



Features		Design	
UPS topology *	Standby (Offline)	Form factor *	Compact
Output power capacity *	0.85 kVA	Cable length	1.83 m
Output power *	520 W	Product colour *	Black
Waveform *	Sine	LED indicators	✓
Input operation voltage (min) *	180 V	<b>Operational conditions</b>	
Input operation voltage (max) *	266 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	47/63 Hz	Storage temperature (T-T)	-15 - 45 °C
Output operation voltage (min)	220 V	Operating relative humidity (H-H)	0 - 90%
Output operation voltage (max)	230 V	Storage relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Non-operating altitude	0 - 4500 m
Maximum current	6 A	<b>Certificates</b>	
Surge energy rating	310 J	Compliance certificates	RoHS
Efficiency	80%	Certification	CE, EAC
Noise level	45 dB	<b>Packaging content</b>	
Surge protection	✓	Manual	✓
Surge protection features	Digital Subscriber Line (DSL)	<b>Weight &amp; dimensions</b>	
Audible alarm(s)	✓	Width	130 mm
Audible alarm modes	Alarm when on battery, Overload alarm	Depth	365 mm
<b>Ports &amp; interfaces</b>		Height	120 mm
USB port	✓	Weight	4.5 kg
USB port type	USB Type-C	<b>Packaging data</b>	
Ethernet LAN (RJ-45) ports	1	Package width	186 mm
<b>Battery</b>		Package depth	441 mm
Battery life (max)	5 year(s)	Package height	190 mm
Battery recharge time	16 h	Package weight	5 kg
Hot-swap battery	✓	<b>Logistics data</b>	
Automatic battery test	✓	Harmonized System (HS) code	85078000
Cold start	✓	Master (outer) case gross weight	16 kg



0731304347323



731304347323

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.