

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 1287483, 1287799, 1983830 (Dokumental MA 4500 blue)
- **Registration number**
The ingredients of this ink meet the criteria of the Regulation 1907/2006/EC (REACH).
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Currently no such applications are identified.
- **Application of the substance / the mixture** alcohol based permanent marking ink
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Staples Europe B.V.
PO Box 23456
1100 DZ Amsterdam
The Netherlands
00800 5000 3000
www.staples.eu
reach@staples-solutions.com
- **Further information obtainable from:**
Manufacturer of the Ink:
msds@dokumental.de
- **1.4 Emergency telephone number:**
Applicable only for the Ink
Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.
999 - National Emergency Number
+44 (0)344 892 0111
National Poison Information Service
Intended for use by medical professionals only.

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS05



GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
propan-1-ol
C.I. Solvent Blue 4 < 0,1% Michler's Ketone
Phosphoric acid mono-bis-(2-ethylhexyl)-ester
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.

Trade name: 1287483, 1287799, 1983830 (Dokumental MA 4500 blue)

(Contd. of page 1)

H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).
P362+P364 Take off contaminated clothing and wash it before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 71-23-8 EINECS: 200-746-9 Reg.nr.: 01-2119486761-29	propan-1-ol Flam. Liq. 2, H225; Eye Dam. 1, H318; STOT SE 3, H336	50-100%
CAS: 12645-31-7 EINECS: 235-741-0 Reg.nr.: 01-2119896587-13	Phosphoric acid mono-bis-(2-ethylhexyl)-ester Skin Corr. 1B, H314	2.5-10%
CAS: 68411-04-1 EINECS: 270-096-9 Reg.nr.: 01-2119979101-41	C.I. Solvent Blue 51 Aquatic Chronic 3, H412	≤2.5%
CAS: 6786-83-0 EINECS: 229-851-8 Reg.nr.: 01-2119950688-22	C.I. Solvent Blue 4 < 0,1% Michler's Ketone Eye Dam. 1, H318; Skin Sens. 1B, H317	≤2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

After inhalation:

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:** If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture** No further relevant information available.

5.3 Advice for firefighters

Protective equipment: No special measures required.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

6.2 Environmental precautions:

Dilute with plenty of water.

(Contd. on page 3)

Trade name: 1287483, 1287799, 1983830 (Dokumental MA 4500 blue)

(Contd. of page 2)

- Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
- Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- If only a short-term loading of the glove material by splashes is expected, tricoted gloves with higher wearability for the better acceptance of the users are recommended.
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Nitrile rubber, NBR
 - **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Trade name: 1287483, 1287799, 1983830 (Dokumental MA 4500 blue)

(Contd. of page 3)

· **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Fluid

Colour:

According to product specification

· **Odour:**

Product specific

· **Odour threshold:**

Not determined.

· **Important information on protection of health and environment, and on safety.**

-

-

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range:

96.5-97.5 °C

· **Flash point:**

22 °C

· **Flammability (solid, gas):**

Not applicable.

· **Ignition temperature:**

360 °C

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower:

2.1 Vol %

Upper:

13.5 Vol %

· **Vapour pressure at 20 °C:**

19 hPa

· **Density at 20 °C:**

0.8 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with water:**

Fully miscible.

· **Partition coefficient: n-octanol/water:**

Not determined.

· **Viscosity:**

Dynamic at 20 °C:

3.5 mPas

Kinematic:

Not determined.

· **Solvent content:**

Organic solvents:

87.9 %

Solids content:

8.1 %

· **9.2 Other information**

The physical and chemical properties given in Section 9.1 are rough data only, which are partially derived from the component's data of the mixture. These data are no binding product specifications.

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 5)

Trade name: 1287483, 1287799, 1983830 (Dokumental MA 4500 blue)

(Contd. of page 4)

- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

71-23-8 propan-1-ol

Oral	LD50	8,000 mg/kg (rat)
Dermal	LD50	4,000 mg/kg (rab)
Inhalative	LC50/4 h	33.8 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation
Causes skin irritation.
- Serious eye damage/irritation
Causes serious eye damage.
- Respiratory or skin sensitisation
May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

6786-83-0 C.I. Solvent Blue 4 < 0,1% Michler's Ketone

EC50 / 48h 0.025 mg/l (Daphnie)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 13*	sludges from paint or varnish containing organic solvents or other hazardous substances

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.



SECTION 14: Transport information

- 14.1 UN-Number
ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name
ADR 1263 PAINT

(Contd. on page 6)

Trade name: 1287483, 1287799, 1983830 (Dokumental MA 4500 blue)

(Contd. of page 5)

· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	3 (F1) Flammable liquids.
· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - Named dangerous substances - ANNEX I None of the ingredients is listed.
 - Seveso category P5c FLAMMABLE LIQUIDS
 - Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
 - Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
 - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
 - National regulations:
 - Technical instructions (air):
- | Class | Share in % |
|-------|------------|
| NK | 50-100 |
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
 - 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H225 Highly flammable liquid and vapour.

(Contd. on page 7)

Trade name: 1287483, 1287799, 1983830 (Dokumental MA 4500 blue)

(Contd. of page 6)

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

• *** Data compared to the previous version altered.**