

COLOURSAFE

PRED SAPPHIRE

PRED13



Key information:

- 13 Gauge Seamless HPPE, Steel, Polyester & Spandex Liner
- High quality Polyurethane (PU) palm coating
- Maximum Cut Level F Protection
- Lightweight, comfortable and dexterous
- Also available in vend ready packaging
- Breathable back
- Elasticated, coloured cuff for size indication

EN388:2016
+ A1:2018



UK
CA
CE



Code:	PRED13	Coating:	Polyurethane (PU)
Liner:	HPPE, Steel, Polyester & Spandex	Pack size:	10 pairs
Size:	7-11	Carton:	120 pairs
Gauge:	13	EN388:2016 + A1:2018	4X43F

Applications include:

Automotive, Component Handling, Construction, Engineering, Fabrication, Sheet Metal Manufacturing

Limitations of Use

Maintenance	Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.
Storage	Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.
Disposal	Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.
Cleaning	Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.
Durability	The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.
Note	Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.



Hands Protected; Work Perfected

just1source.com | sales@just1source.com | 01653 617718

PRODUCT INFORMATION SHEET

These items were imported by: -
Just 1 Source & Supply Limited, Barton Hill, Whitwell, York. YO60 7JX
Telephone: 01653 617718 - www.just1source.com

These items comply with the requirements of the EU Regulation 2016/425 & Regulation 2016/425 on personal protective equipment, as amended to apply in GB, in line with the harmonised and designated standard(s) referenced below.

NOTE: - Declarations of Conformity can be found at www.just1source.com

Limitations of use:

EN 388:2016 + A1:2018, EN ISO 21420:2020 - The overall classification of gloves with two or more layers does not necessarily reflect the performance of the outermost layer. Gloves should not be worn when there is a risk of entanglement by moving parts or machinery.

The EN 388 test results shown below are taken from the palm area of the glove.

EN 388:2016 + A1:2018



4X43F

EN ISO 21420:2020



Test	Performance Level
EN 388:2016 + A1:2018	
Abrasion	4 (Scale 1-4)
Blade Cut (Coup Test)	X (Scale 1-5)
Tear	4 (Scale 1-4)
Puncture	3 (Scale 1-4)
ISO 13997 Cut (TDM)	F (Scale A-F)
Impact Protection	(P if passed)

ISO Cut Level	A	B	C	D	E	F
Newtons	≥2	≥5	≥10	≥15	≥22	≥30

Performance levels are measured where the highest number indicates the best protection. "X" indicates that the product has not been tested against this risk.

Product Code: - **PRED 13** Size: **7 - 11**
 Product Name: - **PRED Sapphire**
 Product Description: - HPPE/Steel/Polyester/Spandex Liner; PU Palm Coated Cut Resistant Glove – Level F

Gloves providing protection against mechanical risks.

Maintenance: examine gloves for damages, splits and holes before each use. Always replace damaged gloves.

Disposal – Dispose of used gloves as instructed by your local authority.

STORAGE: Store in dry ambient conditions

AFTERCARE: No Cleaning Treatment



EU Type Certification issued by **Intertek Italia Spa**,
Via Guido Miglioli,2/A - 20063 Cernusco sul Naliglio
(MI) Italia – **Notified Body 2575**



UK Type Certification issued by **ITS Testing Services (UK) Ltd**, Centre Court, Meridian Business Park, Leicester. LE19 1WD – **Approved Body AB 0362**