

Page: 1

Compilation date: 01/08/2008

Revision date: 11/05/2015

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: 2WORK FLOOR STRIPPER

Product code: 2W04498

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: VOW EUROPE LTD **K HOUSE EUROPA LINK** SHEFFIELD BUSINESS PARK SHEFFIELD S9 1XU

Tel: 0844 980 8000

Email: WWW.VOWEUROPE.COM

#### 1.4. Emergency telephone number

Emergency tel: NHS Direct 08454647

NHS24 0845242424

ROI 018092166

(office hours only)

# Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314; STOT SE 3: H335

Most important adverse effects: Causes severe skin burns and eye damage. May cause respiratory irritation.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation.

Signal words: Danger

#### 2WORK FLOOR STRIPPER

Hazard pictograms: GHS05: Corrosion GHS07: Exclamation mark Precautionary statements: P102: Keep out of reach of children. P282: Wear eye protection. P280: Wear protective gloves. P260: Do not breathe dust/fumes/gas/mist/vapours/spray. P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. P332+313: If skin irritation occurs: Get medical attention. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313: If eye irritation persists: Get medical attention. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P314: Get medical attention if you feel unwell. P362: Take off contaminated clothing and wash before reuse.

#### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

#### 3.2. Mixtures

#### Hazardous ingredients:

#### 3 - BUTOXYPROPAN - 2 - OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
225-878-4	005131-66-8	-	Skin Irrit. 2: H315; Eye Irrit. 2: H319	10-30%

#### 2-AMINOETHANOL

205-483-3	141-43-5	-	Acute Tox. 4: H332; Acute Tox. 4: H312;	1-10%
			Acute Tox. 4: H302; Skin Corr. 1B: H314	

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

- Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash
  - immediately with plenty of soap and water.
- **Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
  - **Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

[cont...]

Page: 2

### 2WORK FLOOR STRIPPER

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

#### 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

## 5.1. Extinguishing media

#### Extinguishing media: Water.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

## Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel.

Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn

leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Neutralise with dilute hydrochloric acid.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

# Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

## 2WORK FLOOR STRIPPER

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Polyethylene.

## 7.3. Specific end use(s)

Specific end use(s): No data available.

## Section 8: Exposure controls/personal protection

## 8.1. Control parameters

## Hazardous ingredients:

#### 2-AMINOETHANOL

#### Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	7.6 mg/m3	15 mg/m3	-	-

**Respirable dust** 

## **DNEL/PNEC** Values

DNEL / PNEC No data available.

## 8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Gas/vapour filter, type K: ammonia and derivatives (EN141).
Hand protection: Gloves (alkali-resistant). Viton gloves.	
Eye protection:	Tightly fitting safety goggles. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

#### Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State:	Liquid	
Colour:	Pale yellow	
Odour:	Characteristic odour	
Evaporation rate:	Moderate	
Oxidising:	Non-oxidising (by EC criteria)	
Solubility in water:	Soluble	
Viscosity:	Non-viscous	
Boiling point/range°C:	100 Melting point/range	C: 0
Flammability limits %: lower:	Not applicable. upp	r: Not applicable.
Flash point°C:	Not applicable. Part.coeff. n-octanol/wat	r: Not applicable.
Autoflammability°C:	Not applicable. Vapour pressu	e: Not applicable.
Relative density:	1.0 - 1.05 p	<b>H:</b> 11.6
VOC g/l:	160	

[cont...]

## 2WORK FLOOR STRIPPER

Page: 5

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

#### Section 11: Toxicological information

#### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### 3 - BUTOXYPROPAN - 2 - OL

ORAL RAT LD50 2700 mg/kg
--------------------------

#### 2-AMINOETHANOL

IVN	RAT	LD50	225	mg/kg
ORL	MUS	LD50	700	mg/kg
ORL	RAT	LD50	1720	mg/kg
SCU	RAT	LD50	1500	mg/kg

#### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

## Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain.

The vision may become blurred. May cause permanent damage.

#### 2WORK FLOOR STRIPPER

Page: 6

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

#### Section 12: Ecological information

12.1. Toxicity

## Hazardous ingredients:

#### 3 - BUTOXYPROPAN - 2 - OL

-	48H EC50	>1000	mg/l
GUPPIES	96H LC50	560-1000	mg/l

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable. The surfactants contained in this preperation comply with the biodegradability

```
criteria as laid down in regulation (EC) No.648/2004 on detergents.
```

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

#### 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

#### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal of packaging: Dispose of as normal industrial waste.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

Transport class: This product does not require a classification for transport.

## Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by

the supplier.

# 2WORK FLOOR STRIPPER

Page: 7

# Section 16: Other information

Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	
	453/2010.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.	
	H312: Harmful in contact with skin.	
	H314: Causes severe skin burns and eye damage.	
	H315: Causes skin irritation.	
	H319: Causes serious eye irritation.	
	H332: Harmful if inhaled.	
	H335: May cause respiratory irritation.	
Legend to abbreviations:	PNEC = predicted no effect concentration	
	DNEL = derived no effect level	
	LD50 = median lethal dose	
	LC50 = median lethal concentration	
	EC50 = median effective concentration	
	IC50 = median inhibitory concentration	
	dw = dry weight	
	bw = body weight	
	cc = closed cup	
	oc = open cup	
	MUS = mouse	
	GPG = guinea pig	
	RBT = rabbit	
	HAM = hamster	
	HMN = human	
	MAM = mammal	
	PGN = pigeon	
	IVN = intravenous	
	SCU = subcutaneous	
	SKN = skin	
	DRM = dermal	
	OCC = ocular/corneal	
	OPT = optical	
	INH = inhalation	
l angl disalaiman	PCP = physico-chemical properties	
Leyal uisciaiiner:	The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage result	
	shall be used only as a guide. This company shall not be held liable for any damage result	
	from handling or from contact with the above product.	[final page]