

**Multi-functional paper**

**Steinbeis No. 3**  
**Multi-functional paper for laser and inkjet printers, 80 gsm**

**Product description**

Steinbeis No. 3 is 100 % recycled. Processed without any environmental harmful bleaching agents (chlorine, chlorine-dioxide or other halogenated bleaching agents) the paper is certified to Blue Angel and EU-Ecolabel. Paper can be recycled after using.

**Target values**

<b>Grammage</b>	gsm	80 ± 3.2	ISO 536
<b>Caliper</b>	µm	100 ± 6	ISO 534
<b>Brightness</b>	%	90.0 ± 2.5	ISO 2470-2
<b>Whiteness</b>	CIE	110.0 ± 2.5	ISO 11475
<b>Opacity</b>	%	> 94	ISO 2471
<b>Roughness</b>	ml/min	300 ± 100	ISO 8791-2

**Application**

Steinbeis No. 3 can be used for all current laser and inkjet printing applications. Manufactured from 100 % recovered waste and using unique technologically advanced processes in an integrated pulp and paper mill.

**Safety, health and the Environment**

**Environmental performance**



PCF (processed chlorine free)  
 Resistance to ageing: DIN 6738, LDK 24-85 and ISO 20494  
 Runnability complies with: DIN EN 12281

**Mill certification:**  
 ISO 9001 (Quality-Management)  
 ISO 14001 (Environmental-Management)  
 ISO 50001 (Energy-Management)  
 ISO 45001 (Occupational Safety)  
 EMAS (European Management and Audit Scheme)

**Product range**

DIN A4, DIN A3, Reel

**Markings packaging**  
 (in accordance with 97/129/EG)

Boxes: corrugated cardboard	PAP 20
Wooden pallets:	FOR 50
Polyethylene stretch film :	LDPE 4
Strapping:	PP 5
Ream wrap:	C/PAP 81

**Storage Recommendation**

Avoid storage under of extreme temperatures and atmospheric humidity:  
 Room temperature: min. 10 °C to max. 30 °C  
 Relative atmospheric humidity (RH): min. 30 % RH to max. 70 % RH

**Printing Recommendation**

Favourable printing conditions:  
 Room temperature: min: 18 °C to max. 24 °C  
 Relative atmospheric humidity: min: 40 % RH to max. 60 % RH.