

TOUCHSAFE

PRED SIGMA SN13DTQ



Key information:

- 13g Green Ultra High Molecular Weight Polyethylene/Spandex Liner
- Robust sandy nitrile palm coating
- Cut Level D
- Contact Heat Level 1
- Additional Thumb Crotch Protection
- Header Carded product
- Touchscreen Capability

EN388:2016
+ A1:2018



4X42D

EN407:2020



X1XXXX

UK
CA
CE



Code: SN13DTQ

Carton: 120 Pairs

Liner: UHMWPE/
Spandex

EN388:2016
+ A1:2018 4X42D

Size: 6 to 11

EN407:2020 X1XXXX

Gauge: 13

Coating: Sandy Nitrile

Applications include:

Agriculture, Construction, Cut Risk Areas, Engineering, Glass Handling, Metal Handling

Limitations of Use

Maintenance	Examine gloves for damages, splits and holes before each use. Always replace damaged gloves. Only properly fitting gloves guarantee protection and grip.
Storage	Store at normal room temperature in a dry, well ventilated area. Avoid direct heat radiation.
Disposal	Used gloves can be contaminated. Dispose with household waste or as instructed by your local authority.
Cleaning	Do not wash. The performance of the product after laundering is unknown. Beat or brush out after each use, depending on level of dirt.
Durability	The period of use depends on the degree or intensity of use in the retrospective application. It is therefore not possible to provide a 'life span' of the gloves.
Note	Due to the nature of this product the user is advised to carry out their own risk assessment before use, depending on application.



Hands Protected; Work Perfected

just1source.com | sales@just1source.com | 01653 617718

PRODUCT INFORMATION SHEET

These items were imported by: -
Just 1 Source & Supply Limited, Barton Hill, Whitwell, York. YO60 7JX
Telephone: 01653 617718 - www.just1source.com

These items comply with the requirements of the EU Regulation 2016/425 & Regulation 2016/425 on personal protective equipment, as amended to apply in GB, in line with the harmonised and designated standard(s) referenced below.

NOTE: - Declarations of Conformity can be found at www.just1source.com

Limitations of use:

EN 388:2016 + A1:2018; EN407:2020; EN ISO 21420:2020 - The overall classification of gloves with two or more layers does not necessarily reflect the performance of the outermost layer. Gloves should not be worn when there is a risk of entanglement by moving parts or machinery.

The EN 388 test results shown below are taken from the palm area of the glove.

EN 388:2016 + A1:2018



4X42D

EN407:2020



X1XXXX

EN ISO 21420:2020



Test	Performance Level	Test	Performance Level
EN 388:2016 + A1:2018		EN407:2020	
Abrasion	4 (Scale 1-4)	Burning Behaviour	X (Scale 0-4)
Blade Cut (Coup Test)	X (Scale 1-5)	Contact Heat	1 (Scale 0-4)
Tear	4 (Scale 1-4)	Convective Heat	X (Scale 0-4)
Puncture	2 (Scale 1-4)	Radiant Heat	X (Scale 0-4)
ISO 13997 Cut (TDM)	D (Scale A-F)	Small Molten Splash	X (Scale 0-4)
Impact Protection	(P if passed)	Large Molten Splash	X (Scale 0-4)

ISO Cut Level	A	B	C	D	E	F
Newtons	≥2	≥5	≥10	≥15	≥22	≥30

Performance levels are measured where the highest number indicates the best protection. "X" indicates that the product has not been tested against this risk.

Product Code: -	SN13DTQ	Size: 6 - 11
Product Name: -	PRED Sigma	
Product Description: -	13g Green UHMWPE/Spandex Liner; Cut Level D; with Thumb Crotch Protection, Touchscreen Capability; Sandy Nitrile Palm Coating	

Gloves providing protection against mechanical risks.

Maintenance: examine gloves for damages, splits, and holes before each use. Always replace damaged gloves.

Disposal – Dispose of used gloves as instructed by your local authority.

STORAGE: Store in dry ambient conditions	AFTERCARE: No Cleaning Treatment
--	----------------------------------



EU Type Certification issued by **CTC**, 4 Rue
Hermann Frenkel, 69367 LYON, Cedex 07,
FRANCE – **Notified Body 0075**



UK Type Certification issued by **SATRA Technology Centre**, Wyndham Way, Telford Way, Kettering. NN16 8SD – **Approved Body AB 0321**