Sony BRC-X1000 Dome IP security camera Indoor 3840 x 2160 pixels Ceiling/Floor

Brand : Sony Product code: BRC-X1000/W

Product name: BRC-X1000

- Excellent low light sensitivity
- Flexible installation
- Cinematic 24p pictures
- 1" Exmor R CMOS, 14.2 MP, 2160p, PTZ, RS-422, 3G-SDI, HDMI

Sony BRC-X1000. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling/Floor, Product colour: White, Form factor: Dome. Minimum illumination: 1.7 lx, Lens viewing angle, horizontal: 64.6°, Tilt angle range: -30 - 90°. Sensor type: CMOS. Optical zoom: 12x, Focal length range: 9.3 - 111.6 mm

Performance		Video	
Type * Placement supported * Connectivity technology * PTZ control Day/night mode Antenna gain level (max) Light exposure modes Design	IP security camera Indoor Wired	Maximum resolution * Total megapixels * Supported graphics resolutions Supported video modes Frame rate Gain control type Automatic gain control	3840 x 2160 pixels 20.4 MP 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 3840 x 2160 720p, 1080i, 1080p, 2160p 60 fps Auto/Manual
Form factor *	Dome	Full HD	*
Mounting type *	Ceiling/Floor	Network	
Product colour * Camera	White	Ethernet LAN * Networking standards Wi-Fi *	✓ IEEE 802.3at ×
Camera pan control	✓	Storage	
Camera tilt control	~	Built-in HDD *	
Minimum illumination Lens viewing angle, horizontal	1.7 lx 64.6°		×
Tilt angle range	-30 - 90°	Ports & interfaces	_
Tilt speed	60 °/sec	Ethernet LAN (RJ-45) ports	1 1
Pan range	-170 - 170°	HDMI ports quantity DC-in jack	1 ✓
Pan speed	60 °/sec	,	•
Auto flip	✓	Power	
White balance	Auto, Indoor, Manual, Outdoor	Power source type * DC output current	PoE 13.2 A
Camera shutter speed	1/10000s - 1/8 (59.94/29.97), 1/10000s - 1/6 (50/25)	·	13.2 A
Image sensor		Operational conditions	
Number of sensors	1	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Sensor type *	CMOS		-20 - 00 C
Lens system		Weight & dimensions Width	198 mm
Zoom capability	✓	Depth	198 mm 238 mm
Optical zoom	12x	Height	260 mm
Focal length range	9.3 - 111.6 mm	Weight	4.3 kg
Auto focus	✓	Packaging content	
Maximum aperture number	4.5	Number of cameras *	1



5013493418325

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.