APC

APC Smart-UPS On-Line, 1500VA, Rackmount 2U, 230V, 8x C13 IEC outlets, Network Card, W/ rail kit, Used W/O Lithium-ion external battery

Brand : APC

Product code: SRT1500UXI-NCLI

Product name : Smart-UPS On-Line, 1500VA, Rackmount 2U, 230V, 8x C13 IEC outlets, Network Card, W/ rail kit, Used W/O Lithium-ion external battery

Smart-UPS On-Line, 1500VA, Rackmount 2U, 230V, 8x C13 IEC outlets, Network Card, W/ rail kit, Used W/O Lithium-ion external battery

APC Smart-UPS On-Line, 1500VA, Rackmount 2U, 230V, 8x C13 IEC outlets, Network Card, W/ rail kit, Used W/O Lithium-ion external battery:

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 1500VA on-line 2U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with 1x IEC 320 C14 input and 8x IEC 320 C13 outlets. The UPS has a preinstalled Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 5-year warranty, and has to be used with an external Lithium-ion battery sold separately.

Features

UPS topology *	Double-conversion (Online)
Output power capacity *	1.5 kVA
Output power *	1350 W
Waveform *	Sine
Input operation voltage (min) *	80 V
Input operation voltage (max) *	240 V
Input frequency *	40 - 70 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Surge energy rating	340 J
Heat dissipation	450 BTU/h
Crest factor	3:1
Output voltage Total Harmonic Distortion (THD)	2%
Noise level	50 dB

Ports & interfaces

AC outlet types	C13 coupler, C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	✓
Serial ports quantity	1
Ethernet LAN (RJ-45) ports	1

Ports & interfaces

Emergency Power Off (EPO) connector	✓
SmartSlot	✓

Design

Form factor *	Rackmount
Rack capacity	2U
Product colour *	Black
International Protection (IP) code	IP20
Certification	CE, CE Mark, EAC, RCM, UK PSTI, VDE

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 15240 m

Weight & dimensions

Width	432 mm
Depth	590 mm
Height	85 mm
Weight	17.5 kg
Package width	810 mm
Package depth	600 mm
Package height	245 mm
Package weight	28.2 kg

0731304338727

731304338727