

TP-Link INSIGHT S385 Bullet IP security camera Outdoor 2880 x 1620 pixels Wall

Brand : TP-Link **Product code:** INSIGHT S385(2.8MM)

Product name: INSIGHT S385

- 4K (8MP) Ultra HD and 24h Full-Color
- People & Vehicle Analytics§
- Human & Vehicle Classification
- Smart Detection
- Smart Video Enhancement Technology
- Active Defense and Two-Way Audio
- IP67 Waterproof
- H.265+ Compression Technology
- 12V DC/PoE

VIGI 8MP Outdoor Full-Color Bullet Network Camera, 1/2.7", 1/3 to 1/10000 s, F1.6, 3840 x 2160, CBR, VBR, BLC/3D DNR/HLC/SmartIR, 120 dB, 12V DC \pm 5%, Max. 10.5 W, 5.5 mm Coaxial Power Plug, PoE: 802.3af/at, class 0, Max. 11.5 W, IP67, 184 x 74 x 74 mm, 0.525 kg, White

TP-Link INSIGHT S385. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Wall, Product colour: White, Form factor: Bullet. Lens viewing angle, horizontal: 111.4° , Lens viewing angle, vertical: 58.8° , Lens viewing angle, diagonal: 134° . Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm ($1 / 2.7^{\circ}$). Detect distance: 64 m, Observe distance: 27 m, Recognize distance: 13 m





Performance		Audio	
2.	85 m ✓	Audio output channels Audio formats supported Sample rate Built-in microphone Number of microphones Bit rate range	1 channels G.711 A-law 8 kHz ✓ 1 0 - 64 Kbit/s
Infrared (IR) cut-off filter	✓	Network	
Remote viewing Dynamic range	✓ 120 dB	Ethernet LAN * Networking standards	✓ IEEE 802.3af, IEEE 802.3at
Design Form factor * Mounting type *	Bullet Wall	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Product colour *	White	Wi-Fi *	×
Housing material	Metal	Bluetooth *	×
Protection features International Protection (IP) code	Waterproof IP67	Live view	✓
Weatherproof	IPO7 ✓	Storage	
Camera		Compatible memory cards Maximum memory card size	MicroSD (TransFlash) 512 GB
Minimum illumination Lens viewing angle, horizontal	0 lx 111.4°	Ports & interfaces	
Lens viewing angle, nonzontal Lens viewing angle, vertical Lens viewing angle, diagonal	58.8° 134°	Ethernet LAN (RJ-45) ports DC-in jack	1 •
Tilt angle range	0 - 90°	Security	
Camera shutter speed	1/3 to 1/10000	Built-in siren	✓
Image sensor		Password protection	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Video motion detection	✓
Progressive scan Sensor type *	CMOS	IP address filtering	✓
		HTTPS encryption	✓
		Alert notification type	Push notification

Lens system		Security	
Detect distance	64 m	Motion sensor	✓
Observe distance	27 m	Mirror	✓
Recognize distance Maximum aperture number	13 m 1.6	Human and vehicle targets classification	✓
Identify distance	6 m	Digest authentication	✓
Fixed focal length	2.8 mm	Management features	
Night vision		Web-based management	✓
Night vision *	✓	Web browser	✓
LED type	IR/White	Cloud-managed *	/
Video		Reset button	·
Maximum resolution *	2880 x 1620 pixels		•
Total megapixels *	8 MP	Power	
Video compression formats	H.264, H.264+, H.265, H.265+	Power source type *	DC, PoE
	320 x 240, 352 x 288, 640 x 360, 640 x 480 (VGA), 704 x 576, 848 x 480, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2688 x 1520, 2880 x 1620	Power consumption (max)	10.5 W
Supported graphics resolutions		Power consumption (Power over Ethernet (PoE))	11.5 W
		DC output voltage	12
Video recording	✓ × 1250, 2000 × 1520, 2000 × 1020	Operational conditions	
•	Brightness, Contrast, Mirror,	Operating temperature (T-T)	-30 - 60 °C
Image quality adjustment	Saturation, Sharpness	Storage temperature (T-T)	-40 - 60 °C
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)		0 - 95%
B., .	Main Stream: 256 Kbps to 8 Mbps,	Storage relative humidity (H-H)	0 - 95%
Bit rate	Sub-Stream: 64 Kbps to 512 Kbps	Weight & dimensions	
Back Light Compensation (BLC)	✓	Width	74 mm
Highlight Compensation (HLC)	✓	Height	74 mm
Digital Wide Dynamic Range		Length	184 mm
(DWDR)	·	Weight	525 g
Audio		Packaging content	
Built-in speaker(s)	✓	Number of cameras *	1
Audio system	2-way	Mounting kit	✓
Audio input channels	1 channels	Screws included	✓
		Drilling template included	✓
		Manual	✓



1210002606349

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.