



Xtorm Original USB-C PD cable (1m) Black

Brand : Xtorm **Product code:** CX2071

Product name : Original USB-C PD cable (1m) Black


Original USB-C PD cable (1m) Black

Xtorm Original USB-C PD cable (1m) Black:

This Xtorm Original Cable is designed to be the perfect every-day cable. Powerful fast charging and reliable data transfer are combined with durable features that make this cable able to withstand the wear and tear caused by daily use.

The use of braided nylon not only reinforces the cable, but also ensures its flexibility over long periods of time. The connectors feature a unique metal housing, specially designed with a U-shaped cut out that allows the cable to bend and move more freely.

Xtorm Original USB-C PD cable (1m) Black. Cable length: 1 m. Connector 1: USB C, Connector 2: USB C, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 10 Gbit/s, Product colour: Black



| Features | | Weight & dimensions | |
|----------------------------|--|----------------------------------|----------|
| USB version * | USB 3.2 Gen 1 (3.1 Gen 1) | Cable length * | 1 m |
| Connector 1 * | USB C | Weight | 43 g |
| Connector 2 * | USB C | Packaging data | |
| Connector 1 gender * | Male | Package width | 65 mm |
| Connector 2 gender * | Male | Package depth | 176 mm |
| Connector 1 form factor | Straight | Package height | 201 mm |
| Connector 2 form factor | Straight | Package weight | 75 g |
| Cable jacket material | Nylon/Polyvinyl Chloride (PVC), Aluminum | Packaging content | |
| Maximum data transfer rate | 10000 Mbit/s | Quantity per pack * | 1 pc(s) |
| Maximum data transfer rate | 10 Gbit/s | Logistics data | |
| Product colour * | Black | Products per master (outer) case | 40 pc(s) |
| Plug and Play | ✓ | Master (outer) case width | 325 mm |
| USB Power Delivery | ✓ | Master (outer) case length | 245 mm |
| USB Power Delivery up to | 100 W | Master (outer) case height | 330 mm |
| Power | | Master (outer) case gross weight | 4 kg |
| Output voltage | 20 V | Harmonized System (HS) code | 84733080 |
| Output current (max) | 5 A | | |



8718182274912

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-AUG-2024. Prints or copies of Information are only valid on the printed Publication date