

Fujitsu PRIMERGY RX2540 M7 server Rack (2U) Intel Xeon Silver 4410Y 2 GHz 32 GB DDR5-SDRAM 900 W

Brand : Fujitsu

Product family: PRIMERGY

Product code:
VFY:R2547SC020IN

Product name : RX2540 M7

- No OS
- Intel Xeon Silver 4410Y (30MB Cache, 2GHz)
- 32GB (4800MHz) DDR5-SDRAM (1 x 32)
Intel Xeon Silver 4410Y (30MB Cache, 2GHz), 32GB DDR5-SDRAM (4800MHz), LAN, 900W, No OS
Fujitsu PRIMERGY RX2540 M7. Processor family: Intel Xeon Silver, Processor frequency: 2 GHz, Processor model: 4410Y. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM. HDD size: 2.5". Ethernet LAN. Power supply: 900 W, Redundant power supply (RPS) support. Chassis type: Rack (2U)



Processor		Design	
Processor manufacturer *	Intel	Redundant fans support	✓
Processor family *	Intel Xeon Silver	Performance	
Processor model *	4410Y	Trusted Platform Module (TPM)	✓
Processor frequency *	2 GHz	Trusted Platform Module (TPM) version	2.0
Processor boost frequency	3.9 GHz	Software	
Processor cores	12	Operating system installed *	✗
Processor cache	30 MB	Compatible operating systems *	Windows Server 2022 Datacenter
Motherboard chipset	Intel C741		Windows Server 2022 Standard
Configurable TDP-down	4.5 W		Windows Server 2019 Datacenter
Bus type	OPI		Windows Server 2019 Standard
Memory		Compatible operating systems *	Windows Server 2019 Essentials
Internal memory *	32 GB		SUSE® Linux Enterprise Server 15
Internal memory type *	DDR5-SDRAM		Red Hat® Enterprise Linux 8
Memory clock speed	4800 MHz		
Maximum internal memory *	8 TB	Processor special features	
Storage		CPU configuration (max)	1
HDD size	2.5"	Intel Smart Response Technology version	1.00
Number of HDDs supported	16	Intel Stable Image Platform Program (SIPP) version	0.00
RAID support *	✓	Intel Secure Key Technology version	1.00
Network		Intel TSX-NI version	0.00
Ethernet LAN	✓	Power	
Ports & interfaces		Redundant power supply (RPS) support *	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Power supply *	900 W
VGA (D-Sub) ports quantity	1	Power supply input voltage	100 - 240 V
Expansion slots		Power supply input frequency	50/60 Hz
PCI Express x16 (Gen 4.x) slots	1	Weight & dimensions	
Design		Width	482.2 mm
Chassis type *	Rack (2U)	Depth	800 mm
Product colour	Black	Height	86.9 mm
		Weight	32 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-OCT-2024. Prints or copies of Information are only valid on the printed Publication date