



APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack mountable, NMC, 750VA

Brand : APC

Product code: SMT750RMI2UNC

Product name : APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack mountable, NMC, 750VA



APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack mountable, NMC, 750VA  
APC Smart-UPS SMT750RMI2UNC - 4x C13, USB, Rack mountable, NMC, 750VA. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, C14 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 168 Ah, Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 406 mm, Height: 89 mm



| Features                        |                          | Design                            |  |
|---------------------------------|--------------------------|-----------------------------------|--|
| UPS topology *                  | Line-Interactive         | Form factor *                     | Rackmount  |
| Output power capacity *         | 0.75 kVA                 | Rack capacity                     | 2U   |
| Output power *                  | 500 W                    | Product colour *                  | Black  |
| Waveform *                      | Sine                     | Display type                      | LCD  |
| Input operation voltage (min) * | 151 V                    | LED indicators                    | ✓  |
| Input operation voltage (max) * | 302 V                    | Certification                     | CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE |
| Input frequency *               | 50/60 Hz                 |                                   |  |
| Output operation voltage (min)  | 220 V                    |                                   |  |
| Output operation voltage (max)  | 240 V                    |                                   |  |
| Output frequency                | 50/60 Hz                 |                                   |  |
| Output frequency regulation     | +/- 3 Hz                 | Operational conditions            |  |
| Output voltage regulation       | 5%                       | Operating temperature (T-T)       | 0 - 40 °C  |
| Surge energy rating             | 459 J                    | Storage temperature (T-T)         | -15 - 45 °C  |
| Response time                   | 2 ms                     | Operating relative humidity (H-H) | 0 - 95%  |
| Emergency Power Off (EPO)       | 0                        | Storage relative humidity (H-H)   | 0 - 95%  |
| Noise level                     | 46 dB                    | Operating altitude                | 0 - 3000 m   |
| Surge protection                | ✓                        | Non-operating altitude            | 0 - 15000 m  |
| Audible alarm(s)                | ✓                        | Technical details                 |  |
| Web-based management            | ✓                        | Sustainability certificates       | Green Premium  |
| Audible alarm modes             | Battery replacement      | Compliance certificates           | RoHS   |
| Auto-restart                    | ✓                        | Weight & dimensions               |  |
| Ports & interfaces              |                          | Width                             | 432 mm   |
| AC outlet types                 | C13 coupler, C14 coupler | Depth                             | 406 mm   |
| Power plug                      | C14 coupler              | Height                            | 89 mm  |
| AC outlets quantity             | 4 AC outlet(s)           | Weight                            | 17.2 kg  |
| USB 2.0 ports quantity          | 1                        | Package width                     | 546 mm   |
| Ethernet LAN (RJ-45) ports      | 1                        | Package depth                     | 584 mm   |
| Battery                         |                          | Package height                    | 241 mm   |
| Battery technology              | Sealed Lead Acid (VRLA)  | Package weight                    | 21.2 kg  |
| Battery capacity                | 168 Ah                   | Packaging data                    |  |
| Battery recharge time           | 3 h                      | Rack mount kit                    | ✓  |
| Hot-swap battery                | ✓                        | Cables included                   | Input power cable, USB cable   |
| Automatic battery test          | ✓                        | Quick installation guide          | ✓  |
| Cold start                      | ✓                        | Resource CD                       | ✓  |
|                                 |                          | Logistics data                    |  |
|                                 |                          | Products per pallet               | 16 pc(s)   |

**Logistics data**

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 85078000 |
|-----------------------------|----------|

**Other features**

|                |       |
|----------------|-------|
| Output voltage | 230 V |
|----------------|-------|



0731304327721



731304327721

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.