

Brother PT-P750W label printer 180 x 180 DPI 30 mm/sec Wired & Wireless HSE/TZe Wi-Fi

Brand : Brother

Product code: PTP750WZU1

Product name : PT-P750W

Printer Model for HSE and TZe tapes from 3.5 to 24 mm - PC connection - Wireless - 180 dpi
 Brother PT-P750W. Tape type: HSE/TZe. Maximum resolution: 180 x 180 DPI, Print speed: 30 mm/sec.
 Connectivity technology: Wired & Wireless. Product colour: Black



Printing		System requirements		
Maximum resolution *	180 x 180 DPI		Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64	
Print speed *	30 mm/sec			
Maximum printing width *	2.4 cm			
Maximum print height	1.8 cm			
Vertical printing	✓			
Paper handling		Windows operating systems supported		
Autocutter	✓			
Maximum label width	2.4 cm			
Maximum label length	4 m	Mac operating systems supported	Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks	
Ports & interfaces				
Connectivity technology *	Wired & Wireless			
Ethernet LAN *	✗			
Wi-Fi *	✓			
USB port *	✓			
USB 2.0 ports quantity	1			
Performance		Weight & dimensions		
Built-in barcodes	AZTECCODE, CODABAR (NW-7), Code 39, Data Matrix, EAN128, EAN13, EAN8, GS1 COMPOSITE, GS1 DataBar, GS1-128, ISBN-2, ISBN-5, ITF-25, MaxiCode, Micro QR Code, PDF417, POSTNET, QR Code, UPC-A, UPC-E			
Number of fonts	12			
Tape type	HSE/TZe			
Tape cutting	Automatic			
Image formats supported	BMP, JPG, TIF	Packaging data	Package weight	1.67 kg

Design		Packaging content	
Product colour *	Black	Bundled software	P-touch Editor Lite
		Quick start guide	✓
		AC adapter included	✓
		Carrying case	✓
		Logistics data	
		Harmonized System (HS) code	84433210
		Technical details	
		Supported batteries	LR6, HR6, BA-E001
		Sustainability certificates	ENERGY STAR
		Other features	
		Label type	3.5, 6, 9, 12, 18, 24 mm
		Number of frames	154

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-JAN-2025. Prints or copies of Information are only valid on the printed Publication date