PHILIPS

Philips 5000 series 34E1C5600HE/00 LED display 86.4 cm (34") 3440 x 1440 pixels 4K Ultra HD Black

Brand: Philips **Product family:** 5000 series **Product code:**

34E1C5600HE/00

Product name:

34E1C5600HE/00

Monitor 34E1C5600HE LCD monitor

Philips 5000 series 34E1C5600HE/00 LED display 86.4 cm (34") 3440 x 1440 pixels 4K Ultra HD Black:

This Philips monitor is designed for the remote work environment. The integrated 5MP webcam delivers sharp images, and noise cancelling mic helps people hear you loud and clear. Philips 5000 series 34E1C5600HE/00. Display diagonal: 86.4 cm (34"), Display resolution: 3440 x 1440

pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 21:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black





Display		Ergonomics	
Display diagonal *	86.4 cm (34")	Tilt angle range	-5 - 20°
Display resolution *	3440 x 1440 pixels	Picture-in-Picture	✓
HD type *	4K Ultra HD	On Screen Display (OSD)	✓
Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen *	21:9 LED VA W-LED	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Display brightness (typical)	300 cd/m ²	Number of OSD languages	21
Response time *	4 ms	Plug and Play	✓
Anti-glare screen	✓	LED indicators	Operation, Stand-by
Screen shape *	Curved	Power	
Screen curvature rating	1500R	Energy efficiency class (SDR) *	G
Aspect ratio	21:9	Energy consumption (SDR) per 1000	43 kWh
Contrast ratio (typical) *	3000:1	hours *	43 KWN
Dynamic contrast ratio marketing name	Mega Infinity DCR	Power consumption (typical) *	57 W
Maximum refresh rate *	100 Hz	Power consumption (standby) *	0.5 W
Viewing angle, horizontal	178°	Power consumption (off)	0.3 W
Viewing angle, vertical	178°	AC input voltage	100 - 240 V
Display number of colours *	16.7 million colours	AC input frequency	50 - 60 Hz
Response time (fast)	1 ms	Power supply type	Internal
Pixel pitch	0.23175 x 0.23175 mm	European Product Registry for Energy Labelling (EPREL) code	1172087
Pixel density	109.68 ppi	Operational conditions	
Horizontal scan range	30 - 160 kHz	Operating temperature (T-T)	0 - 40 °C
Vertical scan range	48 - 100 Hz	Storage temperature (T-T)	-20 - 60 °C
Viewable size, horizontal	79.7 cm	Operating relative humidity (H-H)	20 - 80%
Viewable size, vertical	33.4 cm	Operating altitude	0 - 3658 m
Display diagonal (metric)	86.36 cm	Non-operating altitude	0 - 12192 m
DDC/CI	✓	, ,	0 - 12132 111
Haze rate	25%	Weight & dimensions	
Surface hardness	ЗН	Width (with stand)	808 mm
sRGB coverage (typical)	123.24%	Depth (with stand)	281 mm

B1: .1.		Maria I. I. C. di	
Display		Weight & dimensions	
		Height (with stand)	557 mm
Display sRGB ✓		Weight (with stand) Width (without stand)	9.29 kg 808 mm
Performance		Depth (without stand)	111 mm
NVIDIA G-SYNC *		Height (without stand)	381 mm
AMD FreeSync *		Weight (without stand)	7.16 kg
VESA Adaptive Sync support ✓		Packaging data	
Component video sync Sep.	narate sync	Package width	980 mm
Flicker-free technology		Package depth	226 mm
Low Blue Light technology ✓		Package height	519 mm
Multimedia		Package weight	12.4 kg
		Packaging content	3
Number of speakers 2 RMS rated power 5 W			
Built-in speaker(s) * ✓	V	Stand included	✓
Megapixel (approx.) 5 Ml	1D	Cables included	HDMI, USB Type-C, AC
Built-in microphone	ır	Manual	✓
Built-in camera *		Sustainability	
		Doesn't contain	Mercury, PVC/BFR
Design		Other features	
	ming	Compatible operating systems	Mac OS X, Windows 10 / 8.1 / 8 / 7
Product colour * Blac	CK	Picture-by-Picture (PbP)	✓
Ports & interfaces		Exterior finish type	Textured
Built-in USB hub * ✓		Recyclable packaging material	100%
USB hub version 3.2	Gen 1 (3.1 Gen 1)	MultiView	PIP/PBP mode, 2 x devices
USB Power Delivery (USB PD) ✓		Heavy metals free	Hg (mercury)
USB Power Delivery up to 65 V	W	EasyRead mode	1
HDMI * ✓		LowBlue mode	✓
HDMI ports quantity 1		Weight	7.16 kg
HDMI version 2.0		Height	381 mm
DisplayPorts quantity 1		Depth	111 mm
DisplayPort version 1.2		Compliance certificates	RoHS
Audio output		Picture enhancement	SmartImage game
HDCP ✓		Regulatory Approvals	CB; CE Mark; CU-EAC; EAEU RoHS; FCC Class B; ICES-003;
HDCP version 1.4/	/2.2	· · · · ·	TUV/ISO9241-307; TUV-BAUART
Ergonomics		Energy efficiency class (old)	G
VESA mounting * ✓		Width	808 mm
The state of the s	0 x 100 mm	Mean time between failures (MTBF)	50000 h
Panel mounting interface 100			CB, CE Mark, CU-EAC, EAEU RoHS,
Panel mounting interface 100 Cable lock slot * ✓		Certification	FCC Class B, ICES-003.
Cable lock slot *	nsington	Certification	FCC Class B, ICES-003, TUV/ISO9241-307, TUV-BAUART
Cable lock slot *	nsington	Certification Logistics data	
Cable lock slot * ✓ Cable lock slot type Ken	nsington		



8712581783464

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.