DELL C6522QT Interactive flat panel 163.9 cm (64.5") LCD 350 cd/m² 4K Ultra HD Black Touchscreen

Brand : DELL **Product code:** DELL-C6522QT

Product name : C6522QT

- 163.91cm (64.53") 4K 3840 x 2160 LED IPS
- 9ms, 16:9, 350cd/m², 1300:1
- RJ-45, HDMI, DisplayPort, USB
163.91cm (64.53") 4K 3840 x 2160 LED IPS, 16:9, 350 cd/m², 1.073B, 9ms, 178° /178°, 1300:1

DELL C6522QT Interactive flat panel 163.9 cm (64.5") LCD 350 cd/m² 4K Ultra HD Black Touchscreen:

Bring the team together, whether they are in the room or remote, with this brilliant 65" 4K UHD screen with built-in dual 20W speakers.
DELL C6522QT. Product design: Interactive flat panel. Display diagonal: 163.9 cm (64.5"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD, Touchscreen. Product colour: Black

Display

Panel type	IPS
LED backlight	✔
Display diagonal *	163.9 cm (64.5")
Display technology *	LCD
Display resolution *	3840 x 2160 pixels
Display brightness *	350 cd/m²
HD type *	4K Ultra HD
Touchscreen *	✔
Number of simultaneous touchpoints	20
Multi-touch	✔
Native aspect ratio	16:9
Response time	9 ms
Contrast ratio (typical)	1300:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.073 billion colours
Pixel pitch	0.372 x 0.372 mm
Active display area (W x H)	1428.5 x 803.5 mm
Display diagonal (metric)	163.906 cm
Horizontal scan range	30 - 140 kHz
Vertical scan range	24 - 75 Hz
Native refresh rate	60 Hz
Colour gamut	72%

Ports & interfaces

HDMI ports quantity *	3
HDMI version	2.0
DVI port *	✖
DisplayPorts quantity *	1

Design

Bezel width (side)	4.47 cm
Bezel width (top)	4.47 cm

Performance

Purpose *	Corporate
On Screen Display (OSD)	✔

Power

Power consumption (typical) *	92.9 W
Power consumption (standby) *	0.3 W
Power consumption (off)	0.3 W
Power consumption (max)	350 W
Energy efficiency class (SDR)	F
Energy consumption (SDR) per 1000 hours	93 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Heat dissipation	316.99 BTU/h

Computer system

Computer system *	✖
Built-in processor *	✖

Weight & dimensions

Width	1517.9 mm
Depth	78.7 mm
Height	892.9 mm
Weight	45.2 kg

Packaging data

Package weight	55.5 kg

Ports & interfaces

USB port *	✔
USB ports quantity	8
USB version	3.2 Gen 1 (3.1 Gen 1)
USB connector type	USB Type-C
Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Wi-Fi *	✘
Audio (L/R) out	1
RS-232 interface	✔

Audio

Built-in speaker(s) *	✘
Number of built-in speakers	2
RMS rated power	40 W
Speaker impedance	8 Ω
Speaker frequency range	120 - 20000 Hz

Design

Product design *	Interactive flat panel
Placement supported *	Indoor
Orientation	Horizontal
Product colour *	Black
VESA mounting *	✔
Panel mounting interface	400 x 400 mm
Bezel width (bottom)	4.47 cm

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 90%

Logistics data

Harmonized System (HS) code	85285210

Carbon footprint

Total carbon footprint (kg of CO_2e)	2060
Total carbon emissions, standard deviation (kg of CO_2e)	278
Carbon emissions, manufacturing (kg of CO_2e)	800
Carbon emissions, logistics (kg of CO_2e)	286
Carbon emissions, energy usage (kg of CO_2e)	957
Carbon emissions, end-of-life (kg of CO_2e)	18
Total carbon emissions, w/o use phase (kg of CO_2e)	1104
PAIA version	1.2.14, 2021

5397184504949