ASUS PRIME H510M-K R2.0 Intel H510 LGA 1200 (Socket H5) micro ATX

Brand: ASUS **Product code**: 90MB1E80-M0EAY0

Product name: PRIME H510M-K R2.0

ASUS PRIME H510M-K R2.0. Processor manufacturer: Intel, Processor socket: LGA 1200 (Socket H5), Compatible processor series: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9,.... Supported memory types: DDR4-SDRAM, Maximum internal memory: 64 GB, Memory slots type: DIMM. Supported storage drive interfaces: M.2, SATA III, Supported storage drive types: HDD & SSD. Ethernet interface type: Fast Ethernet, Gigabit Ethernet. Component for: PC, Motherboard form factor: micro ATX, Motherboard chipset family: Intel







Processor		Internal I/O	
Processor manufacturer * Processor socket * Compatible processor series *	Intel LGA 1200 (Socket H5) Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium®	EPS power connector (8-pin) TPM connector 12V power connector Rear panel I/O ports	1 1
Number of memory slots * Memory slots type Memory channels Non-ECC	Gold DDR4-SDRAM 2 DIMM Dual-channel	USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * Ethernet LAN (RJ-45) ports * PS/2 ports quantity VGA (D-Sub) ports quantity * HDMI ports quantity * COM ports quantity	2 4 1 1 1 1 1
Supported memory clock speeds	2133,2400,2666,2800,2933,3000,3200 MHz	Network	
	64 GB √	Ethernet LAN Ethernet interface type Wi-Fi *	✓ Fast Ethernet, Gigabit Ethernet
Supported storage drive types Supported storage drive interfaces * Number of HDDs supported Number of storage drives supported	4	Features Motherboard chipset * Audio output channels * Component for *	Intel H510 7.1 channels PC
Internal I/O USB 2.0 connectors * USB 3.2 Gen 1 (3.1 Gen 1) connectors *	2	Motherboard form factor * Motherboard chipset family * Windows operating systems supported	micro ATX Intel Windows 10 x64
Number of SATA III connectors * S/PDIF out connector Front panel audio connector	4	Expansion slots PCI Express x1 (Gen 3.x) slots Number of M.2 (M) slots	1 1
ATX Power connector (24-pin) CPU fan connector Number of chassis fan connectors		BIOS BIOS type * BIOS memory size	EFI AMI 128 Mbit

		_				
Weig	ıht	N.	М	ıme	ncı	nns

 Width
 226 mm

 Depth
 203 mm



4711387113189

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.