Logitech Logi Dock Flex

Brand : Logitech **Product code:** 939-002180

Product name : Logi Dock Flex

- Logi Dock Flex is a managed docking station that enables an easier desk booking experience and a better way to manage shared desks across locations
- Easily combine Logi Dock Flex with Microsoft Teams or Zoom Workspace Reservation or Logitech's own desk booking service for a simple and consistent user experience
- Logi Dock Flex includes ports for 6 USB peripherals, dual 4K displays, Gigabit Ethernet, and up to 100w of power, with no special drivers required
- By using a single USB-C cable, employees easily connect their laptops and gain immediate access to all desk peripherals
- The included cable management is designed to keep employees connected, day after day. Locked-in cables help you make sure desk peripherals aren't lost or unplugged
- Monitor and manage Logi Dock Flex remotely using compatible software such as Logitech Sync, Zoom Device Management, or Microsoft Teams Admin Center Logi Dock Flex





Display		Network	
Display diagonal * Display resolution *	20.3 cm (8") 1280 x 800 pixels	Wi-Fi standards *	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Display technology *	IPS	Bluetooth *	✓
LED backlight	✓	Bluetooth version	5.0
Viewing angle	85°	Ethernet LAN *	✓
Display brightness	300 cd/m ²	Ethernet LAN data rates	10,100,1000 Mbit/s
Touchscreen technology	Capacitive	Security algorithms	128-bit AES
Number of simultaneous touchpoints	5	Ports & interfaces	
Fingerprint resistant	✓	USB port	✓
Design		RJ-45 ports quantity	1
	White	USB Type-C ports quantity	4
Housing colour *		USB 2.0 Type-A ports quantity	3
Cable lock slot	✓ Wasalasta	Power	
Cable lock slot type	Kensington	Power source type	DC
Ambient light sensor	✓	Weight & dimensions	
Oleophobic coating	✓	Width	201 mm
Performance		Depth	177 mm
Windows operating systems supported	✓	Height	141 mm
Mac operating systems supported	MacOS	Weight	1 kg
Audio		Packaging content	
Built-in speaker(s) *		Cables included	AC, USB Type-C
	X	Packaging content	{loc-value}
Built-in microphone *	X	Operational conditions	
Camera		Operating relative humidity (H-H)	10 - 90%
Built-in camera *	×	Storage relative humidity (H-H)	0 - 95%
Network		Operating temperature (T-T)	0 - 40 °C
Wi-Fi *	✓	Storage temperature (T-T)	-40 - 75 °C
*** **	•		



5099206119055

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.