# Philips Signage Solutions 75BDL3511Q/00 Signage Display Digital signage flat panel 190.5 cm (75") IPS 400 cd/m² 4K Ultra HD Black

Brand : Philips

Product family: Signage Solutions

Product code: 75BDL3511Q/00

Product name :
75BDL3511Q/00

Philips Signage Solutions 75BDL3511Q/00. Product design: Digital signage flat panel. Display diagonal: 190.5 cm (75"), Display technology: IPS, Display resolution: 3840 x 2160 pixels, Display brightness: 400 cd/m², HD type: 4K Ultra HD. Product colour: Black

Display

LED backlighting type	Direct-lit LED
Display diagonal *	190.5 cm (75")
Display technology *	IPS
Display resolution *	3840 x 2160 pixels
Display brightness *	400 cd/m²
HD type *	4K Ultra HD
Touchscreen *	✗
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	500000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.4296 x 0.4296 mm
Display diagonal (metric)	189.3 cm
Native refresh rate	60 Hz
Haze rate	1%

Ports & interfaces

HDMI ports quantity *	3
HDMI version	2.0
HDMI input ports quantity	3
DVI port *	✔
DVI-I ports quantity	1
USB port *	✔
USB ports quantity	2
USB version	2.0
Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Wi-Fi *	✗
RS-232C	✔
OPS module slot	✔

Audio

Built-in speaker(s) *	✔
Number of built-in speakers	2
RMS rated power	20 W

Design

Product design *	Digital signage flat panel
Placement supported *	Indoor
Orientation	Horizontal/Vertical
Product colour *	Black

Performance

Purpose *	Universal
On Screen Display (OSD)	✔
Number of OSD languages	12
On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Polish, Russian, Turkish
Mean time between failures (MTBF)	50000 h

Power

Power consumption (typical) *	180 W
Power consumption (standby) *	0.5 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	181 kWh
AC input voltage	100/240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G

Computer system

Computer system *	✗
Built-in processor *	✗
Video formats supported	H.264, MPEG, WMV3
Audio formats supported	AAC, AAC HE, WMA
Image formats supported	BMP, JPEG, PNG

Weight & dimensions

Display width	1683.5 mm
Display depth	69.5 mm
Display height	961.7 mm
Display weight	37.3 kg

Packaging content

Batteries included	✔
Power adapter model	AC,IR sensor,RS-232

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 95%

Certificates

Certification	FCC, Class A CB BSMI VCCI CU ETL EMF PSB

Features

Wall mountable	✔

Design		Other features	
VESA mounting *	✔	Maximum refresh rate	60 Hz
Panel mounting interface	600 x 400 mm		

8712581778613

0685417580385

685417580385