PHILIPS

Philips 1000 series 32E1N1800LA/00 LED display 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD LCD Black

Brand : Philips **Product family:** 1000 series **Product code:** 32E1N1800LA/00

Product name: 32E1N1800LA/00

Monitor 32E1N1800LA 4K UHD monitor

Philips 1000 series 32E1N1800LA/00 LED display 80 cm (31.5") 3840×2160 pixels 4K Ultra HD LCD Black:

This 32-inch monitor is made for clear visuals with its UltraClear 4K UHD resolution, HDR imagery, and VA display. With all these features in mind, you can expect images that are high-quality and crisp. Philips 1000 series 32E1N1800LA/00. Display diagonal: 80 cm (31.5"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black





Display		Ergonomics	
Display diagonal *	80 cm (31.5")	VESA mounting *	✓
Display resolution *	3840 x 2160 pixels	Panel mounting interface	100 x 100 mm
HD type *	4K Ultra HD	Cable lock slot *	✓
Native aspect ratio *	16:9	Cable lock slot type	Kensington
Display technology *	LCD	Height adjustment *	×
Panel type *	VA	Tilt adjustment	/
LED backlight	✓	Tilt angle range	-5 - 20°
Backlight type	W-LED	On Screen Display (OSD)	✓ ·
Touchscreen *	×	on screen bisplay (03b)	Simplified Chinese, Traditional
Display brightness (typical)	300 cd/m ²	On Screen Display (OSD) languages	Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Response time *	4 ms		
Anti-glare screen	✓		
Screen shape *	Flat		
Contrast ratio (typical) *	3500:1	Number of OSD languages	21
Dynamic contrast ratio marketing name	Mega Infinity DCR	Plug and Play	Occuption Chandle
Maximum refresh rate *	60 Hz	LED indicators	Operation, Stand-by
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical	178°	Energy efficiency class (SDR) *	F
Display number of colours *	1.07 billion colours	Power consumption (typical) *	34.9 W
Pixel pitch	0.18159 x 0.18159 mm	Power consumption (standby) *	0.5 W
Pixel density	139.87 ppi	Power consumption (off)	0.3 W
Horizontal scan range	30 - 140 kHz	AC input voltage	100 - 240 V
Vertical scan range	40 - 60 Hz	AC input frequency	50/60 Hz
Viewable size, horizontal	69.7 cm	Power supply type	Internal
Viewable size, vertical	39.2 cm	Operational conditions	
Display diagonal (metric)	80 cm	Operating temperature (T-T)	0 - 40 °C

Display		Operational conditions	
High Dynamic Range (HDR) supported High Dynamic Range (HDR) technology	ported h Dynamic Range (HDR) hnology C/CI re rate 25% our depth our gamut standard High Dynamic Range 10 (HDR10) A bit sRGB	Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Non-operating altitude	-20 - 60 °C 20 - 80% 0 - 3658 m 3658 - 12192 m
DDC/CI		Weight & dimensions	
Colour depth Colour gamut standard Display sRGB		Width (with stand) Depth (with stand) Height (with stand) Weight (with stand)	714 mm 140 mm 512 mm 7.39 kg
Performance		Width (without stand)	7.39 kg 714 mm
NVIDIA G-SYNC *	×	Depth (without stand)	52 mm
AMD FreeSync *	×	Height (without stand)	419 mm
Flicker-free technology	✓	Weight (without stand)	6.25 kg
Low Blue Light technology	✓	Packaging data	
Multimedia		Package width	870 mm
Number of speakers RMS rated power Built-in speaker(s) *	2 4 W	Package height	261 mm 512 mm 9.68 kg
Built-in camera *	×	Packaging content	
	^	Stand included	✓
Design	Hama a	Cables included	AC, HDMI
Market positioning * Product colour *	Home Black	Manual	✓
Ports & interfaces	DIUCK	Sustainability	
Built-in USB hub *	×	Doesn't contain	PVC/BFR
HDMI *	^ ✓	Other features	
HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP HDCP version	2 2.0 1 1.4 1.4/2.2	Compatible operating systems Exterior finish type Picture enhancement Recyclable packaging material Delta E EasyRead mode LowBlue mode Philips SmartUniformity	Mac OS Windows 11/10 Textured SmartImage 100% 2 95 - 102%
		Philips SmartUniformity Mean time between failures (MTBF)	



8721038000597

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.