



APC Smart-UPS RT 3000VA 230V - Marine

Brand : APCProduct code: SURTD3000XLIM

Product name : Smart-UPS RT 3000VA 230V - Marine



Smart-UPS RT 3000VA 230V - Marine

APC Smart-UPS RT 3000VA 230V - Marine:


High density, double-conversion on-line power protection with scalable runtime.
APC Smart-UPS RT 3000VA 230V - Marine. UPS topology: Double-conversion (Online), Output power capacity: 3 kVA, Output power: 2100 W. AC outlet types: C13 coupler, C19 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery recharge time: 2.5 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 3U. Width: 130 mm, Depth: 660 mm, Height: 432 mm



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount
Output power capacity *	3 kVA	Rack capacity	3U
Output power *	2100 W	Cable length	2.44 m
Input operation voltage (min) *	100 V	Product colour *	Black
Input operation voltage (max) *	280 V	LED indicators	✓
Input frequency *	50/60 Hz	Operational conditions	
Output operation voltage (min)	220 V	Operating temperature (T-T)	0 - 55 °C
Output operation voltage (max)	240 V	Storage temperature (T-T)	-15 - 45 °C
Surge energy rating	480 J	Operating relative humidity (H-H)	0 - 95%
Efficiency	92%	Storage relative humidity (H-H)	0 - 95%
Crest factor	3:1	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
Output voltage Total Harmonic Distortion (THD)	3%	Technical details	
Noise level	55 dB	Compliance certificates	RoHS
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler, C19 coupler	Width	130 mm
AC outlets quantity	10 AC outlet(s)	Depth	660 mm
Number of output IEC jumpers	2	Height	432 mm
Ethernet LAN (RJ-45) ports	1	Weight	54.5 kg
Battery		Package weight	63.6 kg
Battery technology	Sealed Lead Acid (VRLA)	Logistics data	
Battery recharge time	2.5 h	Harmonized System (HS) code	85078000
Other features			
		Dimensions (WxDxH)	130 x 660 x 432 mm
		Nominal output voltage	230 V
		Nominal input voltage	230 V

Other features

Package dimensions (WxDxH)	603 x 980 x 347 mm
----------------------------	--------------------



0731304283546



731304283546

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.