## SONY

## Sony BRC-X400 Dome IP security camera Indoor 3840 x 2160 pixels Ceiling/wall

Brand : Sony

Product code: BRC-X400/B

Product name : BRC-X400

BRC-X400, 1/2.5 Exmor R CMOS, 3840x2160, 8.5 MP, 4.4-88mm, F 2.0-3.8, HDMI, RJ-45, BNC, DC 12V, PoE+, 158.4x177.5x200.2 mm, Black

Sony BRC-X400. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, Form factor: Dome. Minimum illumination: 1.6 lx, Lens viewing angle, horizontal: 70°, Tilt angle range: -20 - 90°. Sensor type: Exmor, Optical sensor size: 25.4 / 2.5 mm (1 / 2.5"). Focal length range: 4.4 - 88 mm, Focus: Motorized/Manual, Closest focusing distance: 0.08 m





Porformanco		Video	
Performance Type * Placement supported * Connectivity technology * PTZ control PTZ modes Preset points Day/night mode	IP security camera Indoor Wired ✓ Preset point ✓	Video Supported graphics resolutions Supported video modes Frame rate Video streaming Gain control type Incompared video	640 x 360, 720 x 480, 720 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 3840 x 2160 720p, 1080i, 1080p, 2160p 60 fps ✓ Auto/Manual
Infrared (IR) cut-off filter Light exposure modes Design	✓ Auto, Manual, Shutter priority AE	Image stabilizer Bit rate control Bit rate	✓ Constant Bit Rate (CBR), Variable Bit Rate (VBR) 512 Kbps - 50 Mbps
Form factor * Mounting type * Product colour *	Dome Ceiling/wall Black	Audio Audio formats supported Network	AAC-LC
Camera		Ethernet LAN *	1
Camera pan control Camera tilt control Minimum illumination Lens viewing angle, horizontal Tilt angle range Tilt speed	✓ 1.6 lx 70° -20 - 90° 126 °/sec	Networking standards Supported network protocols Wi-Fi * Bluetooth *	IEEE 802.3at IPv4, IPv6, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, DHCP, DNS, RTP/RTCP, RTSP, UPnP, VISCA X X
Pan range	-170 - 170°	Ports & interfaces	
Pan speed White balance Camera shutter speed	300 °/sec Auto, Indoor, Manual, One push, Outdoor 1/1 - 1/10000 s	Ethernet LAN (RJ-45) ports BNC output ports Microphone in HDMI ports quantity	1 1 1
Image sensor Number of sensors	1	DC-in jack	·

Image sensor		Management features	
ptical sensor size	25.4 / 2.5 mm (1 / 2.5")	Web-based management	1
Sensor type *	Exmor	Power	
Lens system		Power source type *	DC, PoE
Zoom capability	1	Power consumption (max)	25.5 W
Number of lenses *	1	DC output voltage	12
Focal length range	4.4 - 88 mm ✓ Motorized/Manual 3.8 2 0.08 m	Operational conditions	
Auto focus		Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Focus			
Maximum aperture number Minimum aperture number		Weight & dimensions	
Closest focusing distance		Width	158.4 mm
Video		Depth	200.2 mm
	ximum resolution * 3840 x 2160 pixels al megapixels * 8.5 MP	Height	177.5 mm
		Weight	1.8 kg
Video compression formats		Packaging content	
		Number of cameras *	1
		Mounting kit	1

Logistics data

Harmonized System (HS) code

85258900

Publication date: 22-APR-2025. Prints or copies of Information are only valid on the printed Publication date



4548736104754

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.