

Product datasheet

Specifications



Backfeed Box, 95A 3-phase power contactor, bottom connection, for Easy UPS 3S 10-40kVA

SP3OPT008

Overview

| | |
|--------------|---|
| Presentation | Wall-mount box with 95A power contactor and connections that delivers backfeed protection for 400V Easy UPS 3S 10-40 kVA. |
| Lead time | Usually Ships within 2 Weeks |

Physical

| | |
|------------|-------|
| Colour | White |
| Height | 30 cm |
| Width | 55 cm |
| Depth | 20 cm |
| Net weight | 20 kg |

Environmental

| | |
|---------------------------------------|-------------|
| Ambient air temperature for operation | 0...40 °C |
| Operating altitude | 0...2000 m |
| Ambient air temperature for storage | -25...55 °C |

Packing Units

| | |
|------------------------------|-------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 30 cm |
| Package 1 Width | 55 cm |
| Package 1 Length | 20 cm |
| Package 1 Weight | 20 kg |

Offer Sustainability

| | |
|-----------------------|--|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| China RoHS Regulation | China RoHS declaration |

RoHS exemption information Yes

Contractual warranty

Warranty 18 months

Recommended replacement(s)