GIGABYTE

GIGABYTE GP-P650G power supply unit 650 W 20+4 pin ATX ATX Black

Brand : GIGABYTE

Product code: GP-P650G

Product name : GP-P650G

- 80 PLUS Gold certified

- 120mm Smart Hydraulic Bearing (HYB) Fan
- Main Japanese capacitors
- Powerful single +12V rail
- OVP/OPP/SCP/UVP/OCP/OTP protection
- Compact size

650W, ATX, 12V, 80 Plus Bronze

GIGABYTE GP-P650G. Total power: 650 W, AC input voltage: 100 - 240 V, Input current: 12 - 6 A. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 50 cm, SATA power cable length: 150,500 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 140 mm, Depth: 150 mm, Height: 86 mm





Power		Ports & interfaces	
Total power *	650 W	PCI Express power cable length	65 cm
AC input voltage *	100 - 240 V	CPU P4 connector (4-pin)	1
Input current	12 - 6 A	CPU power connector (4+4 pin)	1
Maximum input current (@110V)	12 A	CPU power cable length	60 cm
Maximum input current (@220V)	6 A	ATX power connector (20+4 pin)	1
Power Factor Correction (PFC) type	Active	Floppy disk drive connector	1
Combined power (+3.3V)	120 W	Cabling type	Non-Modular
Combined power (+12V)	650 W		
Combined power (+5V)	650 W	Performance	
Combined power (-12V)	3.6 W	80 PLUS certification *	80 PLUS Bronze
Combined power (+5Vsb)	12.5 W	Purpose *	PC
Max output current (+3.3V)	20 A	Power supply unit (PSU) form factor	ATX
Max output current (+12V)	54.17 A	ATX version	2.31
Max output current (+5V)	20 A	Noise level	2.51 39 dB
Max output current (-12V)	0.3 A	Bearing technology	HDB
Max output current (+5Vsb)	20 A	Mean time between failures (MTBF)	100000 h
Power protection features	Over power, Overcharge, Short circuit, Under voltage		100000 11
	circuit, onder voltage	Design	
Ports & interfaces		Product colour	Black
Motherboard power connector *	20+4 pin ATX	Cooling type	Active
Motherboard power cable length	50 cm	Fan diameter	12 cm
Number of SATA power connectors	6	Number of fans	1 fan(s)
SATA power cable length	150,500 mm	Fan location	Тор
Peripheral (Molex) power connectors (4-pin) *	3	On/off switch	✓
Peripheral (Molex) power cable length	150,500 mm	Weight & dimensions	
		Width	140 mm
PCI Express power connectors (6+2	4	Depth	150 mm
pin)	-	Height	86 mm

Packaging data

Package type

Box

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.