Brother MFC-L9630CDN Laser A4 2400 x 600 DPI 40 ppm

Brand : Brother

Product code: MFC-L9630CDNZU1

Product name : MFC-L9630CDN

- Large 17.6cm touchscreen

- Integrated NFC reader
- Cloud Secure Print
- Gigabit network as standard with optional 2.4/5GHz Wi-Fi module
- Expandable memory capacity (USB flash drive not included)

- Fully compatible with 3rd party print management and document management solutions including Kofax, YSoft

Print/Copy and Scan/Fax, 40ppm, 600 x 600dpi, A4, 2GB, NFC, 503 x 541 x 586 mm, 36500 g

Brother MFC-L9630CDN Laser A4 2400 x 600 DPI 40 ppm:

Our most advanced colour printing technology is guaranteed to make the right impression when it counts. Producing vibrant, professional colour documents and accurate digital files every time. With NFC (for mobile print & card authentication) as standard for secure printing and a large customisable touchscreen, it's ideal for busy offices requiring a user-friendly printer with enterprise level security.





| Printing | | Ports & interfaces | |
|--|--|--|--|
| Print technology * Printing * Duplex printing * | Laser Colour printing | Direct printing * USB port USB 2.0 ports quantity | ✓ ✓ 2 |
| Maximum resolution * | 2400 x 600 DPI | Network | 2 |
| Print speed (black, normal quality, A4/US Letter) * | 40 ppm | Wi-Fi * | × |
| Print speed (colour, normal quality, A4/US Letter) | 40 ppm | Ethernet LAN * Cabling technology | ✓ 10/100/1000Base-T(X) |
| Duplex print speed (black, normal quality, A4/US Letter) | 28 ppm | Ethernet LAN data rates Near Field Communication (NFC) | 100,1000 Mbit/s |
| Duplex print speed (colour, normal quality, A4/US Letter) Time to first page (black, normal) | 28 ppm 10 s | Performance | |
| Time to first page (colour, normal) | 10 s | Internal memory * Sound pressure level (printing) | 2000 MB 55 dB |
| Copying Duplex copying * | 1 | Sound pressure level (duplex printing) | 56.5 dB |
| Copying * | Colour copying | Sound pressure level (quiet mode) | 53 dB |
| Maximum copy resolution * | 600 x 600 DPI | Design | |
| Optical scanning resolution * 600 x 6 | olour scanning 00 x 600 DPI 00 x 600 DPI | Product colour * Market positioning * Built-in display * Display diagonal Control type | White Home & office ✓ 17.8 cm (7") Touch |
| Scanner type * | ADF scanner | Power | |
| Scan to Scan speed (colour) Scan speed (black) | FTP 100 ppm 100 ppm | Power consumption (max) Power consumption (printing) Power consumption (copying) | 1080 W 770 W 730 W |
| Fax | | Power consumption (ready) | 85 W |
| Duplex faxing Modem speed | ✔ 33.6 Kbit/s | Power consumption (sleep) Power consumption (off) AC input voltage | 16.8 W 0.04 W 220 - 240 V |
| Features | | AC input frequency | 50 - 60 Hz |
| Recommended duty cycle Maximum duty cycle * | 520 - 2600 pages per month 2600 pages per month | System requirements | |
| Duplex functions * | Copy, Print, Scan | Windows operating systems supported | 1 |

| Input & output capacity | | System requirements | |
|--|---|------------------------------------|------------|
| Total input capacity * | 520 sheets | Mac operating systems supported | 1 |
| Total output capacity * | 250 sheets | Linux operating systems supported | 1 |
| Multi-Purpose tray | 1 | Mobile operating systems supported | 1 |
| Multi-Purpose tray input capacity | 100 sheets | Operational conditions | |
| Auto document feeder (ADF) | Image: A set of the set of the | • | |
| Auto document feeder (ADF) input capacity | 100 sheets | Operating relative humidity (H-H) | 20 - 80% |
| | | Storage temperature (T-T) | 0 - 40 °C |
| Paper handling | | Operating temperature (T-T) | 10 - 32 °C |
| | | Storage relative humidity (H-H) | 10 - 90% |
| Maximum ISO A-series paper size * A4 | A4 Bond paper, Envelopes, Glossy paper, Plain paper, Recycled paper, Thick paper, Thicker paper, Thin paper | Weight & dimensions | |
| Paper tray media types * | | Width | 503 mm |
| | | | 541 mm |
| | | Depth | |
| ISO A-series sizes (A0A9) * | A4, A5, A6 | Height | 586 mm |
| ISO B-series sizes (B0B9) | B5, B6 | Weight | 36.5 kg |
| Envelopes sizes | C5, Com-10, DL | | |
| Custom media width | 100 - 215.9 mm | | |
| Custom media length | 147.3 - 355.6 mm | | |



5023821216509

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.