

DELL E Series 24 Monitor - E2423H

Brand : DELL

Product family: E Series

Product code: DELL-E2423H

Product name : Dell 24 Monitor - E2423H

- 60.5cm (23.8") Full HD 1920 x 1080 LED VA - 8ms, 16:9, 250cd/m², 3000:1 - VGA, DisplayPort

60.5cm (23.8") Full HD 1920 x 1080 LED VA, 16:9, 250cd/m², 16.7M, 8ms, 178°/178°, 3000:1

DELL E Series 24 Monitor - E2423H:

23.8 inch Full HD monitor featuring a wide viewing angle and an eco-conscious design at an accessible price.

DELL E Series 24 Monitor – E2423H. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. VESA mounting. Product colour: Black







	Power	
60.5 cm (23.8")	Energy efficiency class (SDR) *	E
1920 x 1080 pixels	Energy efficiency class (HDR) *	Not available
Full HD	Energy consumption (SDR) per 100	⁰ 16 kWh
16:9		1 4 1 7 14
LCD		14.17 W
VA		0.3 W
LED	• • •	25 W
×		0.3 W
250 cd/m ²	1 5	100 - 240 V
8 ms		50 - 60 Hz
4	Power supply type	Internal
Flat	Energy efficiency scale	A to G
3000:1	European Product Registry for	1144616
3000:1		
60 Hz	Operational conditions	
178°	Operating temperature (T-T)	0 - 40 °C
178°	Storage temperature (T-T)	-20 - 60 °C
16.7 million colours	Operating relative humidity (H-H)	10 - 80%
5 ms	Storage relative humidity (H-H)	5 - 90%
0.2745 x 0.2745 mm	Operating altitude	0 - 5000 m
93 ppi	Non-operating altitude	5000 - 12192 m
30 - 83 kHz	Weight & dimensions	
50 - 75 Hz	Width (with stand)	552.6 mm
52.7 cm		171 mm
29.6 cm	• • •	420.4 mm
60.47 cm		3.44 kg
×	Width (without stand)	5.44 kg 552.6 mm
	Depth (without stand)	49.7 mm
NTSC	Depth (without stand)	49.7 11111
	1920 x 1080 pixels Full HD 16:9 LCD VA LED ➤ 250 cd/m ² 8 ms ✓ Flat 3000:1 3000:1 3000:1 3000:1 3000:1 60 Hz 178° 178° 16.7 million colours 5 ms 0.2745 x 0.2745 mm 93 ppi 30 - 83 kHz 50 - 75 Hz 52.7 cm 29.6 cm 60.47 cm	60.5 cm (23.8")Energy efficiency class (SDR) *1920 x 1080 pixelsEnergy efficiency class (HDR) *Full HDEnergy consumption (SDR) per 10016:9Power consumption (SDR) per 100LCDPower consumption (typical) *VAPower consumption (standby) *LEDPower consumption (max)XPower consumption (off)250 cd/m²AC input voltage8 msAC input frequency✓Power supply typeFlatEnergy efficiency scale3000:1European Product Registry for60 HzOperational conditions178°Operating temperature (T-T)178°Storage temperature (T-T)16.7 million coloursOperating altitude93 ppiNon-operating altitude30 - 83 kHzWeight & dimensions50 - 75 HzWidth (with stand)2.7 cmDepth (with stand)29.6 cmDepth (with stand)60.47 cmWeight (with stand)

Display		Weight & dimensions	
Colour gamut	83%	Weight (without stand)	3.11 kg
Performance		Bezel width (side)	1.28 cm
NVIDIA G-SYNC *	×	Bezel width (top)	1.28 cm
AMD FreeSync *	Â	Bezel width (bottom)	2.23 cm
Flicker-free technology	7	Packaging data	
Low Blue Light technology	4	Package weight	5.29 kg
Multimedia		Packaging content	
Built-in speaker(s) *	×	Stand included	1
Built-in camera *	×	Cables included	AC, DisplayPort, VGA
Design		Quick start guide	1
Market positioning *	Business	Sustainability	
Product colour *	Black	Sustainability certificates	ENERGY STAR
Front bezel colour	Black	Doesn't contain	PVC/BFR
Detachable stand	1	Carbon footprint	
Feet colour	Black	Total carbon footprint (kg of CO2e)	504
Ports & interfaces		Total carbon emissions, standard deviation (kg of CO2e)	131
Built-in USB hub *	×	Carbon emissions, manufacturing	
VGA (D-Sub) ports quantity HDMI *	1	(kg of CO2e)	340
DisplayPorts quantity	1	Carbon emissions, logistics (kg of CO2e)	25
DisplayPort version	1.2	Carbon emissions, energy usage (kg	137
Headphone out *	×	of CO2e)	137
AC (power) in	1	Carbon emissions, end-of-life (kg of CO2e)	3
Network		Total carbon emissions, w/o use	367
Wi-Fi	×	phase (kg of CO2e)	
Ergonomics		PAIA version	1.3.1
VESA mounting *	✓	Other features	
Panel mounting interface	100 x 100 mm	Introduction year	2022
Cable lock slot *	<	Heavy metals free	Hg (mercury)
Height adjustment *	×	Compliance certificates	RoHS
Pivot	×		
Swivelling	×		
Tilt adjustment	4		
Tilt angle range	-5 - 21°		
On Screen Display (OSD)	4		
Plug and Play	4		
LED indicators	✓		



5397184656907

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.