



# Up-Angle Cat6 Gigabit Molded UTP Ethernet Cable (RJ45 Right-Angle Up M to RJ45 M), Blue, 5 ft. (1.52 m)

MODEL NUMBER: N204-005-BL-UP







### **Highlights**

- Space saving design
- Up Angle connector to Straight
- Cat6 Gigabit rated

#### **System Requirements**

 Use with Cat6, Cat5e, Cat5, or VoIP Networks

## **Package Includes**

5-ft. (1.52 m) Blue Cat6 Up Angle to Straight RJ45 - RJ45 Patch cable

#### **Features**

- 5-ft. (1.52 m) Blue Cat6, Up Angle to Straight RJ45 RJ45 Patch cable
- PVC 4 Pair Stranded Conductors, 24AWG
- Fully Molded Ends
- ETL Verified to TIA/EIA -568-B
- 550Mhz Gigabit Speed Rated

# **Specifications**

OVERVIEW		
UPC Code	037332167576	
Technology	Cat6	
PHYSICAL		
Cable Jacket Color	Blue	
Cable Jacket Material	PVC	
Cable Jacket Rating	СМ	
Cable Shielding	UTP	
Cable Outer Diameter (OD)	6.0 mm	
Number of Conductors	4 Pair	
Conductor Material	Stranded Copper	
Conductor Gauge	24 AWG	





Product Certifications	UL Listed; cUL Listed
STANDARDS & COMPLIANCE	
Griagiess Confilector	140
IP68 Rated Snagless Connector	No No
Antibacterial IDES Rated	No No
FEATURES & SPECIFICATIONS	No
FEATURES & SPECIFICATIONS	
Angled Connector	Yes
Wiring Configuration	EIA/TIA 568B
Connector Type	Molded
PoE Type	Type 2 PoE+ (30W, IEEE 802.3at)
Contact Plating	Gold
Crossover Wiring	No
Side B - Connector 1	RJ45 (MALE) - UP ANGLE
Side A - Connector 1	RJ45 (MALE)
CONNECTIONS	
IEEE Standards Supported	802.3an; 802.3at
Network Compatibility	1 Gbps (Gigabit)
Maximum Bandwidth as Tested	500 MHz
Bandwidth per TIA Standard	250 MHz
COMMUNICATIONS	
Storage Humidity Range	0% to 90% RH, Non-Condensing
Operating Humidity Range	0% to 90% RH, Non-Condensing
Storage Temperature Range	5° to 140°F (-15° to 60°C)
Operating Temperature Range	14° to 122°F (-10° to 50°C)
ENVIRONMENTAL	
Shipping Weight (kg)	0.07
Shipping Weight (lbs.)	0.16
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50
Cable Length (cm)	152.4
Cable Length (in.)	60
Cable Length (m)	1.52
Cable Length (ft.)	5





Product Compliance	CE (Europe); RoHS; IEEE 802.3an 10GBase-T; IEEE 802.3at PoE+; REACH; UKCA	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.